

PUMP TO PERFECTION

INDUSTRY EXCELLENCE, WHERE PERFORMANCE AND DURABILITY MEET

QPS6-460 SUBMERSIBLE PUMP









DESCRIPTION

Quadraflo durable performance pumps are designed to effectively power a wide range of applications. Providing efficient and reliable solutions for high volume industry pump standards.

Quadraflo QPS6-460 6" submersible pump model has a steel exterior that is robust and can withstand any environment. A mechanical design that uses a traditional double seal system to reduce corrosion during abrasive applications.



SPECIFICATIONS

Power Output 12 hp Max Flow 815 GPM Max Head 75 ft Speed 1750 RPM Voltage 460v Phase Three Amperage 13.0 Type Dewatering (high volume) Power Cable 32 ft pH Range 5 - 8 Max. Liquid Temp 60 Degrees F Weight 275 lbs	Discharge Size	6" NPT
Max Head 75 ft Speed 1750 RPM Voltage 460v Phase Three Amperage 13.0 Type Dewatering (high volume) Power Cable 32 ft pH Range 5 - 8 Max. Liquid Temp 60 Degrees F	Power Output	12 hp
Speed 1750 RPM Voltage 460v Phase Three Amperage 13.0 Type Dewatering (high volume) Power Cable 32 ft pH Range 5 - 8 Max. Liquid Temp 60 Degrees F	Max Flow	815 GPM
Voltage 460v Phase Three Amperage 13.0 Type Dewatering (high volume) Power Cable 32 ft pH Range 5 - 8 Max. Liquid Temp 60 Degrees F	Max Head	75 ft
Phase Three Amperage 13.0 Type Dewatering (high volume) Power Cable 32 ft pH Range 5 - 8 Max. Liquid Temp 60 Degrees F	Speed	1750 RPM
Amperage 13.0 Type Dewatering (high volume) Power Cable 32 ft pH Range 5 - 8 Max. Liquid Temp 60 Degrees F	Voltage	460v
Type Dewatering (high volume) Power Cable 32 ft pH Range 5 - 8 Max. Liquid Temp 60 Degrees F	Phase	Three
Power Cable 32 ft pH Range 5 - 8 Max. Liquid Temp 60 Degrees F	Amperage	13.0
pH Range 5 - 8 Max. Liquid Temp 60 Degrees F	Туре	Dewatering (high volume)
Max. Liquid Temp 60 Degrees F	Power Cable	32 ft
7 7 00 2 0g. 000 1	pH Range	5 - 8
Weight 275 lbs	Max. Liquid Temp	60 Degrees F
	Weight	275 lbs

FEATURES

Stainless steel strainer, shaft, impeller, outlet and hardware for maximum corrosion resistance

Pressure enclosed chamber mechanically sealed

Optimizes efficiency and maximum life span of pump

Components equipped for durable conditions

APPLICATIONS

- Construction
- Industrial
- Mining
- Waste Water
- Environmental
- Oil & Gas





POWER	DISCHARGE	VOLTAGE	PHASE	SPEED
12 HP	6"	460 VOLT	THREE	1750 RPM

QPS6-460 PERFORMANCE CURVE



