

PUMP TO PERFECTION

INDUSTRY EXCELLENCE, WHERE PERFORMANCE AND DURABILITY MEET

QPS2-120 SUBMERSIBLE PUMP





SUBMERSIBLE PUMP SERIES



DESCRIPTION

Quadraflo durable performance pumps are designed to effectively power a wide range of applications. Providing efficient and reliable solutions for high volume industry pump standards.



Quadraflo QPS2-120 2" submersible pump model has a steel exterior that is robust and can withstand any environment. A mechanical design that uses a traditional double seal system to reduce corrosion during abrasive applications.

SPECIFICATIONS

Discharge Size	2" NPT	
Power Output	1 hp	
Max Flow	100 GPM	
Max Head	60 ft	
Speed	3465 RPM	
Voltage	120v	
Phase	Single	
Amperage	13.0	
Туре	Dewatering (semi vortex)	
Power Cable	32 ft	
pH Range	5 - 8	
Max. Liquid Temp	104 Degrees F	
Weight	63 lbs	

FEATURES

Stainless steel strainer, shaft, impeller, outlet and hardware for maximum corrosion resistance

Pressure enclosed chamber mechanically sealed

Optimizes efficiency and maximum life span of pump

Components equipped for durable conditions

APPLICATIONS

- Construction
- Industrial
- Mining
- Waste Water
- Environmental
- Oil & Gas









POWER	DISCHARGE	VOLTAGE	PHASE	SPEED
4 110	Oll	100 MOLE		0.450 BBM
1 HP	2"	120 VOL I	SINGLE	3450 RPM

QPS2-120 PERFORMANCE CURVE



