

SUBMERSIBLE PUMP SERIES



[QPS10-460]

APPLICATIONS



Industrial



Oil & Gas



Waste Water



Environmental



Construction



Mining

SPECIFICATIONS

Discharge Size	10" ANSI
Power Output	75hp
Max Flow	4400 GPM
Max Head	120 ft
Speed	3600 RPM
Voltage	460v
Phase	Three
Amperage	150
Type	Dewatering (high volume)
Weight	820 lbs

DESCRIPTION

QUADRAFLO DURABLE PERFORMANCE PUMPS ARE DESIGNED TO EFFECTIVELY POWER A WIDE RANGE OF APPLICATIONS. PROVIDING EFFICIENT AND RELIABLE SOLUTIONS FOR HIGH VOLUME INDUSTRY PUMP STANDARDS.

QUADRAFLO QPS10-460 10" SUBMERSIBLE PUMP MODEL HAS A STEEL EXTERIOR THAT IS ROBUST AND CAN WITHSTAND ANY ENVIRONMENT. A MECHANICAL DESIGN THAT USES A TRADITIONAL DOUBLE SEAL SYSTEM TO REDUCE CORROSION DURING ABRASIVE APPLICATIONS.

FEATURES

Stainless steel strainer, shaft, impeller, outlet and hardware for maximum corrosion resistance

Pressure enclosed chamber mechanically sealed

Optimizes efficiency and maximum life span of pump

Components equipped for durable conditions

PERFORMANCE CURVE

