

Gfp 563TH-4RS

ProductionTop Heat Laminator

What's the best way to make your production even better? Shorten film loading time? Make fewer film changes? Increase throughput speed? The 563TH-4RS does all that and more.

MAXIMIZE PRODUCTIVITY

Inline Rotary Slitters

FAST ROLL CHANGES

Front/Rear Swing-out shafts

EASY LOADING

3" Aluminum Quick-Grip shifts

RUGGED DESIGN

Metal Alloy heaters

VERSATILE

Roll-to-Roll operation



overlamination • mounting • board pre-coating

Spend less time on set-ups and changeovers with swing-out supply shafts.

50% faster throughput and quick application changes save time, effort and money.



- Swing-out Quick-Grip supply shafts
- Drop-in Quick-Grip rewind shafts
- Photoelectric eye for safety
- Includes rear rewind with Rotary Slitters
- Swing-up feed table & 38" output height
- Metal Alloy heater reduces breakage
- 4.4" diameter rollers
- Roller gap measurement scale





Media Alignment disks keep supply rolls from telescoping

563TH-4RS

Rugged Design Professional Quality Proven Performance Economically Priced

Laminating Width	63"
Roller Diameter	4.5"
Roller Gap	1"
Rear rewind with Slitters	Included
Maximum temperature	140°F

Signs

Banners

POP Displays

Trade show
displays Graphic
mounting Photo
mounting
Dry-erase boards
Floor graphics
Window graphics
Vehicle graphics

APPLICATIONS

Laminating speed	0-20 ft/mir

Laminating Speed	0-20 10/11/11
Pressure adjustment	Hand Wheel
Heat method	Metal Alloy heater
Max. roll diameter	8" OD (top); 16" OD (bottom)
Supply Shafts	2 Swing-out
Tension Adjustment	Single knob
Power Supply	110v 12A
Power Consumption	1320W
Foot Pedal	Included
Stand with casters	Included
Net Weight w/ stand	491 lbs.

Shipping Dimensions (L \times W \times H) 89" \times 35" \times 52" 791 lbs.

Warranty:

1 year parts & labor.

Installation is available.



Bullseye Graphics 1085I Stark Road Starkville, MS 39759

Phone: (662) 273-3626 sales@bullseye-graphics.com