

UNDER CABINET LUMINAIRE ANTI-MICROBIAL FINISH HOSPITAL GRADE / MADE IN USA









Anti-microbial finish standard



COLOR CONSISTENCY <3 SDMC L70>72,000

80+CRI


90+AVAIL.



UNDER CABINET LUMINAIRE ANTI-MICROBIAL FINISH HOSPITAL GRADE / MADE IN USA

HOW TO BUILD YOUR FIXTURE

| How to build a part number | Product Series | Light Output | Color Temperature | Length in Inches | Lens Type | Housing Color | Typical extra charge options Suffix part # as required in the sequence below |
|-------------------------------|-------------------|--|---------------------------------|---|-------------|------------------------|---|
| Part number format | 13HC | N | 30K | -24 | -2 | -3 | -AMS |
| Choices | 13HC | N (Normal) H (High) V (Very high) (Custom: specify lumens) | 27K 30K 35K 40K 50K | -12 -18 -24 -36 -48 -60 -72 -84 -96 -108 -120 | -2= Frosted | -0= Satin -3= White | |



SPECIFICATIONS


Airey-Thompson 13HC Series having a cross section of 5" by 1-5/16" made from extruded aluminum with .060 minimum wall thickness and aluminum end caps with light leak gaskets and no visable fasteners and anti-microbial finish. Impact resistant frosted acrylic diffuser. Luminaire shall be equipped with a universal voltage FCC Title 47 Part 15 Class A or B compliant electronic driver to avoid RFI. The luminaire must be ETL Listed for damp locations, have a 5 year warranty and be made in the USA.



UNDER CABINET LUMINAIRE ANTI-MICROBIAL FINISH HOSPITAL GRADE / MADE IN USA


- Construction: extruded 6063T-5 aluminum base and cover with .060 minimum wall thickness, aluminum end caps with light leak gaskets and no visable fasteners, extruded high impact frosted acrylic lens.
- Voltage: Equipped with integral, electronic 120/277v LED driver, FCC Title 47 Part 15 compliant.
- Mounting: Two mounting slots. For continuous row mounting simply remove end caps where luminaires meet and use the provided internal coupler to make a seamless link.
- Finish: Powdercoat anti-microbial white standard, anti-microbial gray optionally available. consult factory for custom finishes.
- Warranty: 5 year limited warranty, see Airey-Thompson distributor terms for details.


- LED'S: Premium LED chips used deliver up to 124 lumens per watt on the system level. Three standard light output options: Normal (545 Lm/FT), high (780 LM/FT), and very high (1090 LM/FT). custom light output programing available. 80+ CRI standard, 90+ available. Color consistency <3SDMC. 27K, 30K, 35K, 40K, and 50K Color temperature LED's are available.
- **Dimming:** Two dimming options available 10% 0-10V dimming 1% 0-10V dimming.
- Housing: Powder coat
 anti-microbial white finish is standard,
 anti-microbial satin aluminum option
 available.
 - **Listing**: ETL Listed damp location.





UNDER CABINET LUMINAIRE ANTI-MICROBIAL FINISH HOSPITAL GRADE / MADE IN USA





| NORMAL OUTPUT FIXTURES | | | | | | | |
|------------------------|---------|--------|--|--|--|--|--|
| LENGTH | WATTAGE | LUMENS | | | | | |
| 12" | 4.4 | 545 | | | | | |
| 24" | 8.8 | 1090 | | | | | |
| 36" | 13.2 | 1635 | | | | | |
| 48" | 17.6 | 2180 | | | | | |

| HIGH OUTPUT FIXTURES | | | | | | |
|----------------------|---------|--------|--|--|--|--|
| LENGTH | WATTAGE | LUMENS | | | | |
| 12" | 6.3 | 781 | | | | |
| 24" | 12.6 | 1562 | | | | |
| 36" | 18.9 | 2343 | | | | |
| 48" | 25.2 | 3124 | | | | |

| VERY HIGH OUTPUT FIXTURES | | | | | | |
|---------------------------|---------|--------|--|--|--|--|
| LENGTH | WATTAGE | LUMENS | | | | |
| 12" | 8.8 | 1090 | | | | |
| 24" | 17.6 | 2180 | | | | |
| 36" | 26.4 | 3270 | | | | |
| 48" | 35.2 | 4360 | | | | |