



- PART NO. 51128901 48" OAL WITH END CAPS**
51128902 48" OAL WITH OUT END CAPS
51228901 96" OAL WITH END CAPS
51228902 96" OAL WITH OUT END CAPS

The 51 series is a high performance, energy efficient lighting system designed to excel in Central Office and Data Center aisle applications.

SPECIFICATIONS

- Condensed width presents minimum restriction to HVAC air flow into the aisle.
- Very shallow design allows mounting in aisles where head room is a concern.
- Extruded satin anodized aluminum housing.
- High efficiently F28T5 lamp/s included.
- High power factor universal voltage (120/277) program start electronic ballast standard.
- Rugged clear prismatic polycarbonate diffuser provides lamp protection.
- Hanger brackets securely support the luminaire anywhere along it's length, for easy mounting.
- Luminaires may be mounted individually or in continuous rows.
- Snap-in covers provide access to the wiring compartment with minimum disassembly.
- Coupler and wire nuts are provided to make connecting luminaires fast and easy.
- 14 ga through wires consist of a power circuit plus 2 yellow wires for 3 way switching. This allows for a 92' continuous row @ 120V.
- All luminaires are Underwriters Laboratories listed file # E 78045

RELATED COMPONENTS	
PART NO.	DESCRIPTION
5101A	TOP FEED END ASSY.
5101	FEED END ASSEMBLY
5102-XX	TRAPEZE HANGER BRKT. (where "XX" matches the width of the fiber tray)
5102U	HANGER FOR UNISTRUT
5110B	BLANK END FITTING

