



# AIRCOLOR STONEX stonechip

## H35

VERSION: 230606  
Page: 1/2

### STONECHIP PROTECTOR

#### DEFINITION



**AIRCOLOR STONEX stonechip** is an elastic, noise-reducing and anti-corrosive product. It protects the vehicles bodies, metal and paint from impact by using its elasticity to absorb the shock and protects from impacting debris. For this reason, it is recommended for treating all the underside parts of the body, plus door-bottoms, wheel-arches, etc. Its soundproofing properties make its use advisable inside the bonnet and boot, since it effectively reduces vibration.

Once dry, the excellent texture allows it to be painted with bodywork basecoat paints, achieving a perfect gloss level.

#### PHYSICAL CHARACTERISTICS

|                          |                                                          |
|--------------------------|----------------------------------------------------------|
| <b>Nature:</b>           | Elastomers and synthetic resins                          |
| <b>Propellant:</b>       | DME                                                      |
| <b>Colour:</b>           | Black, Light grey                                        |
| <b>Specific weight:</b>  | 9.5-9.8 lb/gal @ 68°F                                    |
| <b>Aerosol pressure:</b> | 60.9 ± 0,5 psi @ 68°F                                    |
| <b>VOC:</b>              | 4.5 lb/gal Application 2004/42/EC - IIB (e)(4.04 lb/gal) |
| <b>PWR:</b>              | Category: ABT<br>Category limit: 1.70                    |

#### APPLICATION METHOD


|                                                                                     |                                                                                     |                                                                                     |                                                                                      |                                                                                       |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
|  |  |  |  |  |
| Nozzle kind:<br>White +<br>Cannula                                                  | 2 min                                                                               | 8-12 inches                                                                         | 2 coats                                                                              | 5 min                                                                                 |

#### DRYING TIMES

|                                                                                     |                                                                                     |                                                                                     |                                                                                       |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
|  |  |  |  |
| 68°F                                                                                | 10-15 min                                                                           | 30 min                                                                              | 1 hr                                                                                  |

**REMARKS**

Sand the area to be protected and, clean, dry and remove grease with a suitable degreaser.  
Protect the areas that will not be painted.  
Shake the aerosol before use for approx. 2 minutes after hearing the sound of steel ball mixers.  
It is also recommended to shake it well during the application process.  
The aerosol has a standard nozzle and an extendable nozzle (tube). The nozzle with extension allows you to reach difficult to access areas. The desired texture of the finish is obtained by varying the application distance and the number of coats.  
Drying time depends on temperature, humidity and film thickness that has been applied.

**EQUIPMENT CLEANING****SAFETY**

Follow instructions of product label. For more information check the Safety Data Sheet.  
Compliant with the National Statutory Regulation for Health and Safety at Work and Waste Disposal.

**STORAGE**

Store the product in a ventilated place far from direct exposure to sunlight. Keep between +40°F and +90°F.

**GUARANTEE**

One year in unopened original packaging.

*These products are for professional use only. The Safety Data Sheet should be consulted before use and the precautionary warnings on the product packaging should be observed. Its correct use, according to its purpose and respecting its technical and security data, provided in these documents, is the sole and exclusive responsibility of the user. ROBERLO S.A.U declines any liability due to the incorrect use of any product.*

*The information included in this documentation is based on our scientific and technical knowledge on the date of its issuance. ROBERLO S.A.U reserves the right to modify and/or discontinue all or part of the information at any time and without prior notice. It is the user's responsibility to verify the update of the information. The latest version of this document replaces all previous versions.*

*All clauses contained herein apply to any future changes or modifications.  
For any additional technical information please consult with our Customer Service or our Technical Department.*