Uniclass	L5367	EPIC E42
CI/SfB		Х
April 2020		



Entrance Flooring Systems





creating better environments

# coral®

### The first steps in protecting your building

There's a way to keep your floor and premises looking clean and presentable year in year out, as well as a way to offer your visitors and employees a safe and hygienic environment. All you need is a well thought-out entrance system.

Forbo Coral entrance flooring delivers superior performance in even the toughest environments. Whether facing rain, snow, sand or soil, Coral keeps the outside from getting inside. Coral entrance floors are highly functional and, through their design options, always form an integral part of the building's design scheme.

Coral has been the international market leader in textile entrance flooring for almost 50 years and now offers you more choice than ever before. Each individual range in the collection has been designed to interact with different soiling behaviour as every entrance is a unique environment.



# Contents

- 2 Introduction
- 4 Why choose Coral?
- 8 Coral Click
- 10 Coral Welcome
- 12 Coral Brush
- 14 Coral Classic
- 16 Coral Duo
- 18 Coral Logo
- 20 Coral Tiles
- 22 Nuway
- 24 Technical table
- 26 More Flooring
- 27 What to do next





### WHY CHOOSE CORAL?



### **REDUCTION in cleaning time**

Cleaning Research International has shown that the cost of maintenance is 86% of the total life cycle cost of commercial floor coverings. A well designed Coral entrance flooring system incorporating a 3-step clean-off zone is a highly effective way to cut your future maintenance costs. By stopping up to 95% of walked-in dirt and moisture from reaching your building's floors, Coral can reduce cleaning time for floor coverings by up to 65% and prolong the life of your floor finishes and coverings.

# coral® nuway®

Coral can be used alongside Nuway entrance flooring to further protect your interior space.

Many Coral products use Econyl<sup>®</sup> yarn which is made from used and abandoned fishing nets.



Using Econyl<sup>®</sup> is a way to reduce existing waste, avoid additional manufacturing-related pollution, and keep the

consumption of natural

resources and energy

to a minimum.

coral<sup>®</sup> classic and coral<sup>®</sup> brush are available in tile format for increased flexibility and reduced installation waste.

......

**Enhance your entrance** 

flooring by using

**Coral Logo to express** 

your logo or identity.

**MODULARITY** 

recycled content in



landfill Virtually zero landfill is

achieved by the Coral manufacturing plant.

Many Coral ranges are available with an FR version for fire sensitive areas.

### **Coral pays for itself** within 6 months

**Produced with** 

### green electricity from renewable resources

All the electricity we buy comes from renewable sources. This means our Coral production site is part of an effective environmental management system and has achieved ISO 14001 certification.



### WHY SHOULD YOU CHOOSE CORAL **ENTRANCE MATTING FOR YOUR BUILDING?**

### **ONLY CORAL HAS BEEN PROVEN TO STOP UP TO 95%** OF DIRT AND MOISTURE ENTERING A BUILDING

**Cleaning Research International** has proven that equipping an entrance with 6m<sup>2</sup> of Coral entrance flooring is enough to keep up to 95% of all walked in dirt and moisture out of your building.

### **ONLY CORAL** HAS BEEN PROVEN TO REDUCE CLEANING TIMES OF FLOOR COVERINGS BY UP TO 65%

Cleaning Research International has shown that the cost of maintenance is **86%** of the total life cycle cost of commercial floor coverings.

Coral can reduce cleaning time for floor coverings by up to 65% and prolong the life of your floor finishes.

### CORAL'S UNIQUE CONSTRUCTION **ALLOWS FOR EASIER CLEANING!**

Coral is a **cut pile** product with ultra tough scraper yarns and bulk continuous filament yarns which allows for dirt to easily be released during cleaning, meaning the product **recovers** as new and continues to perform • •

### **ONLY CORAL** PAYS FOR ITSELF IN 6 MONTHS!

A well designed **Coral** entrance flooring system is an investment, not a cost.


By reducing cleaning times **by up to 65%**, the savings made mean that the product and fitting costs for Coral are recouped within 6 months of use!



### **EXTEND YOUR FORBO PRODUCT'S WARRANTY WITH CORAL!**

We're so confident in the dirt stopping performance recovery capabilities\* of our Coral products, that when you combine them with another Forbo interior floor covering product we will increase that product's warranty by 2 years! Some examples are shown below.

> general purpose vinyl 12 year warranty with Coral. www.forbo-flooring.co.uk/eternal




For more information on the extended product warranties when combined with Coral, please visit www.forbo-flooring.co.uk/downloads and download the relevant product's guarantee statement.

\*When products have been cleaned and maintained in accordance with recommended Forbo quidelines

### modul'up

adhesive free vinyl 12 year warranty with Coral. Modul'up is part of our Fast Fit collection visit www.forbo-flooring.co.uk/modulup for more details.





#### **ENTRANCE FLOORING STARTS OUTSIDE AND BRINGS YOU INSIDE**

If you really want to keep your building clean and safe, it's not enough to just put down an entrance mat in front of the door.

Creating a good entrance flooring system means thinking about footfall – the number of people walking in and out in a given period - and walking routes (the directions they take once inside) and applying that information in the design of the entrance area.

One of the best ways to plan an entrance flooring system is to think in terms of applications. The table opposite is designed to help you select which Coral entrance product best meets your needs.

#### INTENSE TRAFFIC AREAS AND HIGH POINT LOADS

For those entrances with extreme footfall, wheeled traffic or outside entrances, such as shopping centres, leisure outlets or transport hubs, our Nuway range of rigid entrance systems may be more suited to your needs.

For further information, please ring **0800 731 2369** for a Forbo Entrance Flooring Systems brochure or visit www.forbo-flooring.co.uk/nuway





# APPI ICATION

APPLICATION

coral<sup>®</sup>click coral®duo coral<sup>®</sup> brush coral<sup>®</sup>welco

### **Coral pays for itself in 6 months**

A well designed Coral entrance flooring system is an investment, not a cost.

Testing by Cleaning Research International has shown that by stopping up to 95% of walked-in dirt and moisture, Coral reduces the time spent cleaning the building's other floor coverings by up to 65%.

The savings made within 6 months means that the product and fitting costs for Coral are recouped within 6 months of use! For full details go to www.forbo-flooring.co.uk/coralpayback

### CONSIDERATIONS

The Coral textile range of entrance flooring products is suitable for use with wheelchairs and perambulatory wheeled traffic. For areas with multiple direction traffic flow, the use of Coral Classic or Coral Brush is recommended, as these Coral ranges are constructed to provide a multi-directional surface pile which limits potential for resistance to movement.

#### entrance flooring applications

OUTSIDE USE (NUWAY ONLY) Any matting placed outside the building entrance creates the first line of defence against foot-borne soil by scraping the coarsest dirt from the soles of shoes before they cross the threshold.

#### INSIDE USE

Moving inside, the next line of defence, is used to remove moisture and finer dirt particles from all feet entering the building.

#### OTHER CIRCULATION AREAS

Other areas in the building also suffer from soil and moisture; reception areas, corridors, walkways to other parts of the building, elevators, staircases, exits, etc. All these areas are prone to residual soiling and will benefit highly from a purposely designed Coral entrance floor to absorb this soiling.

A	oplicatio	on 🔛		ECO	
<b>coral</b> <sup>®</sup> click	2	••••	<b>●●●</b> 0	••00	1
<b>coral</b> ®duo	2	•••0	••••	••00	1
coral <sup>®</sup> brush	2 + 3	••••	<b>●●●</b> 0	•••0	1
coral <sup>®</sup> welcome	2+3	••••	•••0	••••	1
coral <sup>®</sup> classic	2 + 3	••••	●●00	••00	1
coral <sup>®</sup> logo	2 + 3	•••0	●●00	•000	1

# coral<sup>®</sup> click

# The first steps in protecting your building

Coral Click is an exceptionally versatile 'off the shelf' modular matting system that can be assembled on site. Coral Click can be used on its own or in conjunction with our Coral clean-off textile ranges to provide an integrated entrance system.

This versatile PVC tile with Coral textile inserts can be used in all types of buildings and, because it contains no metal components Coral Click entrance products are particularly suitable for installation in the retail environment as they do not interfere with electronic-tagging systems.



- · 'Off the shelf' modular matting system
- Exceptionally easy to fit, handle and store
- Available in 12mm & 17mm depths
- Textile inserts from the award winning Coral Brush collection
- Coral Brush insert is 100% ECONYL regenerated yarn
- Coral entrance flooring systems removes up to 95% of dirt and moisture from shoes and wheeled traffic
- 5 year guarantee
- · Closed structure to prevent heel trap







7830 (12mm) | 7880 (17mm)

Coral Click can be teamed up with our award-winning Coral Brush (sheet or tile) ranges.

7831 (12mm) | 7881 (17mm)



Coral Click 7831 (12mm) 7881 (17mm)








LRV 2 7833 (12mm) | 7883 (17mm)





LRV 2

7837 (12mm) | 7887 (17mm)



7838 (12mm) Plain | 7888 (17mm) Plain LRV 4

# coral<sup>®</sup> welcome

# Where design meets environment

With its contemporary linear design and rich, deep pile, Coral Welcome packs the style and aesthetic appeal of a luxury carpet. It makes an unequivocal statement in any entrance area.

Coral Welcome is more than just a fabulous looking floor covering – it's an environmentally advanced one as well. The secret lies in its use of ECONYL® 100%-regenerated yarn, which is made from regenerated industrial and postconsumer waste. Abandoned fishing nets are one of the sources. Taking the environmental aspect even further, the primary backing is made from recycled PET bottles.



- 100% of the yarn in Coral Welcome is Econyl<sup>®</sup> regenerated solution dyed polyamide
- Primary backing made from recycled PET bottles
- Prevents moisture and dirt being tracked onto interior surfaces
- Striking linear aesthetic which makes a design statement in any entrance
- · Complies with the highest fire class standard for a textile product: B<sub>fl</sub>-s1
- Suitable for heavy contract use: wear class 33
- · Ideal for interior entrances and circulation areas



# coral<sup>®</sup> brush

### The great all-rounder


Coral Brush is suitable for all types of entrance areas, absorbing moisture and removing dry soiling as the weather demands. Created around simple, solid and linear designs, this collection works well with any interior, serving as an eye-catcher or self-effacing support for the rest of the floor design.

Coral Brush is made of three types of yarn, each offering a different benefit, while the space between the yarns serves to hide dirt, which ensures a clean appearance for longer.

The Coral Brush range is also available in tile format for increased flexibility. See page 20 for more information.



- Functional all-rounder that removes both moisture and dirt
- 100% of the yarn in Coral Brush is Econyl® regenerated solution dyed polyamide
- Appealing solid and linear designs
- Complies with the highest fire class standard for a textile product: B<sub>f1</sub>-s1
- Suitable for heavy contract use: wear class 33
- Ideal for interior entrances and circulation areas
- Available in sheet, mats and 50 x 50 cm tiles







Coral Brush offers a choice of 18 colourways that can be used with each other or in combination with other Coral ranges.



LRV 3 5710 asphalt grey

LRV 2

# coral<sup>®</sup> classic

## The ultimate moisture absorber

Research shows that taking just two steps on Coral Classic's moisture absorbing yarns is enough to absorb half of the foot-borne moisture that would otherwise be carried inside on the soles of people's shoes.

A few steps more and your feet are as dry as possible. This has clear benefits. First, the interior floor coverings stay cleaner, longer. Second, resilient floors such as vinyl, ceramics, wood and concrete are less likely to become slippery and dangerous.


Independent tests have shown that Coral Classic will maintain its performance and appearance – for years to come thanks to the use of solution dyed yarns that guarantee its appearance throughout its lifespan.

#### The Coral Classic range is also available in tile format for increased flexibility. See page 20 for more information.



- Maximum moisture absorption and effective dirt removal
- Choice of practical colourways

- Complies with the highest fire class standard for a textile product: B<sub>fl</sub>-s1
- Suitable for heavy contract use: wear class 33
- · Ideal for interior entrances and circulation areas
- Available in sheet, mats and 50 x 50 cm tiles



# coral<sup>®</sup> duo

## The ultimate dirt and moisture remover


A short entrance and clean interior floor coverings don't go together, do they? Well, yes, they can. Coral Duo is the ideal solution when you need maximum dirt removal, unrivalled dirt retention and exceptional moisture absorption, all in just a couple of paces.

Research has shown that Coral Duo retains 10% more dirt in the first few metres than any other textile entrance flooring solution on the market. Which makes it the best choice for smaller entrances. Featuring a ribbed construction. Coral Duo is not only functional, it also provides an aesthetically pleasing aspect to any entrance area and is easy to combine with our Coral Brush and Coral Classic collections.

The direction in which Coral Duo is produced is not the traffic direction. Coral Duo should be installed with the ribs at right angles to the direction of traffic.



- Ideal solution for most entrances and especially smaller entrances
- 75% of the yarn in Coral Duo is Econyl® regenerated solution dyed polyamide
- Unbeatable performance for moisture and dirt removal
- · Complies with the highest fire class standard for a textile product: B<sub>fl</sub>-s1
- Suitable for heavy contract use: wear class 33
- Ideal for interior entrances and circulation areas







# coral<sup>®</sup> logo

### Make a lasting impression

Forbo has the capability to offer a bespoke print or cut-out design service that can be tailored to your precise design specification, offering individuality and a unique point of difference.

Our Coral Logo collection offers a wide range of bright attractive colours. Depending on the colours and design of your corporate identity, you can choose between a printed mat or one with a cut inset logo. The Coral Logo collection is designed to the same standards as all other Coral products, which means it will retain its looks whilst keeping out dirt and moisture for years to come.




### Printed logo mat

- Excellent visual quality and bright colouring
- Best to use for complicated designs with multiple colours
- 42 standard colours available
- Pantone and RAL colours can be matched

#### Cut inset logo mat

- Best to use for extreme traffic conditions and maximum functional performance.
- Any colour from the standard Forbo Coral collection can be used for the base background and logo colours.
- Easy to combine as inlay in larger Coral installations.



### coral<sup>®</sup> logo Technical specifications

í ×	Total thickness	ISO 1765	
	Wear classification	EN 1307	
	Available sizes		
t de la companya de	(all sizes are approx.) Roll sizes with 2.5 cm		
	edge each side		
B	Mat sizes with 2.5 cm edge all sides		
	Colour fastness ratings:		
- Fr	Light	EN ISO 105/B02	
	Rubbing	EN ISO 105/X12	
	Water	EN ISO 105/E01	
	Manufacturing method/ty	ре	
	Designs		
	Pile material		
	Tuft base		
	Backing phthalate free vin	yl	
ĥ	Total weight	ISO 8543	
	Pile installation weight	ISO 8543	
Ť	Pile thickness	ISO 1766	
	Pile density	ISO 8543	
	Number of tufts	ISO 1763	
<b>~</b>	Comfort class	EN 1307	
	Other remarks		

		Coral Log	jo (43xx)*
Total thickness	ISO 1765	Appro	к. 8 mm
Wear classification	EN 1307	31, comm	ercial light
Available sizes		Standard mat sizes (sizes with edges)	Special sizes (sizes without edges
(all sizes are approx.) Roll sizes with 2.5 cm		55 x 90 cm	any width, any length
edge each side		105 x 155 cm 105 x 300 cm	
Mat sizes with 2.5 cm		155 x 197 cm 155 x 300 cm	
edge all sides		197 x 197 cm 197 x 300 cm	up to 192 cm wide
Colour fastness ratings	:		
Light	EN ISO 105/B02	>	- 5
Rubbing	EN ISO 105/X12	4	-5
Water	EN ISO 105/E01	4	-5
Manufacturing method/1	type	Tufted, 1/	8″ cut-pile
Designs		Hi-definition	custom print
Pile material		100% High Twist	Nylon polyamide
Tuft base		Non-wove	n polyester
Backing phthalate free vi	inyl	EVERFC	DRT vinyl
Total weight	ISO 8543	Approx. 33	50 gram/m <sup>2</sup>
Pile installation weight	ISO 8543	Approx. 68	30 gram/m <sup>2</sup>
Pile thickness	ISO 1766	Approx	x. 5 mm
Pile density	ISO 8543	0.113 g	ram/cm <sup>3</sup>
Number of tufts	ISO 1763	Approx. 1	10.000/m <sup>2</sup>
Comfort class	EN 1307	Ŀ	C2
Other remarks		Moisture absorptic Production tolera	apacity: 600 g/m <sup>2</sup> on capacity: 3-4 l/m <sup>2</sup> ance of 5% on size colour
All Coral products meet t excluding loose-laid mat		EN 14041,	<b>CE</b> N 1404
Fire behaviour	EN 13501-1	B <sub>f</sub>	-s1
Slip resistance	EN 13893	C	DS
Personal charging		<2	2 kV

For more information, please visit www.forbo-flooring.co.uk/corallogo



09
39
05

# **coral**<sup>®</sup> tiles

# **coral**<sup>®</sup> brush tiles

#### Coral tiles combine all the moisture absorbing properties of Coral Classic and Coral Brush but with the flexibility that comes with 50 x 50cm tile formats. Using Coral tiles can reduce off-cut waste and also allows for guicker installation. This is particularly relevant when downtime or retail store opening times are at stake. In addition, opting for 50 x 50cm tiles provides more flexibility in installation and also allows easier storage and handling.

Coral tiles are available in all the colours from the Coral Classic and Brush collections and can be combined to provide a very functional, yet very attractive entrance. Coral tiles offer the same product features as the Coral Classic and Brush sheet ranges. The tiles can be laid monolithic or tessellated.

#### The great all-rounder.

- Functional all-rounder that removes both moisture and dirt
- Available in 18 colourways
- 100% of the yarn in Coral Brush is Econyl® regenerated solution dyed polyamide
- Appealing solid and linear designs
- Complies with the highest fire class standard for a textile product: B<sub>fl</sub>-s1
- Suitable for heavy contract use: wear class 33
- · Ideal for interior entrances and circulation areas
- Available in sheet, mats and 50cm x 50cm tiles

# LRV 11 T5716 | masala brown LRV 5 T5724 | chocolate brown LRV 2 T5754 | straw brown T5714 | shark grey LRV 5 T5767 | slate blue LRV 3 T5764 | petrified grey LRV 5 T5715 | charcoal grey LRV 2

T5727 | stratos blue LRV 2 T5722 | comflower blue LRV 4 T5709 | royal purple LRV 2 T5730 | vulcan black LRV 1 T5710 | asphalt grey LRV 2 T5741 | cannon grey LRV 2



# **coral**<sup>®</sup> classic tiles

#### The ultimate moisture absorber.

- Maximum moisture absorption and effective dirt removal
- Available in 13 colourways
- Choice of practical colourways
- Complies with the highest fire class standard for a textile product: B<sub>fl</sub>-s1
- Suitable for heavy contract use: wear class 33
- · Ideal for interior entrances and circulation areas
- Available in sheet, mats and 50cm x 50cm tiles





T4764 | taupe

### nuway®

The recognised market leader in engineered entrance flooring systems, Nuway offers a wide range of rigid single and double sided made-to-order mats which provide an outstanding first line of defence against soil and moisture entering a building on the soles of shoes and the treads of wheeled traffic.

### **Double Sided Systems**

- Nuway Tuftiguard Our best-selling range with long term dirt removal for intense traffic locations and now available with Bamboo and Black Anodised Aluminium variants.
- Nuway Tuftiguard HD Removes soil in intense traffic areas, under the highest loads.

### **Single Sided Systems**

- Nuway Connect Versatile roll up system with a wide choice of inserts, including Coral and bristle. Suitable for shaping on site and very heavy traffic areas.
- Nuway Grid Tough, economical and aesthetically versatile entrance flooring. Available in a wide choice of inserts including Coral Classic and Coral Brush.

### Choice of construction

Most Nuway products are available in a choice of heights and in open or closed construction to meet the requirements of a wide range of entrances.

#### Integrated Entrance Solutions

By using Forbo Coral as the insert material in our single sided Nuway products, it's possible to design a Nuway rigid entrance system where the Coral textile clean-off area matches beautifully.

For more information on Nuway entrance systems, please visit



Forbo's Nuway collection offers value for money alternatives in entrance systems www.forbo-flooring.co.uk/nuway where the level of traffic is very heavy and where aesthetics are key.



### WHAT DO I NEED TO CONSIDER?

Where to use?	Internal or External?	Reversible	Finishes -	Reversible	Removes Moisture	Which should I choose?	Guarantee
	EXT		Scraper bars	Wiper strips	×		GUARANTEE UP TO YEARS
The location, type and level of traffic affects the choice of product.	Product outside will defend against soil and the coarsest of	Double sided rigid entrance systems can be reversible, effectively	and scraper bars/ca allow our Nuway e	oice of wiper strips arriers and inserts to entrance systems to all interior finishes.	Removing moisture from the soles of shoes is vital to prevent	Each product in our Nuway collection offers differing benefits	Standard Guarantee is up to 10 years, depending on the product.
or product.	foot-borne dirt. Inside it will defend against foot-borne moisture and finer dirt	dirt. doubling their lifespan. vill ainst Please see the table below e to see which	Scraper Bars As the name suggests, they scrape soil from the traffic walking across the entrance system.	Wiper Strips Prime rubber and polyamide fibre remove moisture and fine dirt	slipping.	and features.	Installations by FESSI's (Forbo Entrance System Specialist Installer) have an extended guarantee*.
	particles.	are reversible.	Single sided carriers	Single sided inserts			
			with crimping action to secure insert.	Mix and match with Ultragrip rubber, bristle and a wide range of Coral inserts which allow colour co-ordination with interior finishes.			
	Applicatio	on internet	der *	Intense traffic	Extreme point loading	Reversible	Guarantee
<b>nuway</b> ® tuftiguard	1 + 6			\$\$P\$\$P		CDOUBLEC C378000C	15 years*
<b>nuway</b> ® tuftiguarc	IHD <b>1</b> + <b>6</b>			\$\$0\$\$0	μ	CDOUBLEC COUBLEC	15 years*
nuway <sup>®</sup> connect	1 + 6					#SINGLE#	7 years*
<b>nuway</b> ® grid	1 + 6					#SINGLE#	7 years*

\*Nuway installations undertaken by a Forbo Entrance System Specialised Installer (FESSI) are guaranteed for up to 15 years (7 years for Bamboo).

### Coral technical specifications

				<b>l Click</b> Brush insert		<b>l Click</b> extile insert		/elcome xx)*		Brush xx)*		
	Fotal thickness	ISO 1765	14 mm	19 mm	11 mm	16 mm	Approx	κ. 9 mm	Approx	к. 9 mm		
)   	Wear classification	EN 1307					33, comme	ercial heavy	33, comme	ercial heavy		
(	Colours			5		1		3	1	8		
	Available widths						Rolls	Mats	Rolls	Mats		
Ē	all widths are approx.) Roll widths include 2.5 cm						205 cm	105 x 155 cm	105 cm	55 x 90 ci		
	edge each side								155 cm	90 x 155 c		
	Mat widths include 2.5 cm edge all sides								205 cm	135 x 205		
							Roll lengths approx. 27.5 m		Roll lengths approx. 27.5 m	205 x 300		
٦	Tile sizes			24 cm box = 1.37 m²)		24 cm box = 1.37 m <sup>2</sup> )		-		-		
Ċ	Colour fastness ratings:		(	,								
3	Light	EN ISO 105/B02	:	>5		-		7	>	⊳5		
	Rubbing	EN ISO 105/X12		5		-		5		5		
_	Water	EN ISO 105/E01	4	-5		-	4	-5	4	-5		
_	Seawater	EN ISO 105/E02	4	-5		-	4	-5	4	-5		
-	Waterstains	EN 1307 annex G		5		-		5		5		
_	Shampoo	BS 1006		-5		-		-5		-5		
-	Organic solvents	EN ISO 105/X05	4	-5		-	4-5		4	-5		
1	Manufacturing method/type		Injection	moulding	Injection	moulding	Tufted, 5/3	Tufted, 5/32" cut-pile		32″ cut-pile		
[	Designs						Multi-colo	ured linear	Plain designed	coloured ble		
F	Pile material		100% regenerat	ed Econyl® Nylon		-	100% regenerat	ed Econyl® Nylon	100% regenerat	ed Econyl® Ny		
1	Tuft base		Non-wove	n polyester		-	100% r non-woven	ecycled PET/Econyl®	Non-wove	n polyester		
E	Backing (phthalate free vinyl)						EVERFC	RT vinyl	EVERFORT vinyl			
י	lotal weight	ISO 8543	0.4	6 kg	0.4	6 kg	Approx. 39	50 gram/m²	Approx. 40	50 gram/m²		
F	Pile installation weight	ISO 8543					Approx. 75	i0 gram/m²	Approx. 92	20 gram/m²		
Ē	Pile thickness	ISO 1766					Approx	6.3 mm	Approx	к. 7 mm		
F	Pile density	ISO 8543					0.111 g	ram/cm³	0.105 g	ram/cm³		
1	Number of tufts	ISO 1763					Approx 7	79300/m²	Approx.	58000/m²		
2	Comfort class	EN 1307	Ŀ	C3			L	[3	L	C3		
۔ ا	Creating Better Environments											
$\langle  \rangle$	Renewable Electricity		All Coral proc	ducts are manufa	ctured using 100	% electricity ma	de by renewable s	ources.	<u> </u>			
5	Recycled content						23	3%	23	3%		
-	AgBB/DiBt						Pa	iss	Pa	ass		
(	Guarantee						provided it has be rbo requirements			nised		
I	nstallation method	EN 1307	Contractor and regularly maintained in accordance with the Forbo requirements currently in force.   Monolithic, brick, half drop, tessellated, quarter turn or quarter turn mirrored Coral sheet product should alw				ered					
,	All Coral products meet the	e requirements of	EN 14041. Not	e: the requirem	ents of EN 14	)41 do not ap	ply to loose laid	mats and rugs	i.	C EN 14		
	Fire behaviour	EN 13501-1					B <sub>fi</sub>	-s1	B <sub>fi</sub>	-s1		
	Slip resistance	EN 13893					C	S	C	DS		
5.	Personal charging	ISO 6356	1				< 7	kV	< 2	2 kV		

\* Also available with fire retardant backing. \*\* Depending on colour. Visit www.forbo-flooring.co.uk/coral for more details.

26

Coral Classic (47xx)*		Coral Duo (97xx)*		Coral Brush Tile (T57xx)*	Coral Classic Tile (T47xx)*
Appro	vx. 9 mm	Approx	. 9 mm	Approx. 9 mm	Approx. 9 mm
33, commo	ercial heavy	33, comme	rcial heavy	33, commercial heavy	33, commercial heavy
1	13	5	3	18	13
Rolls	Mats	Rolls	Mats		
105 cm	55 x 90 cm	205 cm	No mats		
155 cm	90 x 155 cm				
205 cm	135 x 205 cm				
Roll lengths approx. 27.5 m	205 x 300 cm	Roll lengths a	pprox. 27.5 m		
	-	-		Size: 50 x 50 cm (12 tiles in a box = 3 m <sup>2</sup> )	Size: 50 x 50 cm (12 tiles in a box = 3 m
7	7-8	>	5	>5	7-8
4	1-5	4-	-5	5	4-5
4	1-5	4-	-5	4-5	4-5
4	1-5	4	5	4-5	4-5
	1-5	5		5	4-5
	1-5		-5	4-5	4-5
	1-5	4-		4-5	4-5
Tufted, 5/	32" cut-pile	Tufted, 5/3	2″ cut-pile	Tufted, 5/32" cut-pile	Tufted, 5/32" cut-pile
Multi coloured d	lesigned/coloured	Ribl	bed	Plain designed/ coloured blend	Multi coloured designed/coloured
100% polyamide	-BCF solution dyed	100% polyamide is regenerated		100% regenerated Econyl® Nylon	100% polyamide-BCF solution dyed
Non-wove	en polyester	Non-wover	n polyester	Non-woven polyester	Non-woven polyester
EVERFO	ORT vinyl	EVERFO	RT vinyl	EVERFORT vinyl	EVERFORT vinyl***
Approx. 40	000 gram/m <sup>2</sup>	Approx. 380	00 gram/m²	Approx. 4700 gram/m <sup>2</sup>	Approx. 4700 gram/m <sup>2</sup>
Approx. 87	70 gram/m²	Approx. 67	0 gram/m²	Approx. 920 gram/m <sup>2</sup>	Approx. 870 gram/m <sup>2</sup>
Appro	x. 7 mm	Approx	. 6 mm	Approx. 7 mm	Approx. 7 mm
0.100 g	ıram/cm³	0.095 gr	am/cm <sup>3</sup>	0.105 gram/cm <sup>3</sup>	0.100 gram/cm <sup>3</sup>
Approx.	61500/m <sup>2</sup>	Approx. 3	32000/m <sup>2</sup>	Approx. 58000/m <sup>2</sup>	Approx. 61500/m <sup>2</sup>
Ŀ	C3	LC	2	LC3	LC3
Il Coral products are	e manufactured using 100	% electricity made by ren	ewable sources.		
0-22	2%**	14	%	20%	0-22%**
Pa	ass	Ра	SS	Pass	Pass
	or 5 years under heavy cor nts currently in force.	ntact conditions provided	l it has been profession	ally fitted by a recognised contractor and regularly	maintained in accordance with
oral sheet product s	should always be fully adh	ered		Monolithic or Tessellated	Monolithic or Tessellated
			requirements of EN	Monolithic or Tessellated 14041 do not apply to loose laid mats and r	

B <sub>n</sub> -s1	B <sub>ri</sub> -s1	
DS	DS	
< 2 kV	< 2 kV	

\*\*\* Coral Classic tiles also available with bitumen backing. Please visit www.forbo-flooring.co.uk/Coral for more details.

20%	0-22%**
Pass	Pass
aised contractor and regularly	maintained in accordance with

olithic or Tessellated	Monolithic or Tessellated	

B<sub>fl</sub>-s1 B<sub>fl</sub>-s1 DS DS < 2 kV < 2 kV











### More Forbo Flooring

Why deal with multiple suppliers when you can deal with one? Forbo Flooring Systems is a global producer of commercial flooring solutions. Our flooring solutions offer includes:

- Environmentally friendly, functional and design-oriented linoleum.
- An extensive range of sheet project vinyl, acoustic vinyl and safety vinyl.
- High performing static control flooring for areas with sensitive electronic equipment.
- High quality European manufactured Luxury Vinyl Tiles.
- · Carpet tiles for both public and commercial environments.
- Flocked sheet and tiles for areas that need the benefits of both textile and resilient floor coverings.
- Cushioned vinyl for the home environment in a wide range of designs.
- Entrance flooring systems that keep interior floors clean, dry and safe.

Please visit our website **www.forbo-flooring.co.uk** to see our extensive range of flooring products.

### WHAT TO DO NEXT



If you would like further information on any of the products shown in this brochure, or would like to discuss an entrance flooring project with our experienced advisers, please call our dedicated entrance flooring team on **01773 740 688**, email **efs.flooring.uk@forbo.com** or visit **www.forbo-flooring.co.uk/efs**  SAMPLE SERVICE Samp 0800 731 2369 or en samples.uk@forbo.com

fession of N put y

Please call us on 01773 740 688 for more information.



Whilst Forbo Flooring UK Limited does its best to ensure that the contents of this brochure are correct and accurate at the time of publication, to the fullest extent permitted by law, Forbo Flooring UK Limited makes no, and expressly disclaims all, guarantees of any kind, express or implied in respect of the information, content, materials or products displayed in this brochure and does not represent that the information is accurate, complete or current and you are advised to visit our website at **www.forbo-flooring.co.uk** for up-to-date details or corrections to such contents.

Please note: Digital representations may vary from the actual product. Please order a sample to see the full effect. Contact 0800 731 2369.



28

London EC1 Showroom: 79 St John Street, Clerkenwell London, EC1M 4NR

Tel: 0207 553 9300 Email: ec1@forbo.com

Opening hours: Mon - Fri 9.00am - 4.00pm

Forbo's EC1 showroom is the ideal place to visit when you're looking for that 'perfect colour' or just want to see a wider range of products.

Our full portfolio of brands on display including Tessera, Marmoleum, project vinyl ranges, entrance flooring systems and designs from our Flotex collection.

Why not pop in and enjoy some hospitality while looking at the products or discussing a project with one of our advisors.

Samples can also be ordered by calling **0800 731 2369** or email samples.uk@forbo.com

If you are at the stage where you would like to discuss your project with an experienced contractor specially trained in every aspect of Nuway specification and installation, we would be delighted to put you in touch with an approved FESSI (Forbo Entrance System Specialist Installer) contractor who will be able to visit your site and provide further advice and a detailed quotation.

All available BIM objects for our Nuway and Coral entrance flooring systems can be downloaded directly from **www.bimstore.co.uk** 





#### UK

Forbo Flooring UK Limited High Holborn Road Ripley Derbyshire DE5 3NT

#### London EC1 showroom

79 St John Street, Clerkenwell London EC1M 4NR Tel: 0207 553 9300

#### For commercial enquiries:

If calling from the North, London & South East Tel: 0800 0282 162 Fax: 01772 646 912 bcs.flooring.uk@forbo.com

If calling from Scotland, Midlands & South West Tel: 0800 0935 258 Fax: 01592 643 999 kcs.flooring.uk@forbo.com

#### Nuway enquiries:

Tel: 01773 740 688 Fax: 01773 740 640 efs.flooring.uk@forbo.com

#### **Residential enquiries:**

Tel: 0800 0935 846 Fax: 01592 643 999 krcs.flooring.uk@forbo.com www.forbo-flooring.co.uk

Sample orders: Tel: 0800 731 2369 Fax: 0843 319 1831 samples.uk@forbo.com

#### Ireland

Forbo Ireland Ltd 2 Deansgrange Business Park Blackrock Co Dublin

Tel: 00353 1 2898 898 Fax: 00353 1 2898 177 info.ireland@forbo.com www.forbo-flooring.ie

#### Find us on



#### **Registered office:**

Forbo Flooring UK Limited High Holborn Road Ripley Derbyshire DE5 3NT Registered in England 9200318









