

sas7.com.au





Table of Contents

About SAS7 03

HVAC Mounting Systems 04

Acoustic Screening 05

Architectural Screening 06

Roof Access 07





About SAS7

Safety Access Solutions provide innovative cost- effective solutions to your projects and have been in the industry for over 30 years.

From basic walkway installations to fully engineered customised access systems and mechanical plant platforms!

When it's about safety it's about lives. We are passionate about doing the right thing!






HVAC Mounting Systems







EasyMechMR

(purlin mounted)



Live load rated to 2.5 kPa (up to 5 kPa available)

Super lightweight 14 kg / m2

Penetration free available in modular 600mm increment sizes

Compliant with Australian Standards

EasyMech**CR**

(for concrete roofs)



Live load rated to 2.5 kPa (up to 5 kPa available)

Super lightweight 20 kg / m2

Vibration isolator feet are engineer certified & can take 1000kg (per foot)

Compliant with Australian Standds

Span+

(rafter mounted)



85% lighter than steel

5 x faster install

10.5m span between rafters (can be increased)

Compliant with Australian Standards







Acoustic Screening







Acoustic+



Ultra noise reduction by absorption & reflection.

Most effective system at reducing sound energy

Weighted Sound Reduction Index (Rw) of 28 and a Noise Reduction Coefficient (NRC) of 1.

SoundShield



Noise reduction by reflection.

Weighted Sound Reduction Index (Rw) of 28.

Structural components provide highly durable, long-term stability and performance.

PeaceMaker



Noise reduction by absorption.

Noise Reduction Coefficient (NRC) of 1.

Fit for all weather conditions. Absorptive barrier is moisture resistant, UV resistant and fire retardant.

Ask our team about our Acoustic Flooring Solutions **TESTED BY THE CSIRO**

We use the highest standard of testing that the Commonwealth Scientific and Industrial Research Organisation (CSIRO) has to offer.







Architectural Screening







ClassicScreen

LouvreWall airflow

Screen**to**Roof



Conceal unsightly machinery with the clean lines of our ClassicScreen Wall.

Powder-coated to match any colour scheme.

Lightweight at 7kg/m2.



100% visual barrier, 55% airflow (can be increased).

Increase airflow to improve machinery performance.

Powder-coated to match any colour scheme.




Can be retrofitted to any surface.

Flexible system allows all screen profiles including louvre and acoustic screen profiles.

Sized to suit any plant equipment.















Roof Access







StandardWalkway







Guardrail



Con-form Group Roof Access Solutions are:

- Built from ultra-strong structural grade aluminium with superior live load ratings of 3Kpa.
- Built to withstand volatile and extreme weather conditions.
- Ideal for pitches of 1° to 20 up roof.
- Lightweight, strong & modular.
- Agile and safe systems.
- Cost-effective.

Guardrails are also available on levelled walkways.



