



Concentric Eccentric Reducers

Schedule-STD Size 3/4" x 1/2" - 4" x 1 1/2"



Pipe Size	LARGE DIAMETER			SMALL DIAMETER			Length L	Pipe Schedule Number	Approx. Weight in Pounds
	Outside Diameter	Inside Diameter	Wall Thickness	Outside Diameter	Inside Diameter	Wall Thickness			
	O.D.	I.D.	T	O.D.	I.D.	T			
3/4 x 1/2	1.05	0.824	0.113	0.84	0.622	0.109	1.50	40	0.21
1 x 3/4	1.32	1.054	0.133	1.05	0.824	0.113	2.00	40	0.36
1 x 1/2	1.32	1.054	0.133	0.84	0.622	0.109	2.00	40	0.36
1 1/4 x 1	1.66	1.380	0.140	1.32	1.054	0.133	2.00	40	0.48
1 1/4 x 3/4	1.66	1.380	0.140	1.05	0.824	0.113	2.00	40	0.42
1 1/4 x 1/2	1.66	1.380	0.140	0.84	0.622	0.109	2.00	40	0.42
1 1/2 x 1 1/4	1.90	1.610	0.145	1.66	1.380	0.140	2.50	40	0.65
1 1/2 x 1	1.90	1.610	0.145	1.32	1.054	0.133	2.50	40	0.57
1 1/2 x 3/4	1.90	1.610	0.145	1.05	0.824	0.113	2.50	40	0.56
1 1/2 x 1/2	1.90	1.610	0.145	0.84	0.622	0.109	2.50	40	0.56
2 x 1 1/2	2.38	2.072	0.154	1.90	1.610	0.145	3.00	40	0.94
2 x 1 1/4	2.38	2.072	0.154	1.66	1.380	0.140	3.00	40	0.88
2 x 1	2.38	2.072	0.154	1.32	1.054	0.133	3.00	40	0.81
2 x 3/4	2.38	2.072	0.154	1.05	0.824	0.113	3.00	40	0.74
2 1/2 x 2	2.88	2.474	0.203	2.38	2.072	0.154	3.50	40	1.60
2 1/2 x 1 1/2	2.88	2.474	0.203	1.90	1.610	0.145	3.50	40	1.50
2 1/2 x 1 1/4	2.88	2.474	0.203	1.66	1.380	0.140	3.50	40	1.40
2 1/2 x 1	2.88	2.474	0.203	1.32	1.054	0.133	3.50	40	1.30
3 x 2 1/2	3.50	3.068	0.216	2.88	2.474	0.203	3.50	40	2.20
3 x 2	3.50	3.068	0.216	2.38	2.072	0.154	3.50	40	2.00
3 x 1 1/2	3.50	3.068	0.216	1.90	1.610	0.145	3.50	40	1.90
3 x 1 1/4	3.50	3.068	0.216	1.66	1.380	0.140	3.50	40	1.80
❖ 3 x 1	3.50	3.068	0.216	1.32	1.054	0.133	3.50	40	1.70
3 1/2 x 3	4.00	3.548	0.226	3.50	3.068	0.216	4.00	40	2.80
3 1/2 x 2 1/2	4.00	3.548	0.226	2.88	2.474	0.203	4.00	40	2.70
3 1/2 x 2	4.00	3.548	0.226	2.38	2.072	0.154	4.00	40	2.60
3 1/2 x 1 1/2	4.00	3.548	0.226	1.90	1.610	0.145	4.00	40	2.60
3 1/2 x 1 1/4	4.00	3.548	0.226	1.66	1.380	0.140	4.00	40	2.50
4 x 3 1/2	4.50	4.026	0.237	4.00	3.548	0.226	4.00	40	3.50
4 x 3	4.50	4.026	0.237	3.50	3.068	0.216	4.00	40	3.30
4 x 2 1/2	4.50	4.026	0.237	2.88	2.474	0.203	4.00	40	3.20
4 x 2	4.50	4.026	0.237	2.38	2.072	0.154	4.00	40	3.10
4 x 1 1/2	4.50	4.026	0.237	1.90	1.610	0.145	4.00	40	3.00