TERRAPOR O JUNE 14-18-18

VILLAGE OF SUN RIVER TERRACE BUILDING & ZONING

POOL PERMIT APPLICATION

INSTRUCTIONS

<u>Section 1 and Section 6</u> to be completed by Owner or Authorized Agent. Please note that if your property is in a subdivision, the covenants and restrictions of that subdivision should be consulted to ensure your project is in compliance. Covenants and restrictions for subdivisions can be obtained from the Kankakee County Recorder of Deeds Office. The Building & Zoning Department does not enforce subdivision covenants and restrictions.

Section 4: The application must be sign by the owner or authorized agent.


SWIMMING POOL REGULATIONS

- 1. A site plan drawn close to scale, showing the actual shape and dimensions of the lot to be built on, the size and dimensions on the lot of buildings and structures already existing and the size and location of the swimming pool to be constructed. County 5-13
- 2. Site plan must also include location of overhead or underground utilities. County 5-13
- 3. Building permit is required before construction begins. County 5-13
- 4. Contractor must be registered with County of Kankakee. County 5-86
- 5. Pool or any part of the pool cannot be located any closer than 5 ft. (60 inches) from any side or rear property line. County 4.04-B-2
- 6. Under no circumstances can a pool be located in any front yard. A corner lot shall always be considered as having 2 (two) front yards. County 4.04-C table
- 7. Any structure intended for swimming, recreational bathing or wading that contains water over 24 inches deep shall be required to conform to these requirements. ICC 3901.2
- 8. A 48" barrier must protect the pool on all sides. See attached approved barrier types. ICC 3109.4.1 (see drawing B)
- 9. If a deck is used, the 48" barrier requirement is still in place. ICC 3109.4.1
- 10. Any gate in the barrier must open outwards with a self-closing and self-latching device. ICC 3109.4.1.7 (see drawing A)



11. When the release mechanism of the self-latching device is located less than 54" from the bottom of the gate, the release mechanism shall be located on the pool side of the gate at least 3 inches below the top of the gate. ICC 3109.4.1.7

- 12. When a house wall is used as part of the barrier requirements, the following requirements must be in place.
 - 1. A door in the required barrier with direct access to the pool shall have an audible alarm on the door or a power safety cover. Either must meet all requirements of ICC 3109.4.1.8
 - 2. A door in the required barrier may be allowed to have a self-closing and latching device if approved by the administrative authority and device shows that safety will not be compromised. ICC 3109.4.1.8.3



Drawing B

- 13. All electric circuits to pool must be of ground fault interruption type. NEC
- 14. Drop cords are not allowed to be used on pools for any reason. NEC
- 15. All requirements of ComEd (enclosed) must be followed.

Minimum Clearances for Overhead Service Cable (120, 120/208 or 120/240 Volts)

Location	Minimum Clearances
Over streets, alleys, parking lots, public	
driveways, or over commercial, industrial,	
and farm private property driveways	18 ft.
Over residential private property driveways	12 ft. 6 in.
Spaces accessible to pedestrians only	10 ft. 6 in.
Above or below balconies and roofs*	
accessible to pedestrians	Hft.
Above or below roofs* not accessible	
to pedestrians	3 ft. 6 in.
Horizontal clearance from windows,	
porches, balconies, fire escapes, signs	
or any part of a building normally	
accessible to individuals	
(including access for maintenance)	5 ft.
Horizontal clearance from communication	
or signal wires at the building	I ft.

Conductors are not permitted to pass over any swimming pool or tanks containing flammable materials.

Attachments cannot be made on chimneys.


Service wire attachment shall not exceed 25 ft. above the ground at final grade.

Note:

*A roof, balcony or area is considered accessible to pedestrians if the means of access is through a doorway, ramp, stairway or permanently-mounted ladder. For higher voltages or variance from these clearances, contact your local ComEd representative.

Minimum Clearances Near Swimming Pools

- Horizontal limit of aerial clearance will not measure less than 10 ft. from the inside wall of the pool.
- Underground service cable shall not be permitted under the pool or within 5ft. of the inside wall of the pool. When space limitations prevent service cables from being routed 5ft. or more from the pool, such cables must be installed 24 in. deep in 4 in. conduit at customer's expense.



Swimming Pool Clearances	0-750 V	750-15,000 V
Clearance in any direction	22' 6"	25'
from the edge of the pool	(without violating rule 1)	
Clearanceinanydirection	14' 6"	17'
o a platform (without violating ru		olating rule 1)

Exercise extreme caution near live wires. Do not attempt to measure exact distances to live wires due to danger of electrocution.

- 16. All metallic components including conductive pool shells, perimeter surfaces within 3 feet of pool, underwater lighting, metal fittings such as ladder, slide & diving board anchors, electrical equipment, fixed metal parts and concrete reinforcement such as rebar and WWM must be bonded together with minimum of 8 AWG copper wire. NEC 680.26
- 17. Covers used as safety barriers must be ASTM-F1346-91 approved

FENCE REGULATIONS

- 1. Maximum height is 6 feet in rear and side yards
- 2. Posts must be a minimum 42 inches deep
- 3. Finished side must be out

DECK REGULATIONS

- 1. Stair riser max is 7 ¾", tread max is 10", must have grippable handrail between 1 ¼"-2"
- 2. Post shall be imbedded in concrete a minimum of 12" or use manufactured connectors to prevent lateral displacement.
- 3. Beams shall bear on posts
 - a. Min. 4x4 if setting on top, using connectors to resist uplift
 - b. Minimum 6x6 if notching in w/min. (2) ½" through bolts w/washer
- 4. Ledger boards shall be fastened with ½" x 3" lag screws w/washers staggered 2" from top and bottom 16" o.c.
- 5. Joists shall bear on 1 ½" wood or steel (joist hangers) minimum
- 6. Maximum joist spans:

size	12"o/c	16"o/c	24"o/c
2x6	8'-10"	8'-0"	7'-0"
2x8	11'-8"	10'-7"	8'-8"
2x10	14'-11"	13'-0"	10′7″
2x12	17'-5"	15'-1"	12'-4"

- 7. Stairways shall not be less than 36" in clear width above the permitted handrail height. Maximum riser height is 7 ¾" and minimum tread depth is 10"
- 8. Railings or guardrails are required if deck is 30" or more above finished grade. Guardrails must be a minimum of 36" in height. Posts or spindles shall not allow a 4" sphere to pass through, or be installed in a horizontal manner that results in a ladder effect.
- 9. Railings along stairways are to be 34"-38" in height, measured from the nose of the treads and not allow a 4 3/8" sphere to pass between them. There must be a greppable handrail on at least one side with a cross section of 1 ¼"- 2" which must terminate at a newel or wall. Bottom rails shall be installed to prevent 6" sphere from passing through the stair tread and rail.

Pool Permit Worksheet

NAME		_ ADDRESS			
Size of pool?					
Is there a heater?					_
Distance from back of house?					_
Distance from side yard lot line?					_
Distance from rear yard lot line?					
Is the pool in ground or above ground	?				_
IF THE POOL IS ABOVE GROUND					
Height of pool above grade?					_
If less than 48" it must have a barrier	Fence	(see fence below)	Deck	(see deck below	·)
IF THE POOL IS IN GROUND					
Is there an apron?S	size?	Concrete?		Pavers?	_
What type of barrier ?					
ASTM Safety Cover	Fence	_ (see fence below)	Deck	(see deck below))
<u>Fence</u>					
Type of fence? Privacy					
Height of fence?					_
<u>Deck</u>					
Size of deck?					_
Depth of piers?					_
Spacing of piers?					_
Size of posts?					_
Size of beams?					
Size of floor joists?					_
Spacing of floor joists?					_
Size of decking?					
How high is the deck above grade?	if mor	e than 7 ¾" it needs s	stairs (see	e stairs)	
<u>Stairs</u>					
Width?	Riser?	(max 7 ¾")		Tread?(min	n. 10′
Handrails? (if more	e than 3 risers	(ax , /4 ,			±0
(11 11101)	c dian 5 nsers	, you need these;			
Guardrails					
Height of rail off grade?					
Height of rail off deck?					
Spacing between spindles, posts or off	 f deck?				

SUBMITTAL REQUIREMENTS

- 1. Plot plan showing all existing structures, location of proposed pool, utility services, septic tank & field if applicable.

 a. If fence or deck is included, please include these also.
- 2. Pool permit application.
- 3. Pool permit worksheet.
- 4. Contractor List.
- 5. Manufacturers brochures for pool pump, heater, filter and ASTM cover (if applicable).
- 6. Signed contract or material estimate sheet from a distributor (if doing the work yourself).



VILLAGE OF SUN RIVER TERRACE BUILDING & ZONING POOL PERMIT APPLICATION

Date Received:	Add-On:	Date of Add-On:
Building Permit Fee:		Total Fee:
Date Issued:	Paid:	Permit No.:
Applicant to complete this section:	SECTION 1: OWNER I	NFORMATION
Name:		
		Email:
Mailing Address:		
Contact Person:		Telephone Number:
Email:		
Will the homeowner be perfor	rming the work themselves?	Yes No
	SECTION 2: PROPERTY	INFORMATION
PI No:	Towns	ship:
		<u>-</u>
Subdivision:		Block No.: Lot No:
Zoning District:	Check PI File: Date:	Block No.: Lot No:
	SECTION 3: PROJECT	INFORMATION
Project Description:		
Signed Contract (Attach):		Total Value:
Material:	Labor:	Other:
	SECTION 4: AUTH	ORIZATION
_	ork that will be performed by t	erty, I hereby authorize the addition of the above the contractors listed or by myself. The information
	——————————————————————————————————————	e of Owner or Authorized Agent)
Application Taken By:	SECTION 5: PLAN/ APPL	ICATION REVIEW
Application Reviewed By:		Approved: Denied:
		rippiored.
If denied, state reason why:		

SECTION 6: CONTRACTOR INFORMATION

	Permit #			
Owners Name:	Type of Construction:			
Owners Name: Type of Construction: If the contractor's list should change at any time during the project, a revised list shall be submitted to the Building & Zoning Department of the Construction: Type of Construction: If the contractor's list should change at any time during the project, a revised list shall be submitted to the Building & Zoning Department of the Construction:				
Trade:	License #			
	Signed Aff. Yes No			
Contractor:	Gen. Lib Yes No			
	Work Comp Yes No			
Phone #:	Bond Yes No			
Trade:	License #			
_	Signed Aff Yes No			
Contractor:	Gen. Lib. Yes No			
	Work Comp Yes No			
Phone #:	Bond Yes No			
Trade:	License #			
	Signed Aff. Yes No			
Contractor:	Gen. Lib Yes No			
71	Work Comp Yes No			
Phone #:	Bond Yes No			
m 1				
Trade:	License #			
	Signed Aff. Yes No			
Contractor:				
DI //	Work Comp Yes No			
Phone #:	Bond Yes No			
Trade:	License #			
rade:	Signed Aff. Yes No			
Contractor:	Gen. Lib. Yes No			
Contractor.	Work Comp Yes No			
Phone #:	Bond Yes No			
Plumbing:	License #			
	Signed Aff. Yes No			
	Gen. Lib. Yes No			
	Work Comp Yes No			
Phone #:	Bond Yes No			
State License #: 058 -	Expiration:			
State Registration #: 055-	Expiration:			
Date Received:	Date Approved: Approved By:			