RV SETUP CHECKLIST

Visit the Camping World blog to view the full detailed checklist.

This checklist begins once you've checked into your campground and located your site. Here's everything you need to think about to get your RV ready for daily living: Scout your site. Disconnect your toad or dinghy (Only for motorhomes towing a second vehicle). Use a spotter to pull in. Position your RV within reach of hookups. Install leveling blocks as needed. Chock the wheels. Disconnect your tow vehicle (Towable RVs only). Pull your tow vehicle away (Towable RVs only). Raise or lower the tongue jack or landing legs to level the unit (Towable RVs only). Extend stabilizing jacks. Connect a surge protector and your electrical cord to shore power. Attach a potable drinking water hose, water pressure regulator, and water filter. Connect the sewer hose to the sewer drain outlet. Lower your entry steps. Adjust if applicable. Turn on your refrigerator and switch it to AC power. Turn on your propane supply. Unlock and extend slide-outs. Turn on your water heater to fill the tank. Return all stowed items to their proper positions. Set up kitchen and interior.

Pro Tip: Divide these tasks between you and your travel partner. But then go back and double-check each other's work. There's much to remember when setting up and tearing down a campsite. Using a checklist and double-checking each other's work is the best way to minimize the chances of forgetting something that damages your RV, tow vehicle, or toad/dinghy.

Set up the exterior.

RV TEARDOWN CHECKLIST

Use this checklist to ensure you're ready to head home or explore your next destination:	
	Stow items in your outdoor kitchen.
	Stow all outdoor camp gear (chairs, patio mats, griddles, outdoor games, patio lights, etc.).
	Retract RV awnings.
	Lower TV antenna (if applicable).
	Stow all interior appliances that can shift during travel.
	Turn off all interior and exterior electronics and lights.
	Close the blinds/curtains.
	Turn off your water heater.
	Retract and secure slide-outs.
	Drain holding tanks and stow sewer hose and hose support.
	Turn off the propane supply.
	Turn off the refrigerator.
	Turn off city water and store the water hose, regulator, and filter. Take the time to blow any remaining water out of the hose and filter before stowing.
	Disconnect the surge protector, electrical cord, and any electrical adapters and stow away.
	Check to ensure all rooftop accessories are in the stowed position.
	Retract stabilizing jacks and entry step(s).
	Raise the tongue jack to prep for connecting your tow vehicle (Towable RVs only).
	Connect tow vehicle and weight distribution hitch (Towable RVs only).
	Remove wheel chocks and stow.
	Check tire pressures and condition.
	Pull forward off leveling blocks.
	Collect and store leveling blocks.
	Lock all compartment doors.
	Use a spotter to guide you out of your campsite.
	Connect your toad or dinghy (Motorhomes only).
	Conduct a final walkaround.
	Verify you have all camping partners. Don't leave your furry companions either!
	Stop and re-check all hitch connections after moving a short distance.