

FIRE ARMOR USA

Enforcer XP



KEVLAR® XP™ IS A NEW WOVEN FABRIC FROM DUPONT'S FAMILY OF PERFORMANCE ARAMIDS. KEVLAR® XP™ HAS BEEN COMPLETELY REDESIGNED FOR TODAY'S MODERN THREATS. ONE OF THE KEY IMPROVEMENTS TO THIS FABRIC IS ITS ABILITY TO REDUCE THE BACK FACE DEFORMATION BY 15% OR MORE

MALE MODEL 1216

BALLISTIC THREAT LEVEL II

PERFORMANCE DATA

**NEW 9MM V50 @ 1604 FPS
NEW 357 MAG V50 @ 1630 FPS**

**AVERAGE BFS 9MM - 30.7MM
AVERAGE BFS 357 MAG - 31.5MM**

**WT. PER SQ. FT. - 13.6 OZ. - .85 LBS
THINNESS .22 INCHES**

WOVEN KEVLAR XP ARAMID

BROOKWOOD FIREBALL COVER

DuPont™
KEVLAR®



NIJ 0101.06 CERTIFIED

SPECIAL THREAT TESTED

**WINCHESTER 9MM 127GR RANGER SXT +P+
FIOCCHI 9MM LUGER 115FR FMJ
REMINGTON GOLDEN SABER .40 S&W 165GR BJHP
MAG TECH .357 MAG. 158GR JSP
SPEER .357 SIG 125GR GDHP**

**WINCHESTER .40 S&W 165GR SXT
FHN 5.7X28 SS198 40RG HP
SPEER .45 ACP 230GR GDHP
17GR FSP FRAG - V-50 @ 1738 FPS**



**WWW.FIREARMORUSA.COM
(562) 207-4240**



FIRE ARMOR USA

Enforcer XP



KEVLAR® XP™ IS A NEW WOVEN FABRIC FROM DUPONT'S FAMILY OF PERFORMANCE ARAMIDS. KEVLAR® XP™ HAS BEEN COMPLETELY REDESIGNED FOR TODAY'S MODERN THREATS. ONE OF THE KEY IMPROVEMENTS TO THIS FABRIC IS ITS ABILITY TO REDUCE THE BACK FACE DEFORMATION BY 15% OR MORE

MALE MODEL 1316

BALLISTIC THREAT LEVEL IIIA

PERFORMANCE DATA

NEW 357 SIG V50 @ 1768 FPS

NEW 44 MAG V50 @ 1646 FPS

AVERAGE BFS 357 SIG - 29.4MM

AVERAGE BFS 44 MAG - 37.5MM

WT. PER SQ. FT. - 18.4 OZ. - 1.15 LBS

THINNESS .27 INCHES

WOVEN KEVLAR XP ARAMID

BROOKWOOD FIREBALL COVER

DuPont™
KEVLAR



NIJ 0101.06 CERTIFIED

SPECIAL THREAT TESTED

WINCHESTER 9MM 127GR RANGER SXT +P+

FIOCCHI 9MM LUGER 115FR FMJ

AGUILA 9MM LUGER IQ 65GR HP

WINCHESTER .40 S&W 165GR SXT

17GR FSP FRAG - V-50 @ 1989 FPS

NORINCO 7.62X25 TOKAREV 85GR FMJ



WWW.FIREARMORUSA.COM
(562) 207-4240



FIRE ARMOR USA

Enforcer 3000



THE ENFORCER 3000 IS A BUDGET FRIENDLY DESIGN COMBINING HONEYWELL'S PROVEN GOLD SHIELD®, HONEYWELL'S SPECTRA SHIELD, AND WOVEN TWARON FIBER BY SAATI. THE END RESULT IS A LIGHTER, MORE FLEXIBLE VEST AT A BUDGET FRIENDLY PRICE



NIJ 0101.06 CERTIFIED

MALE MODEL 3316 **BALLISTIC THREAT LEVEL IIIA**

PERFORMANCE DATA

NEW 357 SIG V50 @ 1818 FPS

NEW 44 MAG V50 @ 1578 FPS

AVERAGE BFS 44 MAG - 38MM

AVERAGE BFS 357 SIG - 29.5MM

WT. PER SQ. FT. - 20.9 OZ. - 1.32 LBS

THINNESS .32 INCHES

**WOVEN KEVLAR ARAMID - SAATI, HONEYWELL
SPECTRA SHIELD & HONEYWELL GOLD SHIELD**

DuPont™
KEVLAR®

—**SAATI**

Honeywell

SPECIAL THREAT TESTED

2GR RCC FRAG V-50 @ 3098 FPS

4GR RCC FRAG V-50 @ 2500 FPS

16GR RCC FRAG V-50 @ 2307 FPS

FN SS195LF @ 2137 FPS

9MM CORBON +P 115GR. JHP @ 1401 FPS

9MM WINCHESTER SXT +P+ @ 1289 FPS

9MM FIOCCHI 115GR. FMJ @ 1169 FPS

.40 S&W FEDERAL 165GR. HYDRA-SHOK HP @ 1112 FPS

9MM CIVIL DEFENSE (LIBERTY) 50GR. HP @ 2043 FPS

.40 S&W WINCHESTER 165GR. BONDED JHP @ 1283 FPS

.45 ACP 230GR. SPEER GDHP @ 944 FPS

.40 S&W SPEER 165GR. GDHP @ 1232 FPS

.357 SIG SPEER GDHP @ 1356 FPS



WWW.FIREARMORUSA.COM
(562) 207-4240



FIRE ARMOR USA

Enforcer 3000



THE ENFORCER 3000 IS A BUDGET FRIENDLY DESIGN COMBINING HONEYWELL'S PROVEN GOLD SHIELD®, HONEYWELL'S SPECTRA SHIELD, AND WOVEN TWARON FIBER BY SAATI. THE END RESULT IS A LIGHTER, MORE FLEXIBLE VEST AT A BUDGET FRIENDLY PRICE

FEMALE MODEL 3326

BALLISTIC THREAT LEVEL IIIA

PERFORMANCE DATA

NEW 357 SIG V50 @ 1745 FPS

NEW 44 MAG V50 @ 1619 FPS

AVERAGE BFS 357 SIG - 26.03 MM

AVERAGE BFS 44 MAG - 36.87 MM

WT. PER SQ. FT. - 21 OZ. - 1.32 LBS

THINNESS .32 INCHES

**WOVEN KEVLAR ARAMID - SAATI, HONEYWELL
SPECTRA SHIELD & HONEYWELL GOLD SHIELD**

BROOKWOOD ARCHERLITE COVERING

SPECIAL THREAT TESTED

2GR RCC FRAG V-50 @ 3098 FPS

4GR RCC FRAG V-50 @ 2500 FPS

16GR RCC FRAG V-50 @ 2307 FPS

FN SS195LF @ 2137 FPS

9MM CORBON +P 115GR. JHP @ 1401 FPS

9MM WINCHESTER SXT +P+ @ 1289 FPS

9MM FIOCCHI 115GR. FMJ @ 1169 FPS

.40 S&W FEDERAL 165GR. HYDRA-SHOK HP @ 1112 FPS

9MM CIVIL DEFENSE (LIBERTY) 50GR. HP @ 2043 FPS

.40 S&W WINCHESTER 165GR. BONDED JHP @ 1283 FPS

.45 ACP 230GR. SPEER GDHP @ 944 FPS

.40 S&W SPEER 165GR. GDHP @ 1232 FPS

.357 SIG SPEER GDHP @ 1356 FPS



NIJ 0101.06 CERTIFIED



**WWW.FIREARMORUSA.COM
(562) 207-4240**



FIRE ARMOR USA

Enforcer 5000



THE ENFORCER 5000 IS AN ADVANCED TECHNOLOGICAL DESIGN COMBINING HONEYWELL'S PROVEN GOLD FLEX®, NEW SPECTRA SHIELD® II BALLISTIC MATERIAL AND DUPONT'S KEVLAR® XP™. THE END RESULT IS A LIGHTER, MORE FLEXIBLE VEST THAT STILL SATISFIES THE STRICT PERFORMANCE REQUIREMENTS OF THE NIJ 0101.06 STANDARD.

MALE MODEL 5216M

BALLISTIC THREAT LEVEL II

PERFORMANCE DATA

NEW 9MM V50 @ 1743 FPS

NEW 357 MAG V50 @ 1668 FPS

AVERAGE BFS 9MM - 27.4MM

AVERAGE BFS 357 MAG - 31.39MM

WT. PER SQ. FT. - 13.6 OZ. - .85 LBS

THINNESS .162 INCHES

**WOVEN DUPONT KEVLAR & XP, HONEYWELL
SPECTRA SHIELD & HONEYWELL GOLD SHIELD**

BROOKWOOD ARCHERLITE COVERING

DuPont™
KEVLAR

Honeywell



NIJ 0101.06 CERTIFIED

SPECIAL THREAT TESTED

WINCHESTER 9MM LUGER SXT +P+ @ 1308 FPS

FIOCCHI 9MM LUGER FMJ @ 1119 FPS

WINCHESTER .40 S&W SXT @ 1165 FPS

REM GOLDEN SABER .40 S&W BJHP @ 1120 FPS

FEDERAL .40 S&W HST @ 1008 FPS

SPEER .357 SIG GDHP @ 1413 FPS

SPEER .45 ACP GDHP @ 1141 FPS

FN 5.7 X 28 MM SS197 @ 1644 FPS

2 GR. RCC PROJECTILE @ 2680 FPS

4 GR. RCC PROJECTILE @ 2241 FPS

17 GR. FSP PROJECTILE @ 1871 FPS

9MM NORMA 116 GR. FMJ @ 1260 FPS

FN 5.7X28MM SS 195 HP @ 2041 FPS



WWW.FIREARMORUSA.COM
(562) 207-4240



FIRE ARMOR USA

Enforcer 5000



THE ENFORCER 5000 IS AN ADVANCED TECHNOLOGICAL DESIGN COMBINING HONEYWELL'S PROVEN GOLD FLEX®, NEW SPECTRA SHIELD® II BALLISTIC MATERIAL AND DUPONT'S KEVLAR® XP™. THE END RESULT IS A LIGHTER, MORE FLEXIBLE VEST THAT STILL SATISFIES THE STRICT PERFORMANCE REQUIREMENTS OF THE NIJ 0101.06 STANDARD.

FEMALE MODEL 5226F

BALLISTIC THREAT LEVEL II

PERFORMANCE DATA

NEW 9MM V50 @ 1850 FPS

NEW 357 MAG V50 @ 1733 FPS

AVERAGE BFS 9MM - 27.22MM

AVERAGE BFS 357 MAG - 30.6MM

WT. PER SQ. FT. - 13.7 OZ. - .86 LBS

THINNESS .179 INCHES

**WOVEN DUPONT KEVLAR & XP, HONEYWELL
SPECTRA SHIELD & HONEYWELL GOLD SHIELD**

BROOKWOOD ARCHERLITE COVERING

DuPont™
KEVLAR®

Honeywell



NIJ 0101.06 CERTIFIED

SPECIAL THREAT TESTED

WINCHESTER 9MM LUGER SXT +P+ @ 1308 FPS

FIOCCHI 9MM LUGER FMJ @ 1119 FPS

WINCHESTER .40 S&W SXT @ 1165 FPS

REM GOLDEN SABER .40 S&W BJHP @ 1120 FPS

FEDERAL .40 S&W HST @ 1008 FPS

SPEER .357 SIG GDHP @ 1413 FPS

SPEER .45 ACP GDHP @ 1141 FPS

FN 5.7 X 28 MM SS197 @ 1644 FPS

2 GR. RCC PROJECTILE @ 2680 FPS

4 GR. RCC PROJECTILE @ 2241 FPS

17 GR. FSP PROJECTILE @ 1871 FPS

9MM NORMA 116 GR. FMJ @ 1260 FPS

FN 5.7X28MM SS 195 HP @ 2041 FPS



WWW.FIREARMORUSA.COM
(562) 207-4240



FIRE ARMOR USA

Enforcer 5000



THE ENFORCER 5000 IS AN ADVANCED TECHNOLOGICAL DESIGN COMBINING HONEYWELL'S PROVEN GOLD FLEX®, NEW SPECTRA SHIELD® II BALLISTIC MATERIAL AND DUPONT'S KEVLAR® XP™. THE END RESULT IS A LIGHTER, MORE FLEXIBLE VEST THAT STILL SATISFIES THE STRICT PERFORMANCE REQUIREMENTS OF THE NIJ 0101.06 STANDARD.

MALE MODEL 5316A

BALLISTIC THREAT LEVEL IIIA

PERFORMANCE DATA

NEW 357 SIG V50 @ 1809 FPS

NEW 44 MAG V50 @ 1688 FPS

AVERAGE BFS 357 SIG - 31.3MM

AVERAGE BFS 44 MAG - 38.4MM

WT. PER SQ. FT. - 17.9 OZ. - 1.11 LBS

THINNESS .24 INCHES

**WOVEN DUPONT KEVLAR & XP, HONEYWELL
SPECTRA SHIELD & HONEYWELL GOLD SHIELD**

BROOKWOOD ARCHERLITE COVERING

DuPont™
KEVLAR®

Honeywell



NIJ 0101.06 CERTIFIED

SPECIAL THREAT TESTED

WINCHESTER .40 S&W SXT @ 1101 FPS

WINCHESTER 9MM LUGER SXT +P+ @ 1292 FPS

NORINCO 7.62 X 25MM TOKAREV FMJ @ 1693 FPS

FIOCCHI 9MM LUGER FMJ @ 1161 FPS

AQUILA 9MM LUGAR IQ HP @ 1685 FPS



WWW.FIREARMORUSA.COM
(562) 207-4240



FIRE ARMOR USA

Enforcer 6000



THE ENFORCER 6000 IS AN ADVANCED TECHNOLOGICAL DESIGN COMBINING HONEYWELL'S PROVEN ADVANCED SPECTRA SHIELD® II, AND DUPONT KEVLAR WOVEN BY SAATI. THE END RESULT IS A LIGHTER, MORE FLEXIBLE VEST THAT EXCEEDS THE STRICT PERFORMANCE REQUIREMENTS OF THE NIJ 0101.06 STANDARD.



NIJ 0101.06 CERTIFIED

MALE MODEL 6216M

BALLISTIC THREAT LEVEL II

PERFORMANCE DATA

NEW 9MM V50 @ 1932 FPS
NEW 357 MAG V50 @ 1807 FPS

AVERAGE BFS 9MM - 32.89MM
AVERAGE BFS 357 MAG - 37.02MM

WT. PER SQ. FT. - 11.52 OZ. - .72 LBS
THINNESS .17 INCHES

WOVEN KEVLAR ARAMID BY SAATI,
HONEYWELL ADVANCED SPECTRA II

BROOKWOOD ARCHERLITE COVERING

—SAATI Honeywell DuPont™ KEVLAR

SPECIAL THREAT TESTED

9MM CIVIL DEFENSE (LIBERTY) 50GR. HP @ 1999 FPS
9MM CORBON +P 115GR. JHP @ 1408 FPS
9MM WINCHESTER SXT +P+ @ 1277 FPS
.40 S&W WINCHESTER 165GR. BONDED JHP @ 1247 FPS
.40 S&W FEDERAL 165GR. HYDRA-SHOK HP @ 1099 FPS

.40 S&W SPEER 165GR. GDHP @ 1203 FPS
5.7 X 28 F/N SS195LF @ 2040 FPS
.357 SIG SPEER GDHP @ 1309 FPS
9MM FIOCCHI 115GR. FMJ @ 1159 FPS
.45 ACP 230GR. SPEER GDHP @ 926 FPS



WWW.FIREARMORUSA.COM
(562) 207-4240



FIRE ARMOR USA

Enforcer 6000



THE ENFORCER 6000 IS AN ADVANCED TECHNOLOGICAL DESIGN COMBINING HONEYWELL'S PROVEN GOLD SHIELD®, ADVANCED SPECTRA SHIELD® II, DSM BALLISTIC MATERIAL AND CORE TECHNOLOGY MATERIAL FROM TEXTECH. THE END RESULT IS A LIGHTER, MORE FLEXIBLE VEST THAT STILL SATISFIES THE STRICT PERFORMANCE REQUIREMENTS OF THE NIJ 0101.06 STANDARD.



MALE MODEL 6316M

BALLISTIC THREAT LEVEL IIIA

PERFORMANCE DATA

NEW 357 SIG V50 @ 1781 FPS

NEW 44 MAG V50 @ 1658 FPS

AVERAGE BFS 357 SIG - 27.5MM

AVERAGE BFS 44 MAG - 36.8MM

WT. PER SQ. FT. - 15.84 OZ. - .99 LBS

THINNESS .26 INCHES

TEXTECH ADVANCED CORE, WOVEN KEVLAR ARAMID , HONEYWELL GOLD SHIELD, DYNEEMA

BROOKWOOD ARCHERLITE COVERING



SPECIAL THREAT TESTED

NORINCO 7.62X25MM TOKARAV FMJ @ 1666 FPS

FN 5.7X28MM SS195LF @ 2075 FPS

AGUILA IQ 9MM 65GR HP @ 1664 FPS

.45 ACP 230GR. GDHP @ 875 FPS

GOLD DOT .357 SIG GDHP @ 1375 FPS

9MM CIVIL DEFENSE (LIBERTY) 50GR. HP @ 1991 FPS

9MM CORBON +P 115GR. JHP @ 1428 FPS

9MM WINCHESTER 127GR SXT +P+ @ 1319 FPS

9MM NORMA 116GR FMJ @ 1239 FPS

9MM FIOCCHI 115GR. FMJ @ 1182 FPS

.40 S&W FEDERAL 165GR. HYDRA-SHOK HP @ 975 FPS

.40 S&W REM. GOLDEN SABER 165GR. JHP @ 1156 FPS

.40 S&W WINCHESTER 165GR. BONDED JHP @ 1068 FPS

.40 S&W SPEER 165GR. GDHP @ 1171 FPS

.357 MAG 158GR. MAGTECH JSP @ 1426 FPS

.40 S&W CIVIL DEFENSE (LIBERTY) 60GR. HP @ 1988 FPS

.40 S&W 115GR. SPEER LAWMAN RHT @ 1422 FPS

2GR RCC FRAG - V-50 OF 2879 FPS

4GR RCC FRAG - V-50 OF 2395 FPS

17GR RCC FRAG - V-50 OF 2073 FPS



WWW.FIREARMORUSA.COM
(562) 207-4240



FIRE ARMOR USA

Enforcer 6000



THE ENFORCER 6000 IS AN ADVANCED TECHNOLOGICAL DESIGN COMBINING HONEYWELL'S PROVEN GOLD SHIELD®, ADVANCED SPECTRA SHIELD® II, DSM BALLISTIC MATERIAL AND CORE TECHNOLOGY MATERIAL FROM TEXTECH. THE END RESULT IS A LIGHTER, MORE FLEXIBLE VEST THAT STILL SATISFIES THE STRICT PERFORMANCE REQUIREMENTS OF THE NIJ 0101.06 STANDARD.



FEMALE MODEL 6326F

BALLISTIC THREAT LEVEL IIIA

PERFORMANCE DATA

NEW 357 SIG V50 @ 1883 FPS

NEW 44 MAG V50 @ 1671 FPS

AVERAGE BFS 357 SIG - 25.5MM

AVERAGE BFS 44 MAG - 34.8MM

WT. PER SQ. FT. - 16.48 OZ. - 1.03LBS

THINNESS .26 INCHES

TEXTECH ADVANCED CORE, WOVEN KEVLAR ARAMID , HONEYWELL GOLD SHIELD, DYNEEMA

BROOKWOOD ARCHERLITE COVERING



SPECIAL THREAT TESTED

NORINCO 7.62X25MM TOKARAV FMJ @ 1666 FPS

FN 5.7X28MM SS195LF @ 2075 FPS

AGUILA IQ 9MM 65GR HP @ 1664 FPS

.45 ACP 230GR. GDHP @ 875 FPS

GOLD DOT .357 SIG GDHP @ 1375 FPS

9MM CIVIL DEFENSE (LIBERTY) 50GR. HP @ 1991 FPS

9MM CORBON +P 115GR. JHP @ 1428 FPS

9MM WINCHESTER 127GR SXT +P+ @ 1319 FPS

9MM NORMA 116GR FMJ @ 1239 FPS

9MM FIOCCHI 115GR. FMJ @ 1182 FPS

.40 S&W FEDERAL 165GR. HYDRA-SHOK HP @ 975 FPS

.40 S&W REM. GOLDEN SABER 165GR. JHP @ 1156 FPS

.40 S&W WINCHESTER 165GR. BONDED JHP @ 1068 FPS

.40 S&W SPEER 165GR. GDHP @ 1171 FPS

.357 MAG 158GR. MAGTECH JSP @ 1426 FPS

.40 S&W CIVIL DEFENSE (LIBERTY) 60GR. HP @ 1988 FPS

2GR RCC FRAG - V-50 OF 2879 FPS

4GR RCC FRAG - V-50 OF 2395 FPS

17GR RCC FRAG - V-50 OF 2073 FPS



WWW.FIREARMORUSA.COM
(562) 207-4240

