



# SAFETY DATA SHEET

## Section 1: Identification

<b>GHS product identifier</b>	142 Solvent
<b>Synonyms</b>	Distillates, petroleum, hydro treated light; Hydro treated light distillate; Distillates (petroleum), hydro treated light.; Petroleum hydrocarbon solvent; 140 Flash Solvent; High Flash Stoddard Solvent; High-flash Mineral Spirits; Type IIC Mineral Spirits (meets ASTM D-235 Type 2C specifications).
<b>MSDS #</b>	010115
<b>Supplier's details</b>	State 48 Recycling Inc. 2610 W Holly ST. Suite C Phoenix, AZ 85009
<b>Emergency telephone #</b>	(623) 979-1192 Chemtrec (800) 424-9300

## Section 2: Hazards identification

<b>OSHA/HCS status</b>	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
<b>Classification of the substance or mixture</b>	FLAMMABLE LIQUIDS - Category 4 ACUTE TOXICITY: INHALATION - Category 4 SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2B SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [Narcotic effects] - Category 3 ASPIRATION HAZARD - Category 1
<b>Hazard statements</b>	Combustible liquid. Harmful if inhaled. Causes skin irritation and may cause eye irritation. May be fatal if swallowed and enters airways. May cause drowsiness and dizziness.
<b>Precautionary statements Prevention</b>	Wear protective gloves. Wear eye or face protection. Keep away from flames and hot surfaces. - <b>No smoking</b> . Use only outdoors or in a well-ventilated area. Avoid breathing vapor. Wash hands thoroughly after handling.

## Section 2: Hazards identification continued

- Storage** Store locked up. Store in a well-ventilated place. Keep cool.
- Disposal** Dispose of contents and container in accordance with all local, regional, national regulations.

## Section 3: Composition/information on ingredients

**CAS number** 64742-88-7

**Other means of**

**Identification** Distillates, petroleum, hydro treated light; Hydro treated light distillate; Distillates (petroleum), hydro treated light.; Petroleum hydrocarbon solvent; 140 Flash Solvent; High Flash Stoddard Solvent; High-flash Mineral Spirits; Type IIC Mineral Spirits (meets ASTM D-235 Type 2C specifications)

**Boiling Point:** 350-390°F

**Vapor Pressure:** 30 mmHg

**Solubility In Water:** Negligible

**Appearance/Odor:** Colorless liquid with characteristic odor.

**Vapor Density (Air=1):** 5.5

**Volatile %:** 100

**Specific Gravity (H<sub>2</sub>O=1):** 0.78

**Evaporation Rate (BuAc=1):** 1.5

## Section 4: First aid measures

**Response** INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that gas or vapor is still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell.

SWALLOWED: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

SKIN: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.

EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

## Section 5: Fire-fighting measures

### **Specific hazards arising from the chemical**

Combustible liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

### **Extinguishing media**

#### **Suitable extinguishing Media**

Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

#### **Unsuitable extinguishing Media**

Do not use water jet.

#### **Hazardous thermal decomposition products**

Decomposition products may include the following materials:  
carbon dioxide - carbon monoxide

#### **Special protective actions for fire-fighters**

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

#### **Special protective equipment for fire-fighters**

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6: Accidental release measures

### **Non-emergency personnel**

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

## Section 6: Accidental release measures continued

**For emergency responders** If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information "For nonemergency personnel".

**Environmental precautions** Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Solvent 142 is water polluting material. May be harmful to the environment if released in large quantities.

### Methods and materials for containment and cleaning up

**Small spill** Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

**Large spill** Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7: Handling and storage

### Precautions for safe handling

**Protective measures** Put on appropriate personal protective equipment (see Section 8). Do not swallow. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous. Do not reuse container. Non equilibrium conditions may increase the fire hazard associated with this product. Always bond receiving containers to the fill pipe before and during loading. Always confirm that receiving container is properly grounded. Bonding and grounding alone may be inadequate to eliminate fire and explosion hazards. Carefully review operations that may increase the risks such as tank and container filling, tank cleaning, sampling, gauging, loading, filtering, mixing, agitation, etc.

## Section 7: Handling and storage continued

In addition to bonding and grounding, efforts to mitigate the hazards may include, but are not limited to, ventilation, inerting and/or reduction of transfer velocities. Always keep nozzle in contact with the container throughout the loading process. Do NOT fill any portable container in or on a vehicle.

### Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

## Section 8: Exposure controls/personal protection

### Control parameters

### Occupational exposure limits

142 Solvent

**ACGIH TLV (United States)** 179 ppm (1200 mg/m<sup>3</sup>) 8 hour(s)  
Notes: The TLV for the hydrocarbon solvent is based on the procedure described in Appendix H ("Reciprocal Calculations Method for Certain Refined Hydrocarbon Solvent Vapors") of the ACGIH TLVs® and BEIs® guidelines. The GGVMixture (ACGIH TLV) is based on Column B (McKee et al., 2005) of Table 1 ("Group Guidance Values") of Appendix H.

### Appropriate engineering controls

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

### Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, vapor controls, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

### Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

## Section 8: Exposure controls/personal protection continued

- Eye/face protection** Safety glasses equipped with side shields are recommended as minimum protection in industrial settings. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: Splash goggles. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If inhalation hazards exist, a full-face respirator may be required instead.
- Body protection** Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Hand protection** Chemical-resistant gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers.
- Other skin protection** Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** Use a properly fitted, air-purifying or supplied-air respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

## Section 9: Physical and chemical properties

<b>Physical state</b>	Liquid.
<b>Color</b>	Transparent, colorless.
<b>Odor</b>	Characteristic hydrocarbon solvent odor.
<b>pH</b>	Not available.
<b>Melting point</b>	-49°C (-56.2°F)
<b>Boiling point/boiling range</b>	192 to 205°C (377.6 to 401°F)
<b>Flash point</b>	Closed cup: 67°C (152.6°F) [Tagliabue (ASTM D-56)]
<b>Evaporation rate</b>	<1 (n-butyl acetate. = 1)
<b>Lower and upper explosive (flammable) limits</b>	Lower: 0.8% Upper: 6%
<b>Vapor pressure</b>	0.067 kPa (0.5 mm Hg) [room temperature]
<b>Vapor density</b>	>1 [Air = 1]
<b>Relative density</b>	0.79
<b>Density lbs/gal</b>	Estimated 6.59 lbs/gal
<b>Gravity, °API</b>	Estimated 48 @ 60 F
<b>Solubility</b>	Very slightly soluble in the following materials: cold water.
<b>Solubility in water</b>	1.5 g/l
<b>Auto-ignition temperature</b>	>220°C (>428°F)
<b>Conductivity</b>	<50 picosiemens/meter (unadditized)

## Section 10: Stability and reactivity

<b>Reactivity</b>	Not expected to be Explosive, Self-Reactive, Self-Heating, or an Organic Peroxide under US GHS Definition(s).
<b>Chemical stability</b>	The product is stable.
<b>Possibility of hazardous reactions</b>	Under normal conditions of storage and use, hazardous reactions will not occur.
<b>Conditions to avoid</b>	Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas.
<b>Incompatible materials</b>	Reactive or incompatible with the following materials: oxidizing materials
<b>Hazardous decomposition products</b>	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11: Toxicological information

### Information on toxicological effects

#### **Acute toxicity**

##### **Conclusion/Summary**

**: C9-C15 Alkanes:** In animal studies utilizing mineral spirits containing up to 22% aromatics indicated that the acute central nervous system effects are reversible. Based on existing animal studies, the potential for persistent effects is not clear.

**Distillates (petroleum), hydrotreated light:** Mineral spirits have produced slight to moderate skin irritation particularly with evaporation from the skin is prevented. Animal studies have demonstrated that mineral spirits produced mild respiratory tract irritation at elevated concentrations.

#### **Irritation/Corrosion**

##### **Skin**

**C9-C15 Alkanes:** Primary dermal irritation studies (four hour exposure) in rabbits utilizing mineral spirits containing less than 2% aromatics resulted in slight to moderate skin irritation. In humans, mineral spirits have produced slight to moderate skin irritation particularly with evaporation from the skin is prevented.

##### **Eyes**

No additional information.

#### **Respiratory**

**C9-C15 Alkanes:** Animal studies have demonstrated that mineral spirits produced mild respiratory tract irritation at elevated concentrations. Also, sensory respiratory tract irritation was evident by reduced breathing rates in the test animals in certain studies.

## Section 11: Toxicological information continued

### Sensitization

#### **Skin**

**C9-C15 Alkanes:** In animal studies utilizing mineral spirits containing up to 18%, aromatics skin sensitization is not evident.

#### **Respiratory**

No additional information.

### Mutagenicity

#### **Conclusion/Summary**

**C9-C15 Alkanes:** In vivo and in vitro studies on mineral spirits containing up to 22 % aromatics indicate that these products are not genotoxic.

### Carcinogenicity

#### **Conclusion/Summary**

**C9-C15 Alkanes:** The National Toxicology Program (NTP) conducted two-year carcinogenicity studies in rats and mice with Stoddard Solvent IIC (less than 2% aromatics). The studies indicated that there was some evidence of carcinogenic activity in male rats (adrenal medulla neoplasms and renal tubule adenoma) but no evidence of carcinogenic activity in female rats. Further, there was equivocal evidence of carcinogenic activity in female mice (hepatocellular adenoma) but no evidence of carcinogenic activity in male mice. A low carcinogenic potential is suggested by a lack of genotoxic potential identified in in vivo and in vitro genetic toxicity tests (with and without metabolic activation).

### Reproductive toxicity

#### **Conclusion/Summary**

**C9-C15 Alkanes:** There were no treatment-related effects on pregnancy rate, mortality or gross post mortem observations in animal studies utilizing mineral spirits containing less than 2% aromatics.

### Teratogenicity

#### **Conclusion/Summary**

**C9-C15 Alkanes:** There were no treatment-related effects on pregnancy rate, mortality or gross post mortem observations in animal studies utilizing mineral spirits containing less than 2% aromatics.

### Specific target organ toxicity (single exposure)

<b>Name</b>	<b>Category</b>	<b>Route of Exposure</b>	<b>Target organs</b>
C9-C15 Cycloalkanes	Category 3	Not applicable.	Narcotic effects
C9-C15 Alkanes	Category 3	Not applicable.	Narcotic effects

### Specific target organ toxicity (repeated exposure)

Not available.

### Aspiration hazard

#### **Name**

C9-C15 Cycloalkanes  
C9-C15 Alkanes

#### **Result**

ASPIRATION HAZARD - Category 1  
ASPIRATION HAZARD - Category 1

### Information on the likely routes of exposure

Routes of entry anticipated: Oral, Dermal, and Inhalation.



## Section 11: Toxicological information continued

### Potential acute health effects

<b>Eye contact</b>	May cause eye irritation.
<b>Inhalation</b>	Harmful if inhaled. Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness.
<b>Skin contact</b>	Causes skin irritation.
<b>Ingestion</b>	Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways. Irritating to mouth, throat and stomach.

### Symptoms related to the physical, chemical and toxicological characteristics

<b>Eye contact</b>	Adverse symptoms may include the following: pain or irritation, watering, and redness.
<b>Inhalation</b>	Adverse symptoms may include the following: nausea or vomiting, headache, drowsiness/fatigue, dizziness/vertigo, unconsciousness
<b>Skin contact</b>	Adverse symptoms may include the following: Irritation, redness
<b>Ingestion</b>	Adverse symptoms may include the following: nausea or vomiting

### Potential chronic health effects

<b>General</b>	No known significant effects or critical hazards.
<b>Carcinogenicity</b>	No known significant effects or critical hazards.
<b>Mutagenicity</b>	No known significant effects or critical hazards.
<b>Teratogenicity</b>	No known significant effects or critical hazards.
<b>Developmental effects</b>	No known significant effects or critical hazards.
<b>Fertility effects</b>	No known significant effects or critical hazards.

## Section 12: Ecological information

<b>Toxicity</b>	Not available.
<b>Persistence and degradability</b>	Not available.
<b>Bioaccumulative potential</b>	Not available.
<b>Mobility in soil</b>	Not available.
<b>Other adverse effects</b>	Not available.

## Section 13: Disposal considerations

### Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

### RCRA classification

D018

## Section 14. Transport information

<b>UN number</b>	<b>DOT Classification</b> NA 1993	<b>IMDG</b> Not regulated.	<b>IATA</b> Not regulated.
<b>UN proper Shipping name</b>	NA 1993 Combustible Liquid n.o.s., (Solvent Naphtha), Combustible Liquid		
<b>Transport hazard class(es)</b>	Combustible liquid.		
<b>Packing group</b>	Combustible liquid		
<b>Environmental Hazards</b>	No.	No.	No.
<b>Additional Information</b>	<b>Packaging instruction</b> <b>Passenger aircraft</b> Quantity limitation: 60 L Packaging instructions: 203 (non-bulk) <b>Cargo aircraft</b> Quantity limitation: 220 L Packaging instructions: 203 (non bulk), 241(bulk)		
<b>Special precautions for user</b>	<b>Transport within user's premises:</b> always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.		

## Section 15: Regulatory information

### U.S. Federal regulations

**TSCA 12(b) one-time export:** Nonane, all isomers  
**United States inventory (TSCA 8b):** All components are listed or exempted.

**Clean Water Act (CWA) 307:** Naphthalene; Benzene; Toluene; Ethylbenzene

**Clean Water Act (CWA) 311:** Naphthalene; Benzene; Toluene; Ethylbenzene

This material is classified as an oil under Section 311 of the Clean Water Act (CWA) and the Oil Pollution Act of 1990 (OPA). Discharges or spills which produce a visible sheen on waters of the United States, their adjoining shorelines, or into conduits leading to surface waters must be reported to the EPA's National Response Center at (800) 424-8802.

### SARA 302/304

#### Composition/information on ingredients

#### SARA 304 RQ

Not applicable.

### SARA 311/312

#### Classification

Fire hazard Immediate (acute) health hazard

### Composition/information on ingredients

<u>Name</u>	<u>Fire hazard</u>	<u>Sudden release of pressure</u>	<u>Reactive</u>	<u>Immediate (acute) health</u>	<u>Delayed (chronic) health</u>
C9-C15 Cycloalkanes	Yes	No.	No.	Yes.	No.
C9-C15 Alkanes	Yes	No.	No.	Yes.	No.

**WARNING:** This product contains less than 0.1% of a chemical known to the State of California to cause cancer.

**WARNING:** This product contains less than 1% of a chemical known to the State of California to cause birth defects or other reproductive harm.

## Section 16: Other information

Date of issue/Date of **10/07/2021**

THE INFORMATION IN THIS SAFETY DATA SHEET (SDS) WAS OBTAINED FROM SOURCES WHICH WE BELIEVE ARE RELIABLE. HOWEVER, THE INFORMATION IS PROVIDED WITHOUT ANY WARRANTY, EXPRESSED OR IMPLIED REGARDING ITS CORRECTNESS OR ACCURACY. SOME INFORMATION PRESENTED AND CONCLUSIONS DRAWN HEREIN ARE FROM SOURCES OTHER THAN DIRECT TEST DATA ON THE SUBSTANCE ITSELF. THIS SDS WAS PREPARED AND IS TO BE USED ONLY FOR THIS PRODUCT. IF THE PRODUCT IS USED AS A COMPONENT IN ANOTHER PRODUCT, THIS SDS INFORMATION MAY NOT BE APPLICABLE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION OR PRODUCTS FOR THEIR PARTICULAR PURPOSE OR APPLICATION.