

EN 81.20-50
MRL
& MR
GEARLESS



New installations



Traction



MP2_N Board



EN 81.20-50



MRL & MR

EN 81.20-50

GEARLESS

All the ideal solutions for new elevator installations with machine room (MR) or machine room-less (MRL), based on your needs.

These systems are able to manage elevators with up to 12 stops, ensuring reliability, efficiency and ease of installation.



Domestic



Residential



Public Buildings

Technical

Floors	Up to 12 (expandable to 32)
Serial Communication	CAN to car top
Access Management	Up to 3 entrances
Power Supply	Single or 3 Phase
Emergency Descent	Automatic maneuver
Door Management	Manual or automatic
Conformity	EN 81.21-50 and UNI EN 81.28
VVVF	From 4 KW to 15 KW
Dimensions [mm]	MRL L 400 x P 265 x H 2200 MR » W7: L 600 x P 265 x H 1115 » EQ114: L 730 x P 400 x H 1400
Cabinet Finishes	MRL Lampre N67 RAL 7032 compatibile MR » W7: Lampre F2 RAL 9006 » EQ114: RAL 9006 bucciato

Functions



Telemetry



Pre-cabling



Multiplex



UPS



QuickUP



Stand-By



Reduced Pit



AGV

