

Spiral Hose Guard



Thermoplastic extruded spiral with rounded external surface, smoothed edges and ribbed internal profile
 Lightweight, yet crush-resistant
 Stays in place on the hose without sliding
 Easily overlaps offering greater protection
Material: Propene Polymer, non-toxic
Temperature range: -30° to +175°F
Combustibility: The product is not self-extinguishing. Speed of combustion at British Standard 1524-55 is 1 1/4" per minute

Part Number	Part Description	List Price
BPHG-.25	.25" x 40'	\$35.11
BPHG-.37	.37" x 40'	\$43.45
BPHG-.50	.50" x 40'	\$43.45
BPHG-.62	.62" x 40'	\$52.31
BPHG-.75	.75" x 40'	\$61.85
BPHG-1.00	1.00" x 40'	\$88.60
BPHG-1.10	1.10" x 40'	\$155.55
BPHG-1.38	1.38" x 40'	\$203.75
BPHG-1.75	1.75" x 40'	\$292.55
BPHG-2.56	2.56" x 40'	\$366.10
BPHG-3.15	3.15" x 40'	\$431.56



Mini Ball Valves

Mini Ball Valve



Maximum working pressure: 235 PSI (will handle 300 PSI at 75° F)
 Solid chrome-plated brass ball
 Longer body style for longer and deeper thread connections
 One-piece nickel-plated brass body
 Double seal system allows valve to operate in both directions
 Blowout-proof brass stem
 Temperature range: 32° F to 176° F

Male x Female		
Part Number	Size	List Price
MBV-1/8-MXF	1/8"	\$6.24
MBV-1/4-MXF	1/4"	\$6.24
MBV-3/8-MXF	3/8"	\$6.15
MBV-1/2-MXF	1/2"	\$9.72

Female x Female		
Part Number	Size	List Price
MBV-1/8-FXF	1/8"	\$7.02
MBV-1/4-FXF	1/4"	\$7.02
MBV-3/8-FXF	3/8"	\$6.52
MBV-1/2-FXF	1/2"	\$9.72