Crawler Scissor Lift S08C GS3443C

GDMANLIFT Crawler Scissor Lift S08C GS3443C




Crawler Scissor Lift S08C www.gomanlift.ca


GS3443C


Standard Parameters


Model	S08C	GS3443C
Max. work height	10.5m	34.4'
Max. platform height	8.5m	27.8′
Load capacity	230kg	507lb
Extend platform safe working load	113kg	249lb
Size of platform	2.30x1.11x1.08m 9	90.5"x43.7"x42.5"
Platform extension size	0.90x1.11x1.08m 3	35.4"x43.7"x42.5"
Overall stowed height (lift)	2.33m	91.7"
Overall stowed height	1.82m	71.6"
Overall stowed length	2.52m	99.2"
Overall stowed width	1.69m	66.5"
Standard power	24V/4.5KW,364A	Ah lithium battery
Optional power	6.5hp Gas engine, length/width varies*	
Driving speed-Elevated	0-0.5 km/h*	
Driving speed-Lowered	0-1.5 km/h*	
Lift/Lower time	45/30 sec*	
Max. climbing ability	36%*	
Max. work slope	26%*	
Total weight	2510kg	5533lb





Technical data














Standard Features

- ► Automatic leveling, simple control console
- ▶ suitable for tracking and working on uneven and rough terrain
- ► Easy operation, with gravity lowering (emergency lowering)
- ► Weight dispersal low ground pressure
- ► Hydraulic adjustable rubber crawlers
- ► Made of high tensile steel
- ▶ Optional: platform can slide to the side about 300mm





