



**P16**

## Technical data

Model	P16	GP52	P18	GX59
Max. work height	16.00m	52'	18.30m	60'
Max. platform height	14.00m	46'	16.30m	52'
Load capacity	230kg	500lb	200kg	440lb
Lateral Outreach	8.80m	28.8'	10.10m	33.1'
Jib rotation	90°			
Turntable	360°non-continuous			
Size of platform	0.9*0.8*1.1m		36" x 31.5"	
Overall stowed length	5.98m	19.6'	5.81m	19.1'
Overall stowed width	1.77m		69.6"	
Overall stowed height	2.16m		85"	
Total weight	2000kg	4405lb	2265kg	4995lb
Permitted towing speed	80km/h			
Work slope	20%			
Power Source:	Standard: Lead-acid Battery ( combustion engine and AC available)			



### Standard Features ---Simply reliable!

- ▶ Outriggers manual control; can be towed at 80km/h
- ▶ Hydraulically arms and outrigger interlock
- ▶ 230v(110v) 50Hz 16A outlet in the work platform
- ▶ Made of high tensile steel, hot dip galvanized boom
- ▶ Detachable control panel, can be used at ground for friction drive as option; radio control as optional,
- ▶ Low weight dispersal on ground
- ▶ Self-leveling basket; rotation as optional.
- ▶ Reach standard of ISO, CE and ANSI

