

## Vest Harness with Lanyard

Gemtor's Fall Protection Vest Combines a OSHA/ANSI/CSA compliant polyester full-body harness within a comfortable easy to don, lightweight vest. A pocket at the center of the wearer's back holds a specially designed energy absorbing lanyard (SPCL) Shown ► and described on Page 2.

### Feature & Benefits:

- ✔ Durable water resistant outer shell, mesh lining for user comfort and easy inspection.
- ✔ Dorsal (back) D-ring for fall arrest connection.
- ✔ Quick connect chest and leg strap buckles.
- ✔ Double layer front pockets hold lanyard web and snap hook plus user's gear.
- ✔ Heavy-duty zippered front.
- ✔ Zippered bottom for easy harness inspection.
- ✔ Meets OSHA, ANSI, CSA Z259.10



Part #	Description /Size
846377-1	Small
846377-2	Medium
846377-3	Large
846377-4	Extra-Large
846377-9	Extra-Extra-Large
SPCL	Energy absorbing lanyard

# GEMTOR

# ELEVATOR FALL PROTECTION

...when your life is on the line™



## High Visibility Vest Harness

Gemtor's Fall Protection Vest Combines a OSHA/ANSI/CSA compliant polyester full-body harness within a comfortable easy to don, lightweight, high visibility reflective vest. Includes centrally located lanyard pocket on back.

### Feature & Benefits:

- ✔ Durable water resistant outer shell, mesh lining for user comfort and easy inspection.
- ✔ Dorsal (back) D-ring for fall arrest connection.
- ✔ Quick connect chest and leg strap buckles.
- ✔ Double layer front pockets hold lanyard web and snap hook plus user's gear.
- ✔ Heavy-duty zippered front.
- ✔ Zippered bottom for easy harness inspection.
- ✔ Meets OSHA, ANSI, CSA Z259.10
- ✔ High visibility fabric for better recognition of workers on construction site.



Available Models (High Visibility Vest)	
Size	Part #
Small	846427-1
Medium	846427-2
Large	846427-3
X Large	846427-4
XX Large	846427-9
Energy absorbing lanyard*	SPCL
*Available Separately (See Page 2)	



## Flame Resistant Fall Protection Overalls

Made of 4.5 oz. Nomex® IIIA, this overall is lightweight enough to be worn in almost any climate; offers the flame resistance of Nomex®, and features the fall protection of an OSHA compliant polyester full-body harness. The overall is available in a range of sizes and requires only minimal adjustment since the harness is sized to fit the overall. Quick connect buckles at the shoulder straps makes donning fast and simple. A pocket at the center of the wearer's back holds a specially designed energy absorbing lanyard (Part # SPCL available separately, see Page 2). A chest pocket holds the loose end of the lanyard when not in use. Meets OSHA, ANSI, CSA Z259.10.



Available Models (Overalls)		
Fits Waist	Fits Inseam	Part #
30" - 32"	29"	FPO S/S
	32"	FPO S/M
	35"	FPO S/L
34" - 36"	29"	FPO M/S
	32"	FPO M/M
	35"	FPO M/L
38" - 40"	29"	FPO L/S
	32"	FPO L/M
	35"	FPO L/L
42" - 44"	29"	FPO XL/S
	32"	FPO XL/M
	35"	FPO XL/L
46" - 48"	29"	FPO 2XL/S
	32"	FPO 2XL/M
	35"	FPO 2XL/L
50" - 52"	29"	FPO 3XL/S
	32"	FPO 3XL/M
	35"	FPO 3XL/L



Part #	Description
SP1101UA5	Energy Absorbing Lanyard w/ Aluminum Snaphooks
900-2	Full-Body Harness



### Full-Body Harness

Full body, sub-pelvic harness with quick-connect leg and chest straps with spring loaded shoulder adjustments.  
Color: Green/Yellow.  
Meets CSA Z259.10.  
Part # 900-2

### Energy Absorbing Lanyard

1" wide x 5' long (maximum), adjustable length with aluminum snaphooks at each end. Color: Green/Yellow.  
Meets CSA Z259.11  
Part # SP1101UA5

### 100% Tie-Off Energy Absorbing Lanyard

Two 1" wide x 5' long (maximum) adjustable length legs with aluminum snaphooks at each end. Color: green/yellow.  
Meets CSA Z259.11.  
Part # SP1101UA5




### Special Energy Absorbing Lanyard

This energy absorber is designed specifically for use with the fall protection overalls and vests. The lanyard is adjustable length (3'-5') and features aluminum carabiners for attachment to the back of the fall protection uniform and at the opposite end for attachment to cable grab or other anchorage. The CSA model has steel carabiner for attachment to fall protection uniform and steel snap hook at other end of lanyard. Meets OSHA, ANSI, CSA Z259.11.  
Part # SPCL



### Wire Rope Lifelines

Designed for use with Gemtor cable grab. Made of 3/16" diameter stainless steel wire rope with a 5" loop at one end. Features a Kevlar/Fiberglass sleeve at loop end for protection over a sharp edge. Available in lengths from 50' to 500'. Meets OSHA, ANSI standards.



### Cable Grab

Stainless steel cable grab for use with 3/16" diameter stainless steel wire rope, vertical lifelines. Can be attached, detached and positioned at any point along the lifeline. Weighs only 1 1/2 pounds. Must be used with an energy absorbing lanyard. Meets OSHA, ANSI, CSA Z259.2.1.  
Part # VW655



### Anchor Sling, Choker Style

Provides an OSHA-compliant anchor point when attached to a structural support capable of supporting at least 5,000 lbs. The anchor sling is made of 1 3/4" wide nylon webbing with a 3" wide wear pad to protect against abrasion. The anchor sling is wrapped around the structural support, and the standard size D-ring is passed through the larger D-ring. Connection is made to the standard size D-ring. Meets OSHA, ANSI standards. 4 foot length.  
Part # AS-2-4  
Also available in 6 foot length.  
Part # AS-2-6



### Jumper Kit

These electrical circuit jumpers can be used by elevator mechanics to operate an elevator during installation, modernization or troubleshooting.  
Part # 124027-6 Complete Kit

#### Kit contains:

- Two (2) - Wire leads with alligator clips at each end, 36" long, with caution card.
- One (1) - Wire lead with plunger hooks at each end, 36" long, with caution card.
- One (1) - Wire lead with miniature, stackable banana plugs, 36" long, with caution card.
- Two (2) - WAGO terminal lugs.
- One (1) - Case.

(Continued on reverse side) ▶

### Retractable Lanyard

Compact, lightweight, cast aluminum fall limiter with 1" wide Technora web lifeline. Has a cast aluminum housing and weighs only 2.8 lbs.



#### Available Models

Part #	Description
FLW-11	10' long Polyester lanyard
FLW-11T	10' long Technora lanyard

### Locking Carabiner

Steel offset D-Carabiner with automatic locking gate. Overall length: 4 7/16" Gate opening: 1" Tensile Strength: 10,000 lbs.  
Part #5105



### Deep Pit Fall Protection

This bracket attaches to the elevator rail for attachment of a Retractable Lifeline to allow safe access to deep pit areas.

Part # ERB-1-34 Rail Bracket

Part # SRL-30SERB Retractable Lifeline



### D-Ring Extension

Made of 1" wide x 18" long Polyester webbing. Includes D-Ring on one end and web loop on other end for choker attachment to harness D-Ring.  
Part #540PW



Part #	Length	Part #	Length
20-050K	50'	20-300K	300'
20-100K	100'	20-350K	350'
20-150K	150'	20-400K	400'
20-200K	200'	20-150K	450'
20-250K	250'	20-500K	500'



Front

Back

