

Lightbox Double 100 Dibond

Double-sided LED frames

- NF-041005
- NF-211005
- NF-561005
- Any colour possible

Specifications

- ↔ 100 mm
- 🧰 1.258 kilos/meter
- ↗ 6150 mm
- 💡 Illuminated
- © CE certified
- ✓ Two-year warranty



About the Lightbox Double 100 Dibond

The Lightbox Double 100 Dibond is a double-sided profile. The LEDs are mounted on both sides of the dibond plate. This ensures that the textile fabric is perfectly illuminated.

The advantages

- ✓ High quality light diffusion
- ✓ LED technology: LED on Dibond
- ✓ Delivered pre-assembled
- ✓ Two-year warranty

Mounting



Freestanding

Freestanding frame with a textile on both sides.



Attached to the ceiling

Frames suspended from the ceiling. Both horizontal as well as vertical suspension is possible.

Finish



Closed

An even finish. If desired, holes can be drilled in the profile so that accessories can be attached.

Illumination



LED on Dibond


- Even light distribution due to backlighting
- Suitable for small and medium sized frames
- Narrow frames possible
- Quick installation due to pre-assembled frame

Lightcolour




3000K

Warm white.



4000K

Yellow white.



6500K

Bright white (daylight).

Dimmable



Dimmable

The brightness of the LED frame can be adjusted with a dimmer. This way, the light intensity can be determined depending on the environment.



DALI dimmable

The LED frame is prepared for a connection to a DALI system.

Dimmer



Dimmer

The LEDs have white colours. The three most commonly used colours are: warm white, yellow white and bright white.

Recommended accessories

Locksets



Lockset 100

FK-0240

Extension sets



**Extension set
Eco/Simple**

FK-0510

Connectors



Dibond connector

NF-56280

Led-componenten



FK7 12LEDs

AF92-020



FK7 2LEDs

AF92-005



FK7 3LEDs

AF92-010



FK7 6LEDs

AF92-015

Led-strips



FK2-C 12LEDs
AF92-420



FK2-C 2LEDs
AF92-405



FK2-C 3LEDs
AF92-407



FK2-C 4LEDs
AF92-410

Controllers



**LED controller
dimmer**
AF92-220



Dimmer remote
AF92-230