

# PixelStor 300e

## Data Sheet



## High-Density Expansion

The PS300 expansion line is part of the PS5000 product family. It includes the PS312 and PS392. It is the first storage system which provides uninterrupted video surveillance recording while simultaneously providing metadata to analytics servers. The PS5000 is known for its patented surveillance-optimized cache technology that can scale the video recording to thousands of HD cameras without dropping a single frame of video.

### Applications

- High-performance megapixel cameras
- Very large video surveillance installations
- Analytics metadata storage

### Features:

- **2U and 5U enclosures**
- **Up to 1.5PB of Storage**

**Patented advanced video caching** technology (VAN®<sup>®</sup>, FlowThrough®, StreamAlign®) enables no recording gaps while increasing read/write performance

**Full redundancy** and **high availability** ensure video recording does not stop and is not lost due to any storage failures

**Storage consolidation** for NVR/DVRs significantly lowers purchase, CAPEX, and OPEX costs

**Storage monitoring tools** including BusyPlot®, Proactive™ drive-cloning, Performance Monitoring, Disk Monitoring, and ZM (Zero Maintenance) technology to ensure the best system performance with no loss of video frames

**Effortless installation**, management and administration along with advance RAID



### For more information contact:

**Tel:** +1 (408) 730-2568 | **Toll Free** +1 (888) 902-8981 | **Website:** [www.rasilient.com](http://www.rasilient.com)  
**Sales:** [sales@rasilient.com](mailto:sales@rasilient.com) | **Technical Support:** [techsupport@rasilient.com](mailto:techsupport@rasilient.com)

# PixelStor 300e



## Data Sheet



### Specifications

<b>Enclosure</b>	2U, 5U
<b>Max. HDDs</b>	Up to 92
<b>Capacity</b>	PS312: 3.5" 4, 6, 8, 10, 12, and 14TB SAS or SATA HDD PS392: 3.5" 4, 6, 8, 10, and 12TB SAS HDD
<b>Interface Ports</b>	PS392: Three SAS 3.0/12Gbps ports (per controller) PS312: Two SAS 3.0/6Gbps ports (per controller) One Serial port (per controller)
<b>RAID</b>	5, 6, 10, 50, and 60
<b>Dimensions (WxHxD)</b>	PS312: 3.4"x 17.6"x 23.7"/86.8x445.8x237mm PS392: 8.66"x 17.6"x 38.1" / 220x445.8x968mm
<b>Weight</b>	PS312: 60.5 lbs/27.4 kg PS392: 286 lbs/130 kg
<b>Power</b>	PS312: 600 Watts (Redundant) PS392: 2400 Watts (Redundant)
<b>Operating Temperature</b>	10°C - 35°C

\*Additional configurations are available.  
Please contact Rasilient for a free consultation.



### For more information contact:

**Tel:** +1 (408) 730-2568 | **Toll Free** +1 (888) 902-8981 | **Website:** [www.rasilient.com](http://www.rasilient.com)  
**Sales:** [sales@rasilient.com](mailto:sales@rasilient.com) | **Technical Support:** [techsupport@rasilient.com](mailto:techsupport@rasilient.com)