



DCS-9859 RELIQUEFICATION ASPHALTENE-BASED SLUDGES

DCS-9859 combines a unique blend of surface-active compounds with several proprietary solubilization chemistries. Additionally, micro-surfactants provide penetration into even severely dehydrated deposits, allowing the solubilization chemistries to function quicker. Now deposits across a vast spectrum, even with minimal flow or agitation, can be addressed.

APPLICATIONS

DCS-9859 is for asphaltene-based sludges. It is designed specifically for reliquefying or remediating petroleum (hydrocarbon) based sludges, sediment, and solids.

- The hydrocarbon chains are reliquefied, the viscosity reduced by 80% or more, and the API gravity increased.
- Typically, more than 95% of the available hydrocarbons are recovered without harm to the oil.

For treating tank bottoms, it is recommended that 1-5% plus 1-4% carrier based on volume of crude/sludge should be spotted on the bottom to soak for 24-72hrs., depending on sludge depth.

- If possible, thin the tank solution thoroughly mixed by rolling the tank or using external circulation. Heating of the tank is not necessary, although helpful.

*As each application is unique, please contact your Dry Creek account director for dosage recommendations and additional optimizations.

BENEFITS AND FEATURES

- Increased oil & gas production
- Does not require heating
- Does not require removal prior to refining
- Provides demulsification
- Reduces pumping fees
- Rapid clean-up
- Reduces oil viscosity
- Reduces under deposit corrosion
- Prevents redeposition

28610 Highway 290, Ste. F09-#222, Cypress, TX. 774333 | 713.885.6139
drycreeksolution.com