



CTM-MARINE CW

High-efficient chilled water
marine air conditioners



**24k - 36k - 48k
60k - 72k
BTU**



High-Efficient
Compressor



Compact



Cool/Heat



Titanium
Condenser Coil



Corrosion Free
Base



DDC
Control Board

www.ctm-marine.com

Air conditioners for the modern sailor.

Model No.	CW-24H	CW-36HS	CW-48HS	CW-60HS	CW-72HS
Capacity (BTU)	24,000	36,000	48,000	60,000	72,000
Voltage (V)	208 - 240				
Cycle (Hz) / Phase (Ph)	50-60 / 1				
Input: Cool (A)	7.6	9.5	14	20	23
Input: Heat (A)	9	13	19	25	30
Fuse Max/Min (A)	25 / 16	35 / 20	65 / 40	80 / 50	90 / 60
Locked Rotator Amps (A)	42				
Seawater In / Out Connection (in)	5/8		3/4		
Chilled Water In / Out Connection (in)	3/4		1		
Seawater Flow (GPH)	500	750	1000	1250	1500
Refrigerant Type	R410A				
Net Weight (lbs/Kg)	75 / 34	97 / 44	150 / 68	161 / 73	167 / 76
Width (W) in/mm	14.1 / 360	14.1 / 360	17.7 / 450	20.2 / 515	20.2 / 515
Height (H) in/mm	18.9 / 480	20 / 510	19.6 / 500	21 / 535	21 / 535
Depth (D) in/mm	9.8 / 250	9.8 / 250	13 / 332	13 / 332	13 / 332

S = Soft Start H = 220 v HS = 220 v unit with Soft Start

