



PVC C900

Pressure Rated Water



Specification: AWWA C900-16, CSA B137.3, ANSI NSF61, FM (4"-12" DR 14) NSF/ ANSI 372 (4"-24" DR 25 & 18)

Compound: ASTM D1784 Cell Classification 12454

Gasket: ASTM D3139, ASTM F477



Blue in color. Available in nominal laying lengths of 20 feet . Pipe is manufactured in a certified ISO 9001:2015 facility using PVC resin manufactured in the US without the use of plasticizers.

PIPE SIZE	AVERAGE O.D.	NOM I.D.	MIN WALL (T)	NOM I.D.	MIN WALL (T)	NOM I.D.	MIN WALL (T)
		PRESSURE CLASS 305 DR 14 PIPE STIFFNESS: 815 PSI		PRESSURE CLASS 235 DR 18 PIPE STIFFNESS: 364 PSI		PRESSURE CLASS 165 SDR 25 PIPE STIFFNESS 129 PSI	
4	4.80	4.07	0.343	4.23	0.267	4.39	0.192
6	6.90	5.86	0.493	6.09	0.383	6.31	0.276
8	9.05	7.68	0.646	7.98	0.503	8.28	0.362
10	11.10	9.42	0.793	9.79	0.617	10.16	0.444
12	13.20	11.20	0.943	11.65	0.733	12.08	0.528
14	15.30	-	-	13.50	0.850	14.00	0.612
16	17.40	-	-	15.35	0.967	15.92	0.696
18	19.50	-	-	17.20	1.083	17.85	0.780
20	21.60	-	-	19.06	1.200	19.77	0.864
24	25.80	-	-	22.76	1.433	23.61	1.032

* All sizes in inches



Supplylinesales.com



contact@supplylinesales.com

Supply Line Sales, LLC

P.O. BOX 778026

Henderson, NV 89077