



PVC SDR 32.5-51

Irrigation PIP



Specification: ASTM 2241

Compound: ASTM D1784 Cell Classification 12454

Gasket: ASTM D3139, ASTM F477

White and blue available in color. Available in nominal laying lengths of 20 feet or 22 feet. Pipe is manufactured in a certified ISO 9001:2015 facility using PVC resin manufactured in the US without the use of plasticizers.

PIPE SIZE	AVERAGE O.D.	NOM I.D.	MIN WALL (T)	NOM I.D.	MIN WALL (T)	NOM I.D.	MIN WALL (T)
		PRESSURE CLASS 125 SDR 32.5 PIPE STIFFNESS: 57 PSI		PRESSURE CLASS 100 SDR 41 PIPE STIFFNESS: 28 PSI		PRESSURE CLASS 80 SDR 51 PIPE STIFFNESS: 14 PSI	
6	6.140	5.74	0.189	5.82	0.150	5.89	0.120
8	8.160	7.63	0.251	7.74	0.199	7.82	0.160
10	10.200	9.53	0.314	9.67	0.249	9.78	0.200
12	12.240	11.44	0.377	11.61	0.299	11.73	0.240
15	15.300	14.30	0.479	14.51	0.373	14.66	0.300
18	18.701	17.48	0.575	17.73	0.456	17.92	0.366

* All sizes in inches



Supplylinesales.com



contact@supplylinesales.com

Supply Line Sales, LLC
P.O. BOX 778026
Henderson, NV 89077