

Evans Network of Companies – Federal Vehicle Inspection Form




| | | | | | |
|--|--------|---------|------|--|-------------------|
| Terminal JFL | Unit # | Mileage | Date | Inspection Facility | |
| Carrier/DOT# EVANS Delivery / DOT #038111 | | | | <input type="checkbox"/> Sleeper <input type="checkbox"/> Day Cab | Address and Phone |
| VIN | | | | | Tire Size / / |
| EMAIL inspection and invoice to: SafetyTruckVendor@EvansDelivery.com or FAX 855-965-0954 or MAIL 1171 Market Street, Suite 202, Fort Mill, SC 29708 | | | | | |

INSTRUCTIONS: Mark each row to verify inspection. = OK = Needs Repair NA = Does not apply **QUESTIONS?** Call 1-803-547-7795

| BRAKE SYSTEM | |
|--|--|
| Service brakes | |
| Parking brake | |
| Brake Shoes and Drums | |
| Brake hose/tubing | |
| Low pressure warning devices | |
| Tractor protection valve | |
| Air compressor | |
| EXHAUST SYSTEM | |
| No part of system should be leaking at a point forward or directly below the cab OR be located where it would be likely to burn or melt any electrical or fuel system. | |
| TIRES | |
| Steering axle tires tread 4/32" | |
| All other tires tread 2/32" | |
| No cuts, flats, or separation | |
| WHEELS & RIMS | |
| No Wheels or rims cracked | |
| No loose or missing fasteners | |
| Lock/Side ring | |
| SUSPENSION | |
| No U-bolts, spring hanger, or other axle position part cracked, broken, loose, or missing, resulting in shifting of an axle from its normal position. | |
| No spring assembly broken, loose, or missing. | |

| STEERING MECHANISM | |
|--|--|
| Steering wheel free play (Lash) | |
| Steering column looseness | |
| No loose steering components | |
| Steering gear box loose form frame | |
| Pitman Arm loose from output shaft | |
| No Ball and Socket joints loose | |
| FRAME | |
| No frame members broken or cracked | |
| LIGHTING DEVICES | |
| Complies with CFR 393.11 | |
| FUEL SYSTEM | |
| No visible leak | |
| Fuel tank filler cap present | |
| Fuel tank securely attached | |
| SAFE LOADING | |
| No part of vehicle or load should be able to fall onto the road. Cargo must have protection from shifting. | |
| COUPLING DEVICES | |
| Fifth wheel/mounting | |
| Pintle hooks | |
| Drawbar/towbar tongue | |
| WINDSHIELD AND WIPERS | |
| Complies with CFR 393.60 | |
| All wipers must be operational | |



Notes: _____

This vehicle has: **PASSED** all the inspection items for the federal vehicle inspection report in accordance with 49 CFR 396.
 FAILED the inspection items for the federal vehicle inspection report in accordance with 49 CFR 396. [Please call 1-803-547-7795]

Date _____ Inspector's Signature _____

Rev.7/23/21 Printed Name _____