



535 rue Pierre Levasseur - CS 60263
44158 ANCENIS - FRANCE

T. +33 (0) 2 51 14 14 40
F. + 33 (0) 2 40 96 32 36

www.agrisem.com
agrisem@agrisem.com



Your Dealer:

Stubberud Maskin AS





TURBOMULCH®

TURBOMULCH®



Our company has developed a new range: «Top Soil Management» 2 to 5 cm.







The TURBOMULCH® was design by AGRISEM to manage the surface residues.

The machine can be used just after the harvesting to accelerate the decomposition of residues and equalize the straws.

It used to manage weeds and crop regrowth in several passages. The machine can be used after seeding to improve the ground contact with seed.

TURBOMULCH® also reduces the use of chemical products in agriculture.

Range Specifications

SPECIFICATION	Folding models		
 Working width (≈ m)	6,20	7,30	8,60
 Transport width (≈ m)	3,00	3,00	3,00
 Weight (≈ kg)	1 868	1 968	2 196
 Weight (≈ kg) <i>with cutter roller</i>	2 765	2 978	3 391
Weight (≈ kg) <i>with double rows of disks</i>	3 498	3 775	5 350
 Power req. min-max (≈ hp)	130 - 180	140 - 190	150 - 200
 Number of tines	50	60	70



Two rows of Ø400 mm Turbo discs:

- » Higher cutting capacity
- » Vertical shallow work for weeds management
- » 6° of orientation for very light disturbance



Frontcutter roller:

- » Hydraulic adjustment
- » Increased residues cutting



Five rows of Ø16 x 760 mm tines:

- » High capacity to manage big straw and residues quantity



- » Independant setting of 4th and 5th row angle for better finish and for clearance