




- **BZ** Hand Tools for Blind Rivets
- VNG Hand Tools for Blind Rivet Nuts and Blind Rivet Bolts
- MULTI Hand Tools for Blind Rivets,
 Blind Rivet Nuts and Blind Rivet Bolts
- ⁸ Miscellaneous Tools

BZ 2
Hand Tool for Blind Rivets
with opening spring




Good Ergonomics, Brilliant Transformation

	2,4	3,0	3,2	4,0	4,8	5,0	6,0	6,4	8,0
A	Alumini	um							
\dagger		Steel							
V		Stainles	s steel						
		Copper	alloys						
	0,56	6 kg	STROK	E 8 mm	□ B	Blister	Incl. 4	nosepied	es
	Spec	ial nosep	oieces	page1	38				

No. 310.002.000.000

BZ 44 Hand Tool for Blind Rivets with opening spring



Classic Tool - Robust and Reliable

	2,4	3,0	3,2	4,0	4,8	5,0	6,0	6,4	8,0
A	optional	Alumini	um						
\dagger		Steel							
U		Stainles	s steel						
		Copper	alloys						
	0,63	3 kg	STROK	E 9,5mm	☐ Bli	ister	Incl. 3	nosepied	es
	Spe	cial nose	pieces	▶ page′	138				

No. 310.044.000.000



1



BZ 70

Lever Tool

NEW + OPTIMIZED Available from ab September 2011

3,2 2,4 3,0 4,0 4,8 5,0 6,0 8,0 6,4 Aluminium STROKE 14,5mm plastic case Incl. 4 nosepieces 1,5 kg max. mandrel-ø 3,2 mm Special nosepieces on request

No. 310.070.000.000

ø 45

Illustration similar to original product

NEW + OPTIMIZED Available from ab September 2011

2,4 3,0 3,2 4,0 4,8 5,0 6,0 6,4 8,0 1,65 kg STROKE14,5mm plasic case Incl. 5 nosepieces max.mandrel-ø 4,0 mm Special nosepieces on request

No. 310.072.000.000


BZ 72 Lever Tool




Illustration similar to original product

Manual handling of high strength rivets on request.

BZ 58 Sheare Tool



No. 310.058.000.000



VNG 255

Hand Tool with Assortment





	М3	M4	M5	М6	M8	M10	M12	
		Alumini	um					
		Steel						
		Stainles	s steel					
44		Steel						
0,9 l	кg	pla:	stic case		case si	ze 325	x 250 x 5	50 mm
content					assortn	nent		
• each w	ith 1 pied	ce conversa	ation kit fo	r blind	• 25 pie	ces each	blind riv	et nuts
rivet nu	ts M4, N	И5, M6;			Univer	sal M4, N	И 5;	
• each w	/ith 1 pi	ece threa	ded slee	ve for	• 50 pied	es blind r	ivet nuts	
blind ri	vet bolt	s M4, M5,			Univer	sal M6;		
• each w	ith 1 pi	ece jaw w	vrench		• 25 pie	ces each	n blind riv	et bolts
AF 22,	AF 24,				M4x20	10 and I	M5x2010	
• 1 piece	hex hea	d wrench	AF 6					

No. 310.255.000.000

Possible positions to work










VNG 371 Lever tool



Illustration similar to original product

NEW + OPTIMIZED Available from ab September 2011





- each with 1 piece threaded sleeve for blind rivet bolts M5 M8
- each with 1 piece jaw wrench AF 10, AF 14,
- 1 piece hex head wrench AF 6

No. **310.371.000.000**



VNG 612 Hand Tool





No. 310.612.000.000





Available from September 2011

VNG 152

Hand Tool


with hydaulic assistance





No. 310.152.000.000

Multi 1
Hand Tool for Blind Rivets, Blind Rivet Nuts and Blind Rivet Bolts




	2,4	3,0	3,2	4,0	4,8	5,0	6,0	6,4
А	Alumini	um						
₩		Steel						
		Stainles	s steel					
		Copper	allovs					

	M3	M4	M5	M6	M8	M10	M12	
	Alumini	um						
Ш	Steel							
		Steel						
•								
	plastic	case		case	size 3	60 x 185	x 50 mm	
k	0,56 l	кg		СО	ntinuou	s pivota	ble abou	t 360°
Co	ontent							

- each with 1 nosepiece for blind rivets 2,4; 3,0/3,2mm; 4,0 mm; 4,8/5,0mm
- each with 1 piece conversation kit for blind rivet nuts M3-M6
- each with 1 piece threaded sleeve for blind rivet bolts M4-M6,
- each with 1 piece jaw wrench AF 15/19, AF21/17.AF5/8

No. 310.100.000.000

Multi 5 Lever Tool for Blind Rivets, Blind Rivet Nuts and Blind Rivet Bolts



	2,4	3,0	3,2	4,0	4,8	5,0	6,0	6,4
Α		Alumini	um					
₩		Steel						
Ü		Stainles	s steel					
		Copper	alloys					
						1		l
					•			
	M3	M4	M5	M6	M8	M10	M12	
	M3	M4 Alumini		М6	M8	M10	M12	
	M3			M6	M8	M10	M12	
	M3	Alumini		M6	M8	M10	M12	
	M3	Alumini		M6	M8	M10	M12	

Content

1,9 kg

• each with 1 nosepiece for blind rivets 3,0/3,2mm; 4,0mm; 4,8/5,0mm; 6,0mm; 6,4mm

fold-away handle bars

- each with 1 piececonversation kit for blind rivet nuts M4-M10
- each with 1 piece threaded sleeve for blind rivet bolts M4-M8,
- each with 1 piece jaw wrench AF 15/19, AF 21/17. AF 5/8



VNG 150 is now MULTI 151.

Besides its outstanding positive properties in setting blind rivet nuts, this tool is able to operate blind rivets as well.

	2,4	3,0	3,2	4,0	4,8	5,0	6,0	6,4
A		Alumini	ım					
╽╫		Steel						
		Stainles	s steel					
		Copper	alloys					

М3	M4	M5	M6	M8	M10	M12	
Aluminiu	ım						
Steel							
 Stainles	s steel						
	0						
	Steel						
plasti	ic case		C	ase size	290 x 1	95 x 54 r	nm
0,6 k	g		Î	with hy	draulic c	ompone	nt

Content

each with 1 nosepiece for blind rivets 3,0/3,2mm; 4,0mm; 4,8/5,0mm; 6,0mm; 6,4mm each with 1 piece conversation kit for blind rivet nuts M3-M8

each with 1 piece conversation kit for blind rivet bolts M4-M8,

No. 310.151.000.000

Length 360 mm

Multi 151

Hand Tool for Blind Rivet Nuts, **Blind Rivet Bolts and Blind Rivets** with hydaulic assistance



8



Rivet Cracker





Do not try to open rivets by screwing or carving any longer. This tool "bites" off the rivet heads after removing the mandrel without damaging the component.

	2,4	3,0	3,2	4,0	4,8	5,0	6,0	6,4
ñ	Alumini	um						
Ť	Steel							
U								
	840		845	110	140	1110	1110	
	M3	M4	M5	M6	M8	M10	M12	
	Alumini		IVIO	OIVI	IVIO	IVITU	IVITZ	
	_		CIVIS	IVIO	IVIO	IVITO	IVITZ	

Cutting hardness: 58 Rockwell

	2,4	3,0	3,2	4,0	4,8	5,0	6,0	6,4
n								
Ť	Alumini	um						
V								
			145					
	M3	M4	M5	M6	M8	M10	M12	
	Alumini	ım						
Length 200 mm Cutting hardness: 58 Rockwell								

Removal of Rivet Heads Easy Release of Blind Rivets and Blind Rivet Nuts



Rivet Cracker -small-



Setting of Industrial Rivets

There are many different possibilities to handle industrial

· manual deformation by using riviting dies







Set for rivet head pulling No. 18.509.000.001

DIN 6435 made from hexagon steel savety tempering, shaft equally hardened; delivered in plastic holder

5 rivet-dies 2,0 - 3,0 - 4,0 - 5,0 and 6,0 mm \varnothing







Compressing the shaft / pre-forming of the closing head

Final forming with rivet head setting-tool





by rivet head puller

Axial Hand Tool

Setting of Axial Clamps




Fix our axial clamps with this compatible tool - quick and safe.

Joining the component Positioning and fixing

FOR AXIAL CLAMP RINGS

outside-ø	No.
15,0 mm	18.509.000.150
18,0 mm	18.509.000.180
25,0 mm	18.509.000.250





Outside-ø	No.
12,0 mm	18.509.000.120
16,0 mm	18.509.000.160
20,0 mm	18.509.000.200
27,0 mm	18.509.000.270
30,0 mm	18.509.000.300

FOR AXIAL CLAMP CAPS







The experience of decades and continuous improvement made the successful HONSEL/VVG tools of the BZ- and VNG-series become reliable utilities for industrial volume productions as well as for specialist shops and handcraft.

The sturdy construction and complete equipment with all necessary conversation parts plus comprehensive accessories up to process controled automation systems leave nothing to be desired.

Latest development "designed by Honsel" is the modern type battery tool "Rivdom" on ▶ page 129.

- Pneumatic-Hydraulic Tools for Blind Rivets (BZ-Series)
- Battery Tool for Blind Rivets (Rivdom)
 - Pneumatic-Hydraulic tools for Blind Rivet Nuts and Blind Rivet Bolts (VNG-Series)



BZ 103 A

Pneumatic-Hydraulic Tool with permanent and intervall mandrel exhaustion



Thousandfold Approved – the latest version of the standard tool for reliable processing of blind rivets







2,4	3,0	3,2	4,0	4,8	5,0	6,0	6,4	8,0
Alumini	um							
	Steel							
	Stainles	s steel						
	Copper	alloys						
Content • 4 nosepieces			pressure:5-7 bar max.mandrel-ø: 3,8 mm					
1 set of clamping jaws				stroke :18 mm		air consumption: 2,4 L		
1 bottle hydraulic oil /				noise:		working power		
incl. re-fill unit				< 75 dB	(A)(68,32)	at 7 bar : 11700		00 N
 2 mandrel collectors 			1,8 kg		hose connection:			
special accessory ▶ page 138				C	E	G 1/4 inside, install on left or right side		

No. 320.103.000.000

For useful air pressure accessory take a look on ▶ page 128.

For an optimized processing of our structural FERO®-BULB blind rivets on pages 40+41 the pneumatic-hydraulic tool **BZ 133A** is available on request.

This tool offers a **perfect adjustment** of the stroke (18 mm) and the working power (24.000 N) combined with adapted clamping jaws to the grooves of the mandrel. This guarantees powerful handling with reduced abrasion.





The Strong Tool - even suitable for hight strength blind rivets



BZ 123 A

Pneumatic-Hydraulic Tool with permanent and intervall mandrel exhaustion





ø 110 mm

2,4	3,0	3,2	4,0	4,8	5,0	6,0	6,4	8,0
	Aluminiu			um				
	Steel Stainles							
				s steel				
			Copper	alloys				
Content • 4 nosepieces			pressure:5-7 bar max.mandrel-ø: 4,8 mm					
1 set of clamping jaws				stroke: 25 mm		air consumption: 3,5 L		
1 bottle hydraulic oil / incl. re-fill unit			noise: < 75 dB	(A)(68,32)	working power at 7 bar: 18700N			
2 mandrel collectors				2	34 kg	hose connection:		
special accessory ▶ page 138			C	E	G 1/4 inside, installat on left or right side			

No. 320.123.000.000






2,4	3,0	3,2	4,0	4,8	5,0	6,0	6,4	8,0
Alumini	um							
	Steel							
	Stainles	s steel						
	Copper	alloys						
2,1 kg		hight 365 mm		stroke 18 mm		max. mandrel-ø 3,8 mm		
tensile force at		noise		pressure		air consumption		
7 bar 11700 N		< 75 dB(A)(68,32)		5-7 bar		2,4 litre		
content			1 set 1 mar			1 bottle	hydrauli	c oil
hose co	onnectio	n ø1	/4" inside	e, installa	tion left	or right s	ide	
	balancer mandrel conduction hose mandrel conduction adapter mandrel conduction box							

The new option for axial handling with the approved pneumatichydraulic tolls of the Honsel/VVG BZ-series.

No. 320.102.000.000/5

Rivet Angle Head for BZ Blind Rivet Tools







Rivet angle heads for difficult to reach positions are available on request.

No. 321.102.000.600

For optimized handling we suggest the following accessory for all HONSEL-/VVG-Tools:







No.:

No.:



321.101.000.058 1-1





Additional connections for compressed-air available on request

• Pivoting threaded pipe angle (3), stainless steel 321.121.000.053 2-1 No.: • Valve extension (1) 321.121.000.052 1-1 No.: 321.000.141.360 1-1 • Pressure reducing valve (2) No.: • Pivoting threaded pipe angle (3) including fabric tube with 321.121.000.053 3-1 1/4" external thread and hose coupling (4) No.: • Screw-in hose connector -set- G 1/4" 6 mm (5) 321.121.000.057 1-1 No.:

For undisturbed operation Honsel-/VVG-Tools need a continous, periodic maintenance. Make sure that for BZ-Tools clean and dry, for VNG-Tools clean and lubricated compressed air is available. We advise the use of filter pressure reducers (BZ) or compressed-air service units (VNG).

• Compressed-air service unit (Pressure reducer/

• Screw-in hose connector -set- G 1/4" 9 mm (6)

• Pivoting threaded pipe angle (3), aluminium

320 847 000 000 oil fog lubricator (VNG-Serie) No.: 320 848 000 000 Pressure reducer (BZ-Series) No.:

Additional accessory as for example balancer, spiral coiled tubes or compressors are available on request. Spare parts, special nosepieces or useful special attachments are shown in ▶ chapter 10, pages 135 et sqq.



RIVDOM **Battery Tool for Blind Rivets**

