

# ISO APPROVED WHISTLE DX0276M

DX0276M

**TYPE** EN ISO 12402-B PEALESS WHISTLE


## USES

Audible Distress signal whistle accepted by USCG/SOLAS/MED/ISO for lifejackets and immersion suits.

## FEATURES

Pealess whistle clip and lanyard  
Meets EN ISO 12402-8 and accepted for USCG/SOLAS/MED/ISO  
International orange color  
Weights 12 grams  
Individually packed in a plastic bag

## SPECIFICATIONS

ITEM NO.	DX0276M	
<b>USE</b>	COMMERCIAL / GENERAL	
<b>ATTACHMENT TYPE</b>	Black Lanyard and clip	
<b>PERFORMANCE</b>	EN ISO 12402-8:2006/A1:2001(D)	
<b>ACCEPTED</b>	USCG/SOLAS/MED	
<b>LENGTH</b>	2.75" (70mm)	
<b>WIDTH</b>	0.81" (21mm)	
<b>HEIGHT</b>	0.75" (19mm)	
<b>WEIGHT</b>	12 grams	
<b>COMPOSITION</b>	PLASTIC NON-METALIC	
<b>MOVING PARTS</b>	NONE	
<b>MIN. REQUIRED dB</b>	100 dB	
<b>PACK PER BOX</b>	100 pcs and individually bagged	

## APPROVAL/COMPLIANCE

Tested by DGUV TEST in Germany to EN ISO 12402-8:2006/A1:2011 (D)



---DATREX---