

Ultimate-1500

4GE+2WIFI6 XPON ONU



Product Overview

The Ultimate-1500 is a high-performance **Wi-Fi 6** XPON VoIP Gateway ONT designed to deliver ultra-fast, reliable connectivity. It supports dual-band wireless standards including IEEE 802.11a/b/g/n/ac/ax over both 2.4GHz and 5GHz frequencies, offering combined wireless speeds of up to 1500 Mbps.

Engineered for high reliability and seamless performance, the Ultimate-1500 ensures robust Quality of Service (QoS), simplified network management, and flexible scalability. It fully complies with ITU-T and IEEE technical standards and is compatible with a wide range of third-party OLTs, making it an ideal solution for modern FTTH deployments.



Functional Feature

🌐 Industry Standards Compliance

- Adheres to IEEE 802.3ah and ITU-T G.984 standards, ensuring seamless integration and reliable performance in GPON networks.

🔧 Intelligent Network Management

- Supports automatic ONU discovery, link status monitoring, and remote firmware upgrades for simplified deployment and maintenance.
- Integrated EMS management via SNMP for centralized, efficient network supervision.
- Enables remote access control through intuitive Web GUI and Telnet interfaces.
- Power failure alarm functionality for rapid fault identification and resolution.

🔒 Robust Security Features

- Implements AES encryption/decryption to ensure secure data transmission.
- Built-in firewall with MAC address and URL filtering for enhanced network protection.
- Supports multiple ONU authentication methods including Serial Number (SN) and LOID + Password.

📶 Triple-Play Service Delivery

- Provides single-fiber access supporting Internet, VoIP, and Wi-Fi services.
- Equipped with Wi-Fi 6 technology, supporting 802.11a/b/g/n/ac/ax standards for faster speeds, greater capacity, and improved wireless efficiency.
- Utilizes Dynamic Bandwidth Allocation (DBA) to optimize bandwidth distribution based on real-time demand.


⚙️ Advanced Port & Traffic Control

- Offers port-based VLAN configuration, rate limiting, and bandwidth control for precise traffic management.
- Supports MAC address learning with configurable limits to enhance security and performance.
- Comprehensive VLAN modes including transparent, tagged, translation, and trunk configurations.

📺 Multicast & Broadcast Efficiency

- Supports IGMP in transparent, snooping, and proxy modes for efficient multicast traffic handling.
- Equipped with broadcast storm control to maintain network stability and prevent congestion.





Product Interface and LED



Indicator		Description
PWR	Power status	On: The ONT is power on;
		Off: The ONT is Power off;
PON	ONT Register	On: Success to register to OLT;
		Blinking: In process of registering to OLT;
		Off: Failed to register to OLT or no normal optical signal input;
LOS	PON optical signals	On: Optical power lower than receiver sensitivity;
		Off: Optical in normal;
LAN1-4	LAN port status	On: Ethernet connection is normal;
		Blinking: Data is being transmitted through the Ethernet port;
		Off: Ethernet connection is not set up;
INT	Internet status indicator	On: The routed WAN Internet access service is normal.
		Off: The routed WAN Internet access service is abnormal.

Product Specification

Mechanics	
Dimensions	170mm*120mm*41mm
Weight	About 300g

Hardware		
User Port (LAN)		RJ-45 connector
		4*10/100/1000Mbps adaptive Ethernet port
		Full/half duplex
		Auto MDI/MDI-X
Indicators		PWR / PON / LOS / GE / FE / INT / TEL / WIFI
PON Port	PON Mode	EPON : 1000BASE-PX20+ symmetric
		GPON : FSAN G.984.2 standard, Class B+
	PON Rate	EPON : 1.25Gbps downstream/upstream
		GPON : 2.488Gbps/1.244Gbps downstream/upstream
	Wavelength	Transmit: 1310nm Receiver: 1490nm
	Receiving sensitivity	EPON : -27dBm GPON : -28dBm
	Saturated power	EPON : -3dBm GPON : -8dBm
Transmitting power		EPON:0~4dBm GPON : 0.5~5dBm

WIFI	
IEEE802.11b/g/n/ax(2.4G)	
IEEE802.11a/n/ac/ax(5G)	
2.4G: 40Mhz bandwidth maximum rate 300Mbps 5G : 80Mhz bandwidth maximum rate 1201Mbps Total wireless rate is 1500Mbps	
2.4G EIRP:24dBm / 5 G EIRP:22dBm	

Environment	
Working temperature	0 to 40° C
Operating humidity	10% ~ 90% (Non-condensing)

Power	
External 12VDC/1A power supply adapter	
Power Consumption	<18W

Copyright © USU Telecom India Private Limited. All rights reserved.

Without the prior written consent of USU, any reproduction, excerpting, backup, modification, translation or any other form of commercial use of this document or any portion of this document, and in any form or by any means, to transmit the document are prohibited.