





- gauges and two 7,000 lbs. rolling jacks Drive-through ramps
  - 3-phase motor
- Runway lighting

CD014N101VDL/DD\*

- Internal airline kit

SPECIFICATIONS	CRO14N101YBL/RD* CRO14N102YBL/RD*
Capacity	14,000 lbs.
Maximum Wheelbase	182 1/2" / Standard 215" / Extra Length
Maximum Rise	78 3/4"
Overall Length	20' 13" / Standard 23' 10" / Extra Length
Overall Width	140 1/2"
Width Inside Columns	116 1/4""
Length Between Columns	194 3/4" / Standard 227 3/4" / Extra Length
Overall Height	109 1/16"
Runway Width	20"
Runway Height	7"
Width Between Runways	43"
Rise Time	79 Seconds
Motor	2HP
Minimum Bay Size	15' x 26'/ Standard 15' x 28' / Extra Length

**FEATURES:** 

- 78 3/4" rise height
- · Heavy duty high-performance cable and sheaves system
- Patented articulating shaft design ensures even roller loading.
- · Easy to use single point lift operation with air operated lock release
- Multi-position lock components allow lift to be level at any lock position
- · Self-chocking 41" louvered approach ramps with protective rollers
- Durable powder coat finish



ALI GOLD CERTIFIED

Forward Lift CR014 meets the highest industry safety and performance standards. Your assurance of certification is the gold ALI/ETL certified label.

Phone: 800.423.1722

Fax: 812.273.7329

RWARDIET www.forwardlift.com 📑 🞯 💟 🕒 📴

996 Industrial Drive Madison, IN 47250

Lit# Forward CR014 CUTSHEET.2024.04 ©2024 Vehicle Service Group® All rights reserved. Unless otherwise indicated, Forward Lift, Vehicle Service Group®, Dover and all other trademarks are property of Dover Corporation and its affiliates. \*Lifts available in blue (BL) and red (RD)

Specifications subject to change without notice or liability.