

# CROA14

ALIGNMENT RUNWAY LIFT 14,000 lbs. Capacity



Two runway lengths configured for vehicles with longer wheelbases.

Service vehicles with wheelbases up to 215"

### Alignment-ready lift includes:

Two 7,000 lbs. rolling jacks, two carbon steel front turning radius, internal airlines, rear wheel slip plates, FLR (filter, lubricator, regulator)

#### **FEATURES:**

- Two runway lengths designed for longer vehicle wheelbases
- Tall column design provides a 80 3/4" rise height
- Adjustable front radius gauge positioning and long slip plates allow for a large four wheel alignment wheelbase range
- · Patented articulating shaft design ensures even roller loading
- Heavy duty high-performance cable and sheaves system
- Easy to use single point lift operation with air operated lock release
- Multi-position lock components allow lift to be level at any lock position
- Self-chocking approach ramps with louvers for traction and protective rollers
- Durable powder coat finish





#### ALI GOLD CERTIFIED

Forward Lift CROA14 meets the highest industry safety and performance standards. Your assurance of certification is the gold ALI/ETL certified label.



996 Industrial Drive Madison, IN 47250

Phone: 800.423.1722





Lit# Forward CROA14 CUTSHEET.2024.04 ©2024 Vehicle Service Group® All rights reserved.





Unless otherwise indicated, Forward Lift, Vehicle Service Group®, Dover and all other trademarks are property of Dover Corporation and its affiliates,

Fax: 812.273.7329

\*Lifts available in blue (BL) and red (RD) Specifications subject to change without notice or liability.

**LIFT OPTIONS:** 

· Drive-through ramps • LED runway light kit

## SPECIFICATIONS

CROA14N201YBL/RD\*

| or zon rozmono                               | CROA14N202YBL/RD*                               |
|--|---|
| Capacity                                     | 14,000 lbs.                                     |
| Maximum Wheelbase                            | 182 1/2" / Standard<br>215" / Extra Length      |
| Max. Two Wheel Alignment                     | 166 1/4" / Standard<br>199 1/4" / Extra Length  |
| Max. Four Wheel Alignment                    | 157" / Standard<br>172 1/4" / Extra Length      |
| Min. Four Wheel Alignment                    | 88"   |
| Maximum Rise                                 | 80 3/4"   |
| Overall Length                               | 21' 1" / Standard<br>23' 10" / Extra Length     |
| Overall Width                                | 11' 8 1/2"                                      |
| Width Inside Columns                         | 116 1/4""                                       |
| Length Between Columns                       | 194 3/4" / Standard<br>227 3/4" / Extra Length  |
| Column Height                                | 9' 1 1/8"                                       |
| Runway Width                                 | 20"   |
| Runway Height                                | 9"  |
| Width Between Runways                        | 43"   |
| Front of Runway to<br>Center of Radius Gauge | 22 3/4" to 52 3/4"                              |
| Rise Time                                    | 79 Seconds                                      |
| Motor  | 2HP   |
| Minimum Bay Size                             | 15' x 26'/ Standard<br>15' x 28' / Extra Length |
|  |   |