


# SYMMETRICAL TWO POST LIFT

10,000 lbs. Capacity



## **Spot-Rite**<sup>™</sup>3-Stage **Front Arm Design**

Accommodates vehicle spotting both symmetrically and asymmetrically. Position the vehicle doors in front of or behind the lift columns to prevent door damage and allow easy technician access!



Asymmetric Vehicle Placement

Symmetric Vehicle Placement



### T100295 Extended Height Kit

The column extension kit adds an additional 2 feet to the top of the standard lift. Kit includes an extended length hose, return line, and cables. Existing hardware included with the lift is used to attach the extensions.

For use on the current 500 series model I10 Forward Two Post Lifts.





### ALI GOLD CERTIFIED

Forward Lift I10 meets the highest industry safety and performance standards. Your assurance of certification is the gold ALI/ETL certified label.



996 Industrial Drive Madison, IN 47250

Phone: 800.423.1722 Fax: 812.273.7329






Lit# Forward I10 CUTSHEET.2024.04 ©2024 Vehicle Service Group® All rights reserved.





Unless otherwise indicated, Forward Lift, Vehicle Service Group®, Dover and all other trademarks are property of Dover Corporation and its affiliates.



\*Lifts available in blue (BL) and red (RD) Specifications subject to change without notice or liability.

**FEATURES:** 

Symmetrical column design

Spot-Rite™ 3-stage front arm design - spot vehicles asymmetrically or symmetrically

- Top mounted Direct-Pull lifting technology
- Cylinder rod concealed in carriage
- Adjustable width options
- Optional extended height kit adds 2'
- Single point lock release
- Powder coated finish
- Includes adapter storage bracket
- **ALI Certified**

**INCLUDES LOW-PROFILE THREADED ADAPTERS AND (4 each) ADAPTER EXTENSIONS AT** 3.5" and 5"

### **SPECIFICATIONS** I10N500MBL/RD\*

Capacity	10,000 lbs.
Maximum Rise with 5" Extension	76 1/4"
Overall Height	11' 9"
Optional Extended Height	13' 9" with T100295 kit
Overall Width	10' 9" or optional 11' 5"
Drive-Thru	99" or optional 105"
Overhead Switch Height	137 1/8"
Front Arm Reach (Min/Max)	23" / 44 3/8"
Rear Arm Reach (Min/Max)	36" / 58"
Minimum Adapter Height	3 3/4" without extension
Maximum Adapter Height	8 3/4" with 5" extension
Width Inside Columns	109" Standard 115" Optional
Ceiling Height Required	12'
Voltage/Amps	208-230V, 17 amps
Motor/Phase	1PH / 2HP / 60Hz