



RFL25 HEAVY DUTY FORKLIFT SERVICE LIFT

25,000 lbs. CAPACITY / DRIVE ON FOUR POST LIFT

RAISE YOUR FORKLIFT TO NEW HEIGHTS

Service a variety of vehicle classes and forklifts that fall into this heavy duty group.

Increase both safety and efficiency for general maintenance and inspections with this runway lift.



MODEL RFL25
Lift Colors are Blue and Red **4 POST LIFT**

STANDARD	RFL2500
Lift Capacity	25,000 lbs.
Rise*	68 3/4"
Width Overall	12' 4 13/16"
Length Overall	22' 5"
Max. Wheelbase	175"
Inside of columns	132"
Between columns	177"
Column height	7' 3/4"
Runway Width	24"
Runway height	8 3/8"
Width between runways	13" Min / 42" Max
Min Bay Size	16' x 26'
Motor / Voltage*	4 HP / 208 - 230V
Time of Full Rise	95 seconds

*Rise measures floor to top of runway at full stroke.

LIFT COLORS ARE BLUE AND RED

♦ 3-Phase power available

FEATURES:

- Low profile ramps allow for easy on / off operation or add an optional ramp kit for drive-through ease
- Folding ramps with rear chocks that automatically engage when lift is raised
- Dual locking system with a single point air lock releases four column locks with the push of a single button
- Air connection with filter regulator and lubricator

OPTIONAL ACCESSORIES

TECH LIGHT™ LED Runway Lighting Kit / Four light wands for effective runway lighting

Oil Drain Pans include splash guard, drain valve and dust cap

Internal Airline Kit

Removable Work Steps for lifts with slots on sides of runways

Rotary Lift

2700 Lanier Drive / Madison, IN 47250, USA

rotarylif.com     

Lit# Rotary RFL25 Cutsheet.2021.11

©2021 VEHICLE SERVICE GROUP™, Printed in U.S.A., All Rights Reserved. Unless otherwise indicated, ROTARY, VEHICLE SERVICE GROUP™, DOVER and all other trademarks are property of Dover Corporation and its affiliates.

North / South America Information

Sales: 800.445.5438
insidesales@vsgdover.com

Tech. Support: 800.445.5438
technicalsupport@rotarylif.com

Government Sales: 800.445.5438 X5655

For additional information: rotarylif.com/Government-Purchasing-Assistance/

Product specifications, part numbers, images and component descriptions are subject to change without notice or liability.

Global Contact Information

USA: 1.812.273.1622

Canada: 1.905.812.9920

Latin America / Caribbean: 1.812.273.1622

Brazil: +55.11.4534.1995

