

Cement Wire Wound Resistors				Non-inductive 25W series			
Part number	Resistance	Power Handling	Tolerance	Length (±1.5mm)	Width (±1.5mm)	Lead Diameter	Lead Length
ENWR25-05-1.0/PB	1.0Ω	25W	5%	60 mm	14 mm	0.8 mm	35 mm
ENWR25-05-1.5/PB	1.5Ω	25W	5%	60 mm	14 mm	0.8 mm	35 mm
ENWR25-05-2.2/PB	2.2Ω	25W	5%	60 mm	14 mm	0.8 mm	35 mm
ENWR25-05-3.3/PB	3.3Ω	25W	5%	60 mm	14 mm	0.8 mm	35 mm
ENWR25-05-3.9/PB	3.9Ω	25W	5%	60 mm	14 mm	0.8 mm	35 mm
ENWR25-05-4.7/PB	4.7Ω	25W	5%	60 mm	14 mm	0.8 mm	35 mm
ENWR25-05-5.6/PB	5.6Ω	25W	5%	60 mm	14 mm	0.8 mm	35 mm
ENWR25-05-6.8/PB	6.8Ω	25W	5%	60 mm	14 mm	0.8 mm	35 mm
ENWR25-05-8.2/PB	8.2Ω	25W	5%	60 mm	14 mm	0.8 mm	35 mm
ENWR25-05-10.0/PB	10.0Ω	25W	5%	60 mm	14 mm	0.8 mm	35 mm
ENWR25-05-12.0/PB	12.0Ω	25W	5%	60 mm	14 mm	0.8 mm	35 mm
ENWR25-05-15.0/PB	15.0Ω	25W	5%	60 mm	14 mm	0.8 mm	35 mm
ENWR25-05-18.0/PB	18.0Ω	25W	5%	60 mm	14 mm	0.8 mm	35 mm
ENWR25-05-22.0/PB	22.0Ω	25W	5%	60 mm	14 mm	0.8 mm	35 mm
ENWR25-05-33.0/PB	33.0Ω	25W	5%	60 mm	14 mm	0.8 mm	35 mm