

IXQ - Laminated Steel Core Coils

Bobbin	ELC55	ELC56	Winding
SIZE (mm)			
12AWG	Up to 2.3 mH, 400W	Up to 12 mH, 500W	Coil Winding : E1
14AWG	Up to 2.5 mH, 400W	Up to 12 mH, 500W	Coil Winding : E2
15AWG	Up to 4.0 mH, 400W	Up to 20 mH, 500W	Coil Winding : E3
16AWG	Up to 6.2 mH, 400W	Up to 22 mH, 500W	Coil Winding : E4
17AWG	Up to 6.8 mH, 350W	Up to 22 mH, 400W	Coil Winding : E5
18AWG	Up to 18 mH, 300W	Up to 50 mH, 300W	Coil Winding : E6
19AWG	Up to 33 mH, 250/200/150W	—————	
20AWG	Up to 45 mH, 150W	—————	
22AWG	Up to 45 mH, 150W	—————	
Model No.:	<p style="text-align: center;">Bobbin Number AWG Value:1.0mH</p> <p style="text-align: center;">↑ ↑ ↑</p> <p style="text-align: center;">ELC55-18-1000</p>	<p style="text-align: center;">Bobbin Number AWG Value:5.0mH</p> <p style="text-align: center;">↑ ↑ ↑</p> <p style="text-align: center;">ELC56-16-5000</p>	<p style="text-align: center;">Coil Winding : E9</p>
Lead Length:	Lead Length 6.5cm with 3cm tinned (For your reference)		