

Part number	Capacitance	Dissipation Factor	Outside Diameter (±0.5mm)	Cap Length (±1mm)	Lead Diameter	Lead Length
SCAP40-03-1.00	1.00 μ F	0.0001	13.00 mm	23.00 mm	0.80 mm	25.00 mm
SCAP40-03-1.10	1.10 μ F	0.0001	14.00 mm	23.00 mm	0.80 mm	25.00 mm
SCAP40-03-1.20	1.20 μ F	0.0001	15.00 mm	23.00 mm	0.80 mm	25.00 mm
SCAP40-03-1.30	1.30 μ F	0.0001	13.00 mm	25.00 mm	0.80 mm	25.00 mm
SCAP40-03-1.50	1.50 μ F	0.0001	14.00 mm	25.00 mm	0.80 mm	25.00 mm
SCAP40-03-1.60	1.60 μ F	0.0001	15.00 mm	25.00 mm	0.80 mm	25.00 mm
SCAP40-03-1.80	1.80 μ F	0.0001	16.00 mm	25.00 mm	0.80 mm	25.00 mm
SCAP40-03-2.00	2.00 μ F	0.0001	17.00 mm	25.00 mm	0.80 mm	25.00 mm
SCAP40-03-2.20	2.20 μ F	0.0001	16.00 mm	28.00 mm	0.80 mm	30.00 mm
SCAP40-03-2.40	2.40 μ F	0.0001	17.00 mm	28.00 mm	0.80 mm	30.00 mm
SCAP40-03-2.50	2.50 μ F	0.0001	17.00 mm	28.00 mm	0.80 mm	30.00 mm
SCAP40-03-2.70	2.70 μ F	0.0001	18.00 mm	28.00 mm	0.80 mm	30.00 mm
SCAP40-03-3.00	3.00 μ F	0.0001	19.00 mm	28.00 mm	0.80 mm	30.00 mm
SCAP40-03-3.30	3.30 μ F	0.0002	20.00 mm	28.00 mm	0.80 mm	35.00 mm
SCAP40-03-3.50	3.50 μ F	0.0002	17.00 mm	33.00 mm	0.80 mm	35.00 mm
SCAP40-03-3.60	3.60 μ F	0.0002	17.00 mm	33.00 mm	0.80 mm	35.00 mm
SCAP40-03-3.90	3.90 μ F	0.0002	18.00 mm	33.00 mm	0.80 mm	35.00 mm
SCAP40-03-4.00	4.00 μ F	0.0002	18.00 mm	33.00 mm	0.80 mm	35.00 mm
SCAP40-03-4.30	4.30 μ F	0.0002	19.00 mm	33.00 mm	0.80 mm	35.00 mm
SCAP40-03-4.50	4.50 μ F	0.0002	19.00 mm	33.00 mm	0.80 mm	35.00 mm
SCAP40-03-4.70	4.70 μ F	0.0002	19.00 mm	33.00 mm	1.00 mm	35.00 mm
SCAP40-03-5.00	5.00 μ F	0.0002	21.00 mm	33.00 mm	1.00 mm	35.00 mm
SCAP40-03-5.10	5.10 μ F	0.0002	21.00 mm	33.00 mm	1.00 mm	35.00 mm
SCAP40-03-5.60	5.60 μ F	0.0002	22.00 mm	33.00 mm	1.00 mm	35.00 mm
SCAP40-03-6.00	6.00 μ F	0.0002	23.00 mm	33.00 mm	1.00 mm	35.00 mm
SCAP40-03-6.20	6.20 μ F	0.0002	23.00 mm	33.00 mm	1.00 mm	35.00 mm

Part number	Capacitance	Dissipation Factor	Outside Diameter ($\pm 0.5\text{mm}$)	Cap Length ($\pm 1\text{mm}$)	Lead Diameter	Lead Length
SCAP40-03-6.80	6.80 μF	0.0003	24.00 mm	33.00 mm	1.00 mm	35.00 mm
SCAP40-03-7.00	7.00 μF	0.0003	25.00 mm	33.00 mm	1.00 mm	35.00 mm
SCAP40-03-7.50	7.50 μF	0.0003	26.00 mm	33.00 mm	1.00 mm	35.00 mm
SCAP40-03-8.00	8.00 μF	0.0003	24.00 mm	38.00 mm	1.00 mm	40.00 mm
SCAP40-03-8.20	8.20 μF	0.0003	24.00 mm	38.00 mm	1.00 mm	40.00 mm
SCAP40-03-9.10	9.10 μF	0.0003	25.00 mm	38.00 mm	1.00 mm	40.00 mm
SCAP40-03-10.0	10.00 μF	0.0003	26.00 mm	38.00 mm	1.00 mm	40.00 mm
SCAP40-03-11.0	11.00 μF	0.0003	27.00 mm	38.00 mm	1.00 mm	40.00 mm
SCAP40-03-12.0	12.00 μF	0.0004	28.00 mm	38.00 mm	1.00 mm	40.00 mm
SCAP40-03-13.0	13.00 μF	0.0004	27.00 mm	45.00 mm	1.00 mm	40.00 mm
SCAP40-03-14.0	14.00 μF	0.0004	27.00 mm	45.00 mm	1.00 mm	40.00 mm
SCAP40-03-15.0	15.00 μF	0.0004	28.00 mm	45.00 mm	1.00 mm	45.00 mm
SCAP40-03-16.0	16.00 μF	0.0004	29.00 mm	45.00 mm	1.00 mm	45.00 mm
SCAP40-03-18.0	18.00 μF	0.0004	31.00 mm	45.00 mm	1.00 mm	45.00 mm
SCAP40-03-20.0	20.00 μF	0.0004	32.00 mm	45.00 mm	1.20 mm	45.00 mm
SCAP40-03-22.0	22.00 μF	0.0005	34.00 mm	45.00 mm	1.20 mm	45.00 mm
SCAP40-03-24.0	24.00 μF	0.0005	32.00 mm	53.00 mm	1.20 mm	45.00 mm
SCAP40-03-27.0	27.00 μF	0.0005	34.00 mm	53.00 mm	1.20 mm	45.00 mm
SCAP40-03-30.0	30.00 μF	0.0006	36.00 mm	53.00 mm	1.20 mm	45.00 mm
SCAP40-03-33.0	33.00 μF	0.0006	38.00 mm	53.00 mm	1.20 mm	50.00 mm
SCAP40-03-36.0	36.00 μF	0.0007	39.00 mm	53.00 mm	1.20 mm	50.00 mm
SCAP40-03-39.0	39.00 μF	0.0007	38.00 mm	58.00 mm	1.60 mm	50.00 mm
SCAP40-03-41.0	41.00 μF	0.0008	39.00 mm	58.00 mm	1.60 mm	50.00 mm
SCAP40-03-43.0	43.00 μF	0.0008	40.00 mm	58.00 mm	1.60 mm	50.00 mm
SCAP40-03-45.0	45.00 μF	0.0008	41.00 mm	58.00 mm	1.60 mm	50.00 mm
SCAP40-03-47.0	47.00 μF	0.0008	42.00 mm	58.00 mm	1.60 mm	50.00 mm