

DJI PHANTOM Application Notes

Aircraft: All Models

MOUNTING: OPTION #1 TOP of DRONE

MOUNTING: The Drone Retriever can be mounted to the top center of the housing with Dual Lock removable fasteners. ADDITIONALLY you should use the releasable Ziptie to insure reliable attachment due to the curvature of the top center of the drone. The Ziptie should fit snugly around the body of the drone. DO NOT over tighten. Make sure it does not cover any downward vision system sensors.

- The ziptie should be inserted into the front or back of the Drone Retriever and slid through the plastic housing of the Drone Retriever along the bottom of the enclosure. **DO NOT PUT THE TIE WRAP OVER THE TOP OF THE DRONE RETRIEVER AS THIS WILL NOT ALLOW IT TO OPEN WHEN NEEDED.** Insure that the tail of the Ziptie does not interfere with the propellers.



MOUNTING: OPTION #2 Bottom of DRONE

CONFIGURING YOUR REMOTE:

- **DANGER:** If your drone has a **BOTTOM MOUNTED** vision system sensors you **MUST** Deactivate them when using the **DRONE RETRIEVE**.

MOUNTING: The Drone Retriever can be mounted to the Bottom of Drone with Dual Lock removable fasteners. **ADDITIONALLY** you should use the releasable Ziptie to insure reliable attachment in the event of a battery retention failure. The Ziptie should fit snugly around the body of the drone. **DO NOT** over tighten. Insure that the tail of the Ziptie does not interfere with the propellers

