

Cleaning Gray Tank Sensors

Copyright © 2018 – Dale Lee Sumner

Q: Do you have any suggestions regarding cleaning the sensors on the gray tank since there is no way to flush it out other than hydro-jet cleaning?

R: You can back-flood your gray tank via the sink in the bathroom - make sure the gray valve outside is closed, first. Then, turn on the "cold" tap and let the water run into the sink. You'll know when the gray tank is full when water flows up through the drain into the shower pan. Turn off the water, then pull the gray tank valve open and let the tank drain. Do this several times the first time you try to flush out the gray tank. You should also repeat the process whenever you dump your tanks. If your RV has two gray tanks, you'll have to do the same thing via your kitchen sink. (**Comment:** If the kitchen sink starts to back-up, its gray tank is full).

Concerning the sensors, you might want to try TankTechRx in your gray tank (as well as the black tank). It's made up of live bacteria rather than chemicals. So, if you use TankTechRx, don't use any other tank treatment or clean your sinks and shower with any type of chemical cleaner - they all kill the bacteria. My wife uses white vinegar for cleaning the sinks, shower, and toilet, just before we dump the tanks.

If you're not already here, the next time you are in Central Florida, I recommend you call the people at HoldingTankCleaning.com about cleaning both of your holding tanks. Their phone number is 1-855-RV-TANKS (788-2657). They also sell and ship the TankTechRx product anywhere in the US.

Hope this helps.

Dale

SUMDALUS-USA