

max. 3,500 kg/7,700 lbs



SH-3500-B

## Vacuum Lifting Device SH-3500-B

Threefold vacuum pump capacity compared with the previous standard SH-2500-UNI-B device, producing a significantly faster buildup of vacuum, also suitable for more porous elements. Complete automatic drive via integral petrol engine with electric starter.

Optional available: Wheelset SH-3500-RS, support feet SH-3500-AF and remote control SH-3500-FFS.

- With integral chain-box and load-securing chain.
- Suction and release operation via comfortable button-activation on the control console.
- Built-in operating hours counter.
- With fork sleeves for lifting forks for transportation and for laying.
- All available SH-suction plates are compatible with the SH-3500-B. (in connection with SPS-2500 an adapter is required)

Type	Description	Type of Drive Petrol Engine kW	Dead Weight kg (lbs)	Working Load Limit/WLL -600 mbar kg (lbs)	Order-Number
SH-3500-B	Basic device, without suction plate	3.6	177.4 (390)	3,500 (7,700)	52400041
SH-3500-B-FFS	Basic device, without suction plate. With remote control	3.6	180 (395)	3,500 (7,700)	52400047

### Accessories

Type	Description	Dead Weight kg (lbs)	Working Load Limit/WLL kg (lbs)	Order-Number
SH-3500-RS	Wheelset for SH-3500-B	10.6 (25)		42500256
SH-3500-AF	Support feet for SH-3500-B	12.8 (30)		42400579
SH-AD	Retrofit kit with Rotator	44.1 (95)		42500267
SH-TRA-3500 Spreader Bar	For multiple use of the suction plates single plates adjustable. Suction plate turnable by 90°. Distance between centres of suction plates adjustable from max. 1,450 mm (57 inch) to min. 560 mm (22 inch)	63.3 (140)	3,500 (7,700)	42500260