



## VACUUM-HANDY VH-1/25

max. 50 kg/110 lbs

### One-man operation for lightweight slabs and short transportation distance

To install non porous slabs. The vacuum suction force is produced by only pressing the device down onto the surface of the slab. Afterwards the slab can be lifted by hand. To release the slab, just a finger tip is necessary to open a simple valve.

Attention: Can only be used on non porous materials nearby the ground level.

- Accurate and quick installation with no gap in-between slabs. Ergonomically good working position for installation.
- Also previously layed slabs can be picked up again.
- Robust seal ring, can be exchanged within seconds without glueing.
- By purchasing of an additional two-man handle VH-2-HG the VH-1/25 can be used for two-men operation.
- The working load limit is then 50 kg (110 lbs).
- Durable surface protection by galvanizing.

VH-1/25



VH-1/25 with VH-2-HG

Type	Diameter mm (in)	Dead Weight kg (lbs)	Working Load Limit/WLL kg (lbs)	Order-Number
VH-1/25	280 (11)	5 (10)	25 / 50 (55 / 110)	52600009

### Accessories:

Type	Description	Dead Weight kg (lbs)	Order-Number
VH-2-HG	Two-man handle for VH-1/25	3 (7)	42600155

### Spare Parts:

Type	Order-Number
Replacement seal	42730008