

Quotations and Data-Sheet

Model		GL-SC-400X	GL-SC-600X	GL-SC-800X	GL-SC-1000X	GL-SC-1200X
Lifting Capacity	kg	400	600	800	1000	1200
Cup Qty	/	4	6	8	10	12
Single Cup Size	mm	300	300	300	300	300
Single Cup Lifting Capacity	kg	100	100	100	100	100
Rotation	/	360° manual rotate				
Tilting	/	90° manual				
Volte	V	DC12				
Charger	V	AC220/110				
Weight	kg	70	90	100	110	120
Sucker Frame Size	mm	850*750*300	1800*900*300	1760*1460*300	1900*1600*300	1900*1600*300
Extension Bar Length	mm	500				
Control System	/	Integrated Control Cabinet and Wired Remote Control				
Package Size	mm	1230*910*390				
G.W	kg	97	110	123	150	163
Unit Price	INR/SET	2,35,000	2,55,000	2,85,000	3,15,000	3,35,000
Terms & Conditions	<ul style="list-style-type: none"> ❖ Price Term: Ex works vadodara. GST and freight Extra ❖ Delivery Time: 15 days upon Advance Payment ❖ Payment Terms: 100% in advance ❖ Quality warranty: 12 Months. Free Spare Parts Replacement ❖ Packing: wooden carton. ❖ Validity: 15days 					

Advantages

- ✓ Sealed cover for components protection, safe and reliable. Usually cooperated with bridge crane to use in glass deep processing and handling job, or with cantilever crane to use in glass curtain wall installation job.
- ✓ Adjustable type, can be changed the position of the suction cup to absorb glass of different shapes and sizes (also can be customized according to the glass size)
- ✓ Manually rotated 360° in the vertical side, and manually rotated 90° in the horizontal side, but taking and releasing by electric.
- ✓ Adopt American THOMAS vacuum pump and high quality maintenance-free battery, no need the air source or power supply during use.
- ✓ Japan Panasonic digital display vacuum pressure switch , battery fuel gauge, clearly monitor the safe use.
- ✓ With vacuum pressure auto supply system, during handling glass, ensure the whole vacuum system maintained at a relatively constant safety pressure value.
- ✓ Equipped with the power-cut but pressure-keeping device and alarm device. If power failure accidently, the pressure-keeping function can extend the handling time and make the use safer.
- ✓ Equipped with 12V backup battery, can be replaced in time to ensure the progress of the project.

