



ANDIG[®]
SYSTEMS



PRODUCT NAME

1131_{BL}



TECHNICAL SPECIFICATIONS

Wavelength	1310 nm / 1550 nm (Single Mode) + VFL + 1625 nm (Live Fiber Test)+ OPM
Measurement	Realtime & Averaging (upto 3 min)
Display	7 inch , 800 x 480 TFT Colour LCD
Event Dead Zone	< 1 mtr
Attenuation Dead zone	< 4 mtrs
Pulse Widths	SM : 5ns, 10ns , 50ns , 100ns, 500ns, 2us , 10us & 20us
Range Settings	SM : 0 – 1 km / 0 – 2 km / 0 – 5 km / 0 – 10 km / 10 – 20 km / 20 – 50 km / 50 – 100 km / 100- 200 km
Data Points	Upto 512,000
Group Index of Refraction	1.40000 to 1.600000
Dynamic Range	32dB (1310nm), 30dB (1550nm) & 30dB(1625nm)
VFL output power	VFL— Output 10mW
Trace File Format	Bellcore , jpeg picture
Trace File Storage Medium	16 GB External Storage , 2 x USB ports

GENERAL SPECIFICATIONS

Size	260 mm x 220 mm x 80 mm
Weight	1.5 kg (without battery & protection cover)
Operating Temperature	-10° C to + 55°C
Storage Temperature	-20° C to + 60°C
Power	7500 mAh Li Ion Battery & Fast Charge Adaptor
Battery Life	10hr (continuous operation)
Recharge Time	8 hrs

1131BL



No. 34/2, 3rd Floor, 10th Cross,
Rajaji Nagar 1st N Block, Bengaluru - 560010
HQ : Bengaluru, Karnataka, IN



+91 99800 97685



andigsystem@gmail.com



www.andigsystems.co.in