

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: H2O Solutions Frosty Foam

PRODUCT USE: Car wash

MANUFACTURED FOR: H2O Solutions LLC.
PO Box 1776
Mt. Juliet, TN 37121-1775

INFORMATION PHONE: 615-714-5240

EMERGENCY PHONE: INFOTRAC
1-800-535-5053 USA & Canada
352-323-3500 International

SECTION 2 - HAZARD(S) IDENTIFICATION

CLASSIFICATION: Skin Corrosion: Category 2
Eye Damage: Category 2B
STOT Single Exposure: Category 1
Flammable Liquid: Category 2

PICTOGRAMS:



GHS ELEMENTS:

SIGNAL WORD: Danger

HAZARD STATEMENT(S): H315 | Causes skin irritation.
H320 | Causes eye irritation.
H370 | Causes damage to organs.
H225 | Highly flammable liquid and vapour.

PRECAUTIONARY STATEMENT(S): P210 | Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233 | Keep container tightly closed.
P240 | Ground/bond container and receiving equipment.
P241 | Use explosion-proof electrical/ventilating/lighting/other equipment.
P242 | Use only non-sparking tools.
P243 | Take precautionary measures against static discharge.
P260 | Do not breathe dust/fume/gas/mist/vapours/spray.
P264 | Wash any exposed body parts thoroughly after handling.
P270 | Do not eat, drink or smoke when using this product.
P280 | Wear protective gloves/protective clothing/eye protection/face protection.
P302 + P352 | IF ON SKIN: Wash with plenty of soap and water.
P303 + P361 + P353 | IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305 + P351 + P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Safety Data Sheet

H2O Solutions Frosty Foam

Page 2 of 7

Version: 1.0011

Revision Date: 02/22/2019

Print Date: 03/29/2019

P307 + P311 | IF exposed: Call a POISON CENTER or doctor/physician.

P321 | Specific treatment (see supplemental first aid instruction on this label if immediate administration of antidote/specific measures/cleansing agent/immediate measures is/are appropriate/required).

P333 + P313 | If skin irritation or rash occurs: Get medical advice/attention.

P337 + P313 | If eye irritation persists: Get medical advice/attention.

P362 | Take off contaminated clothing and wash before reuse.

P370 + P378 | In case of fire: Use appropriate media for extinction if water increases risk.

P403 + P235 | Store in a well-ventilated place. Keep cool.

P405 | Store locked up.

P501 | Dispose of contents/container to appropriate waste disposal entity in accordance with local/regional/national/international regulation.

ADDITIONAL PRECAUTIONS: None Known

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	CAS #	PERCENT
Solvent	67-56-1	70 - 80%
Alkybenzenesulfonic Acid	68584-22-5	< 1.0%
Surfactant	9004-82-4	< 1.0%
Sodium Xylenesulfonate	1300-72-7	< 1.0%
Nonylphenol ethoxylate	127087-87-0	< 1.0%
Surfactant	61789-40-0	< 1.0%
Isopropanolamine Mixture	N/E	< 1.0%
Fragrance	N/E	< 1.0%
2-Butoxyethanol	111-76-2	< 1.0%
Dye Basic Violet 10	81-88-9	< 1.0%

The chemical identity of some or all components is confidential business information (trade secret) and is being withheld as permitted by 29CFR19191200 (i). No other ingredients know to be hazardous.

SECTION 4 - FIRST AID MEASURES

EYES:	Check for and remove contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.
SKIN:	Wash skin surfaces thoroughly after contact. Wash clothing and clean shoes thoroughly before reuse. Get medical attention if irritation develops.
INHALATION:	Move exposed person to fresh air. If breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen clothing. Get medical attention immediately.
INGESTION:	Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

GENERAL: Physicians: No specific treatment. Treat symptomatically. Contact poison treatment specialist if large quantities have been inhaled or ingested.

See Section 11 for exposure symptoms.

SECTION 5 - FIRE FIGHTING MEASURES

FLAMMABILITY: In a fire or if heated, a pressure increase will occur and the container may burst.

EXTINGUISHING MEDIA: Use an extinguishing agent suitable for the surrounding fire.

PROTECTIVE EQUIPMENT: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with full face-piece operated in positive pressure mode.

ADDITIONAL INFORMATION: Thermal decomposition products-carbon monoxide, sulfur oxides, metal oxide/oxides, halogenated compounds.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: No action should be taken involving individual risk or without suitable training. Isolate area. Avoid contact with material. Do not breathe vapors. Provide adequate ventilation. Wear proper personal protective equipment.

ENVIRONMENTAL: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform relevant authorities if the product reaches sewers, waterways or soil.

CONTAINMENT/CLEANUP: Stop leak if without risk. Move containers from spill area. Contain or absorb with inert dry material. Dispose of according to local regulations. See Section 1 for emergency contact information and 13 for waste disposal.

SECTION 7 - HANDLING AND STORAGE

SAFE HANDLING: Wear appropriate personal protective equipment (see Section 8). Eating drinking and smoking should be prohibited. Do not get into eyes or on skin. Do not ingest. Keep containers tightly closed. Do not reuse container.

SAFE STORAGE: Store in accordance with local regulations. Store in original container away from foods, drink and incompatible materials. Keep container tightly closed. Do not store unlabeled. Use appropriate containment.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Apply technical measures to comply with occupational exposure limits. Mechanical ventilation, eyewash stations, showers where necessary.

Safety Data Sheet

H2O Solutions Frosty Foam

Page 4 of 7

Version: 1.0011

Revision Date: 02/22/2019

Print Date: 03/29/2019

EYE PROTECTION:	Safety eye-wear/face shield complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.
RESPIRATORY PROTECTION:	Use a properly fitted air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates necessity. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product & the safe working limits of the chosen respirator.
HAND PROTECTION:	Chemical resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
SKIN PROTECTION:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

COMPONENT	ACGIH TWA ppm	OSHA/NIOSH STEL ppm	OSHA/ACGIH STEL mg/m3
Solvent	200.00	250.00	None
Alkybenzenesulfonic Acid	None	None	0.20
Surfactant	None	None	None
Sodium Xylenesulfonate	None	None	None
Nonylphenol ethoxylate	None	None	None
Surfactant	None	None	None
Isopropanolamine Mixture	5.00	None	None
Fragrance	None	None	None
2-Butoxyethanol	20.00	None	None
Dye Basic Violet 10	None	None	None

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE:	Liquid	UPPER EXPLOSIVE LIMITS:	NA
COLOR:	Red	LOWER EXPLOSIVE LIMITS:	NA
ODOR:	Cherry	VAPOR PRESSURE:	NA
ODOR THRESHOLD:	NA	VAPOR DENSITY:	NA
PH:	NA	RELATIVE DENSITY:	0.00
MELTING POINT:	NA	SOLUBILITY:	Completely Water Soluble
FREEZING POINT:	-255.00 F	PARTITION COEFFICIENT:	NA
BOILING POINT:	0	AUTO-IGNITION TEMPERATURE:	NA
FLASH POINT:	NA	DECOMPOSITION TEMPERATURE:	NA
EVAPORATION RATE:	NA	SPECIFIC GRAVITY:	NA

Safety Data Sheet

H2O Solutions Frosty Foam

Page 5 of 7

Version: 1.0011

Revision Date: 02/22/2019

Print Date: 03/29/2019

FLAMMABILITY: Flammable % VOLATILE: 90.00000
VISCOSITY (cst): 0.00

SECTION 10 - STABILITY AND REACTIVITY

REACTIVITY: HAZARDOUS DECOMPOSITION PRODUCTS
CHEMICAL STABILITY: Stable under normal conditions.
POSSIBILITY OF HAZARDOUS REACTIONS: |POSSIBILITY OF HAZARDOUS REACTIONS
CONDITIONS TO AVOID: Sparks, heat, and open flames.
INCOMPATIBLE MATERIALS: Sulfuric acid, strong inorganic acids, aluminum or lead, oxidizing agents, peroxides, Nitric Acid, Perchloric Acid and Chromium Trioxide.
HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide.

SECTION 11 - TOXICOLOGICAL INFORMATION

ROUTES OF ENTRY: Inhalation Absorption Ingestion

ACUTE EXPOSURE HAZARDS:

EYE CONTACT: May cause irritation, tearing and burning. May also cause eye injuries persisting for several days.
DERMAL: N/E
ORAL: N/E
INHALATION: N/E.

Solvent (CAS No. 67-56-1)
Oral LD50: Rabbit 15800 mg/kg
Surfactant (CAS No. 9004-82-4)
Oral LD50: Rat 1600 mg/kg
Sodium Xylenesulfonate (CAS No. 1300-72-7)
Oral LD50: Rat 5 g/kg
Nonylphenol ethoxylate (CAS No. 127087-87-0)
Oral LD50: Rat 1600 mg/kg
Surfactant (CAS No. 61789-40-0)
Oral LD50: Rat >5000 mg/kg
Isopropanolamine Mixture (CAS No. N/E)
Oral LD50: Rat >2000 mg/kg
2-Butoxyethanol (CAS No. 111-76-2)

Oral LD50: Rat 470 mg/kg

SECTION 12 - ECOLOGICAL INFORMATION

ECOTOXICITY: No data available.

PERSISTENCE & DEGRADABILITY: No data available.

BIOACCUMULATIVE POTENTIAL: No data available.

MOBILITY IN SOIL: No data available.

OTHER ADVERSE EFFECTS: No data available.

Solvent (CAS No. 67-56-1)

Fish LC50: Trout 19000 mg/L 96h

Sodium Xylenesulfonate (CAS No. 1300-72-7)

Fish LC50: Minnow 1000 mg/L 96h

Isopropanolamine Mixture (CAS No. N/E)

Crustacean LC50: >100 mg/L 96h

2-Butoxyethanol (CAS No. 111-76-2)

Crustacean LC50: Daphnia 1818 mg/L 24h

SECTION 13 - DISPOSAL CONSIDERATION

Material that cannot be saved for recovery or recycling should be managed in an appropriate and approved waste facility. Processing, use or contamination of the product may change the waste management options. Waste generators must decide if discarded material is a hazardous waste. State and local disposal regulations may differ from federal disposal definitions. Dispose of container and unused contents in accordance with federal, state and local requirements.

SECTION 14 - TRANSPORT INFORMATION

DOT (US)

UN NUMBER: UN1993

SHIPPING NAME: Flammable Liquid, N.O.S.

TECHNICAL NAME: (Methanol)

HAZARD CLASS: 3

PACKAGING GROUP: II

SECTION 15 - REGULATORY INFORMATION

Safety Data Sheet

H2O Solutions Frosty Foam

Page 7 of 7

Version: 1.0011

Revision Date: 02/22/2019

Print Date: 03/29/2019

SARA 313 COMPONENTS	CAS NO.	% LESS THAN
2-Butoxyethanol	111-76-2	< 1.0%
CALIFORNIA PROP. 65 COMPONENTS	CAS NO.	% LESS THAN
Surfactant	61789-40-0	< 1.0%

SECTION 16 - OTHER INFORMATION

HAZARDOUS MATERIAL INFORMATION SYSTEM (U.S.A.)

Health Hazard	2
Fire Hazard	3
Reactivity	0
Personal Protection	B

Caution: HMIS ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks and 4 representing significant hazards or risks.

- A Safety Glasses
- B Safety Glasses, Gloves
- C Safety Glasses, Gloves, Apron
- D Face Shield, Gloves, Apron
- E Safety Glasses, Gloves, Dust Respirator
- F Safety Glasses, Gloves, Apron, Dust Respirator
- G Safety Glasses, Gloves, Vapor Respirator
- H Splash Goggles, Gloves, Apron, Dust & Vapor Respirator
- I Safety Glasses, Gloves, Dust & Vapor Respirator
- J Splash Goggles, Gloves, Apron, Dust & Vapor Respirator
- K Airline Hood or Mask, Gloves, Full Suit, Boots
- X Consult your supervisor for special handling directions

NATIONAL FIRE PROTECTION ASSOCIATION (U.S.A.)



NFPA warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health, and reactivity hazards of chemicals.

Information on this form is furnished solely for the purpose of compliance with the Occupational Safety and Health Act of 1970 and shall not be used for any other purpose. Use or dissemination of all or any part of this information can be grounds for legal action.

To the best of our knowledge, the information provided in this Safety Data Sheet is accurate as of the date of its issue. However, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE. The information this Safety Data Sheet contains is being given to that material when combined with other material(s) or when used otherwise than as described herein.

In all cases, it is the responsibility of the user to determine the applicability of such information and recommendations and the suitability of any product for its own particular purpose. All materials may represent unknown hazards and should be used with caution.