

# SERIE OCEAN



## D.OCEAN109+ D.OCEAN09

## D.OCEAN112+ D.OCEAN12

|                                             |         |                            |                            |
|---------------------------------------------|---------|----------------------------|----------------------------|
| Alimentazione                               |         |                            |                            |
| Capacità nominale                           | Btu/kW  | 9000(3207~11260)/2,6       | 12000(3412~13648)/3,43     |
| Potenza assorbita                           | W       | 640(240~1380)              | 820(290~1510)              |
| Corrente assorbita                          | A       | 3.8(1.2~8.1)               | 4.7(1.5~9.2)               |
| EER                                         |         | 4,05                       | 4,20                       |
| Capacità nominale                           | Btu/kW  | 9553(3207~11601)/2,8       | (3412~15354)/3,8           |
| Potenza assorbita                           | W       | 660(240~1552)              | 930(290~1720)              |
| Corrente assorbita                          | A       | 4.0(1.2~9.0)               | 5.4(1.5~10.0)              |
| COP                                         |         | 4,25                       | 4,10                       |
| Raffr. stagionale Capacità (pdesignc)       | kW      | 2,6                        | 3,4                        |
| SEER/Classe Efficienza Energetica           |         | 8,5/A+++                   | 8,5/A+++                   |
| Risc. (clima caldo) Capacità (pdesignh)     | kW      |                            |                            |
| SCOP/Classe Efficienza Energetica           |         |                            |                            |
| <b>Unità interna</b>                        |         |                            |                            |
| Portata d'aria max. Raffr./Risc.            | m3/h    | 650/650                    | 650/650                    |
| Liv. Press.Sonora (Turbo/Alta/Med/Bas/Mute) | dB(A)   | 42/39/35/29/24             | 42/39/35/29/24             |
| Dimensioni (LxAxP)                          | mm      | 820×306×210                | 820×306×210                |
| Peso netto/lordo                            | Kg      | 9,5/12                     | 9,5/12                     |
| <b>Unità Esterna</b>                        |         |                            |                            |
| Liv. Press.Sonora/Potenza Sonora            | dB(A)   | 52/62                      | 52/62                      |
| Dimensioni (LxAxP)                          |         | 795×549×305                | 795×549×305                |
| Peso netto/lordo                            | Kg      | 25/28                      | 27/30                      |
| <b>Refrigerante</b>                         |         |                            |                            |
| Tipo/GWP/Quantità precaricata               |         | R32/0.57kg/675/0.385tonnes | R32/0.82kg/675/0.554tonnes |
| <b>Tubazione gas</b>                        |         |                            |                            |
| Lato liquido/Lato gas                       | Pollici | 3/8"/1/4"                  | 3/8"/1/4"                  |
| Max lungh. Tubazioni/dislivello             | m       | 25/10                      | 25/10                      |