



*Make it EZ!*

## Hitch Tool Specifications

Hydraulic Recommendations ..... 20-30 GPM @ 3000 psi

Hydraulic Connection Type ..... 3/4" Flush Face Coupling

Rated Burst Pressure for Hydraulic Connections ..... 15 ksi (103.4 MPa)

Rated Tongue Weight Capacity<sup>1</sup> on Standard Base ..... 6000 lbs (2722 kg)

Rated Tongue Weight Capacity<sup>1</sup> on Fixed Base & Compact Utility Base ..... 2000 lbs (907 kg)

Hydraulic Cylinder Information ..... See Chart Below

Type of Cylinder	Quantity	Bore	Rod Diameter	Stroke	Push <sup>2</sup>	Pull <sup>2</sup>
Clamp	1	2 in 51 mm	1.0 in 25 mm	3.5 in 89 mm	9,425 lbs 41.9 kN	7,069 lbs 31.4 kN

Mass of Double Cylinder Rotating Base ..... 436 lbs (198 kg)

Mass of Compact Utility Base ..... 188 lbs (85 kg)

Mass of Fixed Base ..... 176 lbs (80 kg)

Mass of Hitch Tool (tool head only) ..... 50 lbs (23 kg)

Mounting Method ..... Universal Quick Attach (Customizable)

1. Max Weight Capacity = Machine Operating Capacity – Weight of Attachment  
Should not exceed the rated weight capacity of the attachment
2. Push and Pull are based on 3000 psi at 20-30 GPM