

Dual inlet 25% more effcient heat removal

FEATURES

- Patent Pending Turbulent Liquid Cooling technology for an efficient heat removal
- Lower CPU Temperature for Higher Sustained Processing Speed

No thermal throttling - low CPU temperature

- 25% higher thermal headroom compared to conventional AIO liquid coolers
- Low Noise by fluid dynamic bearing 0.5 Sone at Max Power
- Highly configurable and easy to install
- Supports Intel LGA 3647 single and dual CPU
- 3 Year Warranty
- Money Back Guarantee if not satisfied with order within 30 days

TECHNICAL SPECIFICATIONS

• Water Block Cold Plate Material: Copper

Water Block Dimension: 91 x 87 x 22 mm

Radiator Material: Copper

• Fan Max Speed: 2100 RPM

• Fan Static Pressure: 27 Pa

• Max Air Flow: 114.5 m³/h (per fan)

• Radiator & Fan Unit Dimension:

* Optional 360 mm radiator

391 x 120 x 70 mm

* Optional 240 mm radiator 271 x 120 x 70 mm

• Pump Max Flow Rate: 600 L/h

• Pump Max Pressure Head: 25.49 kPa

• Pump Unit Dimension: 62 x 60 x 48 mm

• Tubing Length:

Distance from Pump to Y-Splitter Inlet: 400 mm Distance from Water Block to Radiator Unit: 560 mm

Weight: 5.0 kg





SYSTEM REQUIREMENTS

• 4 Pin PWM Header

Max Power: 8 W

Voltage: DC 12 V

MOUNTING KIT

• 4x M4-0.7 Mount Screws

• 8x Philip Head Screw M3-0.5 x 6 mm



