## **TOAST NETWORK DIAGRAM**

**⊡to**ast

**NETWORKING AREA CUSTOMER MODEM: TOAST ROUTER: MUST HAVE 1 PORT OPEN** FOR TOAST DEVICES ONLY FOR TOAST INTERNET: Ţ TOAST MINIMUM REQUIREMENTS: \*\*\*\* 15 MB/S DOWNLOAD 5 MB/S UPLOAD TOAST NETWORK SWITCH: FOR TOAST DEVICES ONLY WIRELESS (((●))) ACCESS POINT ... LEGEND: **KITCHEN DISPLAY** WALL MOUNTED FEMALE RJ-45 JACK Ð Ð Ð STANDARD POWER RECEPTICLE with TERMINAL/RECEIPT TERMINAL/RECEIPT **TERMINAL / RECEIPT KITCHEN PRINTER(s)** a 120v ground circuit PRINTER PRINTER PRINTER CAT5e / CAT6 ETHERNET CABLING (RUN BY CUSTOMER) PATCH CABLE (PROVIDED BY TOAST) WIFI DEVICE - NO CABLING REQUIRED Remember, Toast *does not* provide mounting, cabling, or any

form of drilling services, and the cost for those services is not reflected in any Toast quote. Please be aware that failure to follow the instructions outlined here could incur additional fees.