

ASSEMBLING THE

www.manplow.com/assembly-instructions

1. Assemble Leg between Hips

This will be a snug fit. You may need to use tools.

Do not over tighten. This is your Tension Control. You will want the leg to swing up and down with some

resistance. You can adjust tension at any time.





Assembled

Handle Leg

MANPLOW

-HANDLE

ASSEMBLY

PRO

Assembled Boost Bar

Handle Leg Sleve to

2. Handle Leg Sleeves

When adding Boost Bar to existing equipment, remove the blade and handle connectors. Slide Handle Lea Sleeves over bottom of handle legs. With new equipment, assemble Handle Top U and Handle Legs first. Slide the Handle Lea Sleeve over the Handle Lea.

3. Attach blade to Handle Legs

Follow assembly instructions. Hand tighten. Tighten with tools after Cross Bar is attached.

4. Attach the Cross Bar to U Handle

The Cross Bar attaches on the user side (opposite the blade) of the Handle Legs. Follow hardware sequence.

Hardware Sequence

Washer

Saddle Spacer (place flat sides

Curved Washer

Bolt



Lock

Nut






Cross Bar





Handle Leg Sleve /Handle



Boost Mode PIVATED

With the Boost Bar's Foot down. you are in Boost Mode!

The safer way to lift and toss snow!



Boost Mode

Bring the Leg up and over the cross bar until vou're ready to Boost.

Keep the Foot out from under foot!

