

PS-66 BENCH NOTCHER









PS-66 Bench Notcher



The PEXTO PS-66 is the only machine that combines notching and coping in one compact unit. The machine may also be used for shearing strip and box corner tab notching. A machine designed to handle the many small, diversified jobs in the sheet metal shop.

The PS-66 features a worktable with edges machined squared for accurate and convenient gauge setting, reversible upper blades, 4-edge lower blades, and shatterproof finger guard.

No. PS-66 Notcher, Coper, Shear

- Hand Operated
- Bench or Floor Mounted
- Adjustable Gauge Stops
- Replaceable Blades
- Finger Guards

Blades may be mounted for conventional splay cutting, starting at the outside edges, shearing to apex, or for pierce cutting, starting at apex and shearing to outside edges. Pierce cutting permits shearing inside the blank and coping. The PS-66 can cut a full 6" x 6" corner notch in one stroke. Saves the 6" x 6" cut out blank. By removing one frame bolt, will shear or square 6" material of any length.





| PEXTO BENCH NOTCHER SPECIFICATIONS | NO. PS-66 | |
|--|--|--|
| Maximum shearing capacity, mild steel (Splay-cut) | 16ga/1,60mm | |
| Maximum shearing capacity, mild steel (Pierce-cut) | 18ga/1,25mm | |
| Maximum notch | 6 x 6in x 90 degrees 152 x 152mmx 90degrees | |
| Stroke | 3/4in / 19mm | |
| Shearing width (any length) | 6in / 152mm | |
| Shipping Weight | 210lbs./95.5kg | |

| ORDERING GUIDE | CATALOG NO. | SHIPPING WEIGHT |
|---|------------------------|-----------------------------|
| No. PS-66 Pexto Notcher Floor Stand | 145070661 239006010 | 200lbs./91kg 97lbs./44kg |
| Hi-Speed Blade (Upper Blade Set) | 250006604 | 1lb/.4kg |
| Hi-Speed Blade (Lower Blade Set) | 250006603 | 1lb/.4kg |
| No. PS-66 Pexto Notcher with Box Flange Blades Floor Stand | 145070662 239006010 | 200lbs./91kg 97lbs./44kg |
| Box Flange Blades (Upper Blade Set) | 250006606 | 1lb/. 4kg |
| Box Flange Blades (Lower Blade Set) | 250006605 | 1lb/. 4kg |